



PRIORITY
WIRE & CABLE, INC.
9110 U.S.



Utility Wire & Cable

Code Name Reference

| Code Name | Cond. Size | Pg. # | Code Name | Cond. Size | Pg. # | Code Name | Cond. Size | Pg. # | Code Name | Cond. Size | Pg. # |
|------------|------------|-------|-------------|------------|-------|--------------|------------|-------|--------------|------------|-------|
| Aega | 3/0 AWG | 19 | Cairo | 465.4 MCM | 3 | Dachshund | 4 AWG | 17 | Gelding | 336.4 MCM | 20 |
| Akron | 30.58 MCM | 3 | Camellia | 1000 MCM | 2 | Daffodil | 350 MCM | 1 | German-Coach | 4 AWG | 21 |
| Alliance | 246.9 MCM | 3 | Canary | 900 MCM | 6 | Dahlia | 556.5 MCM | 1 | Gladiolus | 1510.5 MCM | 2 |
| Almond | 1/0 AWG | 16 | Canna | 397.5 MCM | 1 | Daisy | 266.8 MCM | 1 | Goldenrod | 954 MCM | 2 |
| Alton | 48.69 MCM | 3 | Canton | 394.5 MCM | 3 | Darien | 559.5 MCM | 3 | Goldentuft | 450 MCM | 1 |
| Ames | 77.47 MCM | 3 | Cardinal | 954 MCM | 6 | Dartmouth | 400 MCM | 26 | Gonzaga | 300 MCM | 26 |
| Amherst | 195.7 MCM | 3 | Carnation | 1431 MCM | 2 | Daumier | 500 MCM | N/A | Gould | 250 MCM | N/A |
| Anaheim | 155.4 MCM | 3 | Cattail | 750 MCM | 2 | Davidson | 3/0 AWG | 28 | Goya | 2/0 AWG | N/A |
| Anona | 336.4 MCM | 16 | Cavolinia | 2/0 AWG | 19 | Degas | 250 MCM | N/A | Grackle | 1192.5 MCM | 6 |
| Appaloosa | 4/0 AWG | 20 | Cenia | 1/0 AWG | 19 | Delgado | 4 AWG | 26 | Grapefruit | 1033.5 MCM | N/A |
| Apple | 6 AWG | 16 | Cerapus | 4/0 AWG | 19 | Dipper | 1351.5 MCM | 6 | Greeley | 927.2 MCM | 3 |
| Apricot | 4 AWG | 16 | Cezanne | 2 AWG | N/A | Doberman | 2 AWG | 17 | Grosbeak | 636 MCM | 6 |
| Arabian | 4 AWG | 21 | Cherrystone | 3/0 AWG | 19 | Dorking | 190.8 MCM | 7 | Grouse | 80.0 MCM | 7 |
| Arbutus | 795 MCM | 2 | Chestnut | 1 AWG | 16 | Dotterel | 176.9 MCM | 7 | Grullo | 2/0 AWG | 20 |
| Arca | 4/0 AWG | 18 | Chickadee | 397.5 MCM | 5 | Dove | 556.5 MCM | 5 | Guinea | 159 MCM | 7 |
| Arch | 2 AWG | N/A | Chihuahua | 6 AWG | 17 | Drake | 795 MCM | 6 | Hackberry | 266.8 MCM | 16 |
| Artemia | 4 AWG | 18 | Chola | 6 AWG | 20 | Dufay | 250 MCM | N/A | Hackney | 4 AWG | 20 |
| Aster | 2/0 AWG | 1 | Choppin | 4/0 AWG | N/A | Duke | 600 MCM | 26 | Haiotis | 6 AWG | 18 |
| Azusa | 123.3 MCM | 3 | Chow | 2 AWG | 17 | Dungeness | 2/0 AWG | 18 | Hals | 350 MCM | N/A |
| Bach | 3/0 AWG | N/A | Chukar | 1780 MCM | 7 | Dyke | 2 AWG | 28 | Handel | 1 AWG | N/A |
| Bard | 8 AWG | 26 | Chutepoke | 850 MCM | 6 | Eagle | 556.5 MCM | 5 | Hanoverian | 3/0 AWG | 20 |
| Barnacles | 4 AWG | 18 | Claffin | 6 AWG | 26 | Earlham | 4/0 Awg | 28 | Harrier | 4 AWG | 17 |
| Bay | 6 AWG | 21 | Clam | 2 AWG | 19 | Echinus | 1/0 Awg | 18 | Harvard | 1/0 AWG | 26 |
| Beaumont | 1113 MCM | 6 | Clemson | 2 AWG | 26 | Egret | 636 MCM | 6 | Hawk | 477 MCM | 5 |
| Beech | 2 AWG | 16 | Clio | 2/0 AWG | 19 | El Greco | 3/0 MCM | N/A | Hawkweed | 1000 MCM | 2 |
| Belgian | 2 AWG | 21 | Clydesdale | 4 AWG | 20 | Elgin | 652.4 MCM | 3 | Hawthorn | 1192.5 MCM | 2 |
| Beloit | 4/0 AWG | 26 | Cochin | 211.3 MCM | 7 | Emory | 500 MCM | 26 | Haydn | 1/0 AWG | N/A |
| Bergen | 1/0 AWG | 27 | Cockle | 2 AWG | 19 | Erskine | 6 AWG | 27 | Heeler | 1/0 AWG | 17 |
| Bittern | 1272 MCM | 6 | Cockscomb | 900 MCM | 2 | Eskimo | 4 AWG | 17 | Hen | 477 MCM | 5 |
| Bitterroot | 2750 MCM | 2 | Collie | 6 AWG | 17 | Everett | 2 AWG | 26 | Heuchera | 650 MCM | 1 |
| Bluebell | 1033.5 MCM | 2 | Columbine | 1351.5 MCM | 2 | Fairfield | 750 MCM | 27 | Hickory | 4 AWG | 16 |
| Bluebird | 2156 AWG | 7 | Conch | 2 AWG | 19 | Falcon | 1590 MCM | 7 | Hippa | 6 AWG | 18 |
| Bluebonnet | 3500 MCM | 2 | Condor | 795 MCM | 6 | Fig | 3/0 AWG | 16 | Hofstra | 250 MCM | 26 |
| Bluejay | 1113 MCM | 6 | Converse | 2/0 AWG | 27 | Filbert | 3/0 AWG | 16 | Holbein | 4/0 AWG | N/A |
| Bobolink | 1431 MCM | 7 | Coot | 795 MCM | 6 | Finch | 1113 MCM | 6 | Hollins | 3/0 AWG | 27 |
| Bosch | 500 MCM | N/A | Coreopsis | 1590 MCM | 2 | Flag | 700 MCM | 1 | Holyoke | 500 MCM | 27 |
| Brahma | 203.2 MCM | 7 | Corot | 4/0 AWG | N/A | Flamingo | 666.6 MCM | 6 | Hornbeam | 4 AWG | N/A |
| Brahms | 2/0 AWG | N/A | Cosmos | 477 MCM | 1 | Flicker | 477 MCM | 5 | Huckleberry | 477 MCM | 16 |
| Brant | 397.5 MCM | 5 | Costena | 1/0 AWG | 20 | Flint | 740.8 MCM | 3 | Hunter | 2/0 AWG | 27 |
| Breadfruit | 636 MCM | N/A | Cowry | 336.4 MCM | 19 | Flustra | 3/0 AWG | 18 | Hurricane | 500 MCM | 20 |
| Brenau | 1/0 AWG | 27 | Cowslip | 2000 MCM | 2 | Fordham | 1000 MCM | 26 | Hyacinth | 500 MCM | 1 |
| Bronco | 336.4 MCM | 20 | Crab | 4 AWG | 18 | French-Coach | 6 AWG | 21 | Ibis | 397.5 MCM | 5 |
| Bruegel | 3/0 AWG | N/A | Crayfish | 2/0 AWG | 18 | Fulgar | 3/0 AWG | 18 | Iris | 2 AWG | 1 |
| Buckeye | 4/0 AWG | 16 | Criollo | 1/0 AWG | 20 | Furman | 700 MCM | 26 | Ives | 2/0 AWG | N/A |
| Bull | 1/0 AWG | 17 | Cuckoo | 795 MCM | 6 | Fusus | 4 AWG | 18 | Janthina | 1/0 AWG | 19 |
| Bunting | 1192.5 MCM | 6 | Curlew | 1033.5 MCM | 6 | Gable | 1/0 AWG | N/A | Jessamine | 1750 MCM | 2 |
| Butte | 312.8 MCM | 3 | Cuttlefish | 4/0 AWG | 19 | Gammarus | 1/0 AWG | 18 | Joist | 1/0 AWG | N/A |
| Butternut | 4 AWG | 16 | Cyclops | 2/0 AWG | 18 | Gannet | 666.6 MCM | 6 | Joree | 2515 MCM | 7 |

1-800-945-5542

www.PriorityWire.com

Code Name Reference

| Code Name | Cond. Size | Pg. # | Code Name | Cond. Size | Pg. # | Code Name | Cond. Size | Pg. # | Code Name | Cond. Size | Pg. # |
|-------------|------------|-------|-------------|------------|-------|---------------|------------|-------|--------------|------------|-------|
| Kenyon | 1 AWG | 26 | Nasturtium | 715.5 MCM | 2 | Pratt | 250 MCM | 27 | Starling | 715.5 MCM | 6 |
| Kingbird | 636 MCM | 6 | Neritina | 1/0 AWG | 19 | Prawn | 4 AWG | 18 | Stephens | 2 AWG | 27 |
| Kiwi | 2167 MCM | 7 | Niagara | 350 MCM | 28 | Princeton | 6 AWG | 26 | Stilt | 715.5 MCM | 6 |
| Lafayette | 2/0 AWG | 28 | Notre Dame | 1/0 AWG | 28 | Purdue | 1/0 AWG | 28 | Strauss | 750 MCM | N/A |
| Lapwing | 1590 MCM | 7 | Nuthatch | 1510.5 MCM | 7 | Purpura | 1/0 AWG | 19 | Strombus | 4 AWG | 19 |
| Lark | 397.5 MCM | 5 | Oilnut | 1/0 AWG | N/A | Quail | 2/0 AWG | 5 | Suffolk | 3/0 AWG | 20 |
| Larkspur | 1033.5 MCM | 2 | Oldenburg | 4/0 AWG | 20 | Quince | 1/0 AWG | 16 | Swan | 4 AWG | 5 |
| Laurel | 266.8 MCM | 1 | Olive | 4/0 AWG | 16 | Rail | 954 MCM | 6 | Swanate | 4 AWG | 5 |
| Leda | 1/0 AWG | 18 | Orange | 2/0 AWG | 16 | Ramapo | 2 AWG | 27 | Swarthmore | 3/0 AWG | 28 |
| Leghorn | 134.6 MCM | 7 | Orchid | 636 MCM | 1 | Ranella | 1/0 AWG | 19 | Sweetbriar | 4/0 AWG | 27 |
| Lepas | 4/0 AWG | 18 | Oriole | 336.4 MCM | 5 | Rapheal | 1/0 AWG | N/A | Swift | 636 MCM | 6 |
| Les Boules | 864.9 MCM | 6 | Ortolan | 1033.5 MCM | 6 | Ravel | 3/0 AWG | N/A | Syracuse | 2/0 AWG | 28 |
| Lilac | 795 MCM | 2 | Osprey | 556.5 MCM | 5 | Raven | 1/0 AWG | 5 | Syringa | 477 MCM | 1 |
| Limpet | 336.4 MCM | 19 | Ostrich | 300 MCM | 5 | Razor | 4/0 AWG | 19 | Teal | 605 MCM | 6 |
| Lindin | 2 AWG | N/A | Oxlip | 4/0 AWG | 1 | Redwing | 715.5 MCM | 6 | Tern | 795 MCM | 6 |
| Linnet | 336.4 MCM | 5 | Oyster | 4 AWG | 18 | Rider | 500 AWG | 27 | Terrier | 4 AWG | 17 |
| Lippizaner | 336.4 MCM | 20 | Palomino | 2 AWG | 20 | Robin | 1 AWG | 5 | Thoroughbred | 2/0 AWG | 21 |
| Listz | 1 AWG | N/A | Paludina | 6 AWG | 19 | Rockland | 3/0 AWG | 27 | Thrasher | 2312 MCM | 7 |
| Lully | 500 MCM | N/A | Pansy | 1 AWG | 1 | Rook | 636 AWG | 6 | Trillium | 3000 MCM | 2 |
| Lupine | 2500 MCM | 2 | Parakeet | 556.5 MCM | 5 | Rose | 4 AWG | 1 | Triton | 2/0 AWG | 19 |
| Magnolia | 954 MCM | 2 | Parrot | 1510.5 MCM | 7 | Rubens | 2/0 AWG | N/A | Trotter | 3/0 AWG | 21 |
| Malamute | 1/0 AWG | 17 | Partridge | 266.8 MCM | 5 | Ruddy | 900 MCM | 6 | Tufts | 3/0 AWG | 26 |
| Mallard | 795 MCM | 6 | Patella | 6 AWG | 18 | Runcina | 2/0 AWG | 19 | Tulip | 336.4 MCM | 1 |
| Marigold | 113 MCM | 2 | Paw Paw | 556.5 MCM | 16 | Rust | 250 MCM | 28 | Tulsa | 4 AWG | 28 |
| Martin | 1351.5 MCM | 7 | Peach | 2 AWG | 16 | Rutgers | 350 MCM | 26 | Turkey | 6 AWG | 5 |
| McNeil | 350 MCM | N/A | Peachbell | 6 AWG | 1 | Sagebrush | 2250 MCM | 2 | Valerian | 250 MCM | 1 |
| Meadowsweet | 600 MCM | 1 | Peacock | 605 MCM | 6 | Sandcrab | 1/0 AWG | 18 | Vassar | 4 AWG | 27 |
| Melita | 3/0 AWG | 19 | Pear | 4 AWG | 16 | Sanddollar | 3/0 AWG | 19 | Verbena | 700 MCM | 1 |
| Mercer | 4 AWG | 26 | Pecan | 2/0 AWG | 16 | Scallop | 4 AWG | 19 | Violet | 715.5 MCM | 1 |
| Merlin | 336.4 MCM | 5 | Pekingese | 6 AWG | 17 | Schnauzer | 2 AWG | 17 | Vizsla | 6 AWG | 17 |
| Minex | 6 AWG | 18 | Pelican | 477 MCM | 5 | Scoter | 636 MCM | 6 | Voluta | 6 AWG | 19 |
| Minorca | 110.8 MCM | 7 | Penguin | 4/0 AWG | 5 | Setter | 6 AWG | 17 | Wake Forest | 4/0 AWG | 28 |
| Mistletoe | 556.5 MCM | 1 | Peony | 300 MCM | 1 | Sewanee | 750 MCM | 26 | Walking | 4/0 AWG | 21 |
| Molles | 397.5 MCM | N/A | Percheron | 2/0 AWG | 20 | Shellbark | 3/0 AWG | N/A | Walnut | 6 AWG | 16 |
| Monet | 1 AWG | N/A | Periwinkle | 4 AWG | 19 | Shepherd | 6 AWG | 17 | Waxwing | 266.8 MCM | 5 |
| Monmouth | 4/0 AWG | 27 | Persimmon | 2/0 AWG | N/A | Shetland | 1/0 AWG | 21 | Wesleyan | 350 AWG | 27 |
| Moreau | 250 MCM | N/A | Petrel | 101.8 MCM | 7 | Shrimp | 2 AWG | 18 | Whelk | 4 AWG | 19 |
| Morgan | 4 AWG | 20 | Petunia | 750 MCM | 2 | Sipho | 2/0 AWG | 18 | Whippet | 4 AWG | 17 |
| Morochuca | 6 AWG | 20 | Pheasant | 1272 MCM | 6 | Slippery Rock | 350 MCM | 28 | Windham | 750 MCM | 28 |
| Mozart | 4/0 AWG | N/A | Phlox | 3/0 AWG | 1 | Snail | 1/0 AWG | 19 | Wittenberg | 2 AWG | 28 |
| Mulberry | 266.8 MCM | 16 | Pigeon | 3/0 AWG | 5 | Snapdragon | 900 MCM | 2 | Wofford | 500 MCM | 28 |
| Murex | 1/0 AWG | 19 | Pignut | 2 AWG | 16 | Sneezewart | 250 MCM | 1 | Wood Duck | 605 MCM | 6 |
| Mursia | 3/0 AWG | 19 | Pinto | 4 AWG | 20 | Soffit | 1 AWG | N/A | Yale | 2/0 AWG | 26 |
| Mussel | 2 AWG | 19 | Planetree | 4/0 AWG | N/A | Solaster | 2 AWG | 18 | Zinnia | 500 MCM | 1 |
| Mustang | 2 AWG | 20 | Plover | 1431 AWG | 7 | Spaniel | 4 AWG | 17 | Zuzara | 4/0 AWG | 19 |
| Nannynose | 336.4 MCM | 19 | Pomegranate | 4/0 AWG | N/A | Sparate | 2 AWG | 5 | | | |
| Narcissus | 1272 MCM | 2 | Poppy | 1/0 AWG | 1 | Sparrow | 2 AWG | 5 | | | |
| Nassa | 2/0 AWG | 19 | Portunus | 4/0 AWG | 19 | Squab | 605 MCM | 6 | | | |

1-800-945-5542

www.PriorityWire.com

Table of Contents

Section I. Bare Aluminum Transmission & Distribution

| | |
|-------------------------|-------|
| AAC..... | 1-2 |
| AAAC..... | 3 |
| ACAR..... | 4 |
| ACSR..... | 5-7 |
| Aluminum Tie Wire | 7 |
| ACSR/AW..... | 8-9 |
| ACSR/TP | 10-12 |
| ACSS | 13-14 |
| ACSS/TW | 15 |

Section II. Aluminum 600 Volt Overhead

| | |
|------------------------------|-------|
| Covered Line Wire | 16 |
| Duplex Service Drop | 17 |
| Triplex Service Drop | 18-19 |
| Quadruplex Service Drop..... | 20-21 |

Section III. Primary URD Cable 15KV-35KV

| | |
|-------------------------|-------|
| 15 KV TR-XLPE URD | 22-23 |
| 25 KV TR-XLPE URD | 23-24 |
| 35 KV TR-XLPE URD | 24-25 |

Section IV. Aluminum 600 Volt URD

| | |
|----------------------------|----|
| Single Conductor..... | 26 |
| Duplex Conductor..... | 26 |
| Triplex Conductor | 27 |
| Quadruplex Conductor | 28 |
| 8000 Series | 29 |

Section V. Control Cable

| | |
|------------------------------------|-------|
| General Purpose Control Cable..... | 30-31 |
| XLP/CPE Control Cable | 32-33 |

Section VI. Specialty

| | |
|--|-------|
| Riser Wire (Solid and Stranded) / Jumper Cable / Clear Grounding Cable | 34 |
| RHH/RHW-2/USE-2/(Copper and Aluminum)..... | 35-37 |
| Bare and Tinned Copper | 38 |
| Aluminum Clad Steel Wire..... | 39 |
| Ground Rods | 40-41 |
| Ground Rod Accessories..... | 42 |
| Spacer Cable FR-NP | 43-45 |
| Galvanized Guy Wire..... | 46 |
| Tap Wire..... | 46 |
| Generator Cable..... | 47-48 |
| Tracer Wire | 49-50 |
| XLPE/CPE Instrumentation Cable..... | 51 |
| Shielded Tray Cable | 52 |
| Fiber Optic Line Card | 53 |
| Line Card | 54 |



AAC - All Aluminum Conductor

APPLICATION: Stranded 1350-H19 aluminum conductors are used for primary and secondary transmission and distribution.

Class AA is for bare conductors used in overhead lines.

Class A is for conductors to be covered with weather-resistant materials and for bare conductors where greater flexibility is required. Class is an indication of relative conductor flexibility, AA being the least flexible.

SPECIFICATIONS: AAC bare conductors meet or exceed the following ASTM specifications:

B-230 Aluminum 1350-H19 Wire for Electrical Purposes.

B-231 Concentric-Lay-Stranded Aluminum 1350 Conductors.

| Code Word | Conductor Size | Stranding | | Diameter | | Cross Sectional Area | Weight | Rated Breaking Strength | Resistance** | | Ampacity* |
|-------------|----------------|--------------|-------|---------------|-------------|----------------------|---------|-------------------------|--------------|-----------|-----------|
| | | No. of Wires | Class | Indiv. Strand | Comp. Cable | | | | DC @ 20°C | AC @ 75°C | |
| | AWG/kcmil | | | inches | inches | Sq. In. | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps |
| Peachbell | 6 | 7 | A | 0.0612 | 0.184 | 0.0206 | 25 | 563 | 0.6580 | 0.8050 | 103 |
| Rose | 4 | 7 | A | 0.0772 | 0.232 | 0.0328 | 39 | 881 | 0.4140 | 0.5060 | 138 |
| Iris | 2 | 7 | AA,A | 0.0974 | 0.292 | 0.0522 | 62 | 1,350 | 0.2600 | 0.3180 | 185 |
| Pansy | 1 | 7 | AA,A | 0.1093 | 0.328 | 0.0657 | 79 | 1,640 | 0.2070 | 0.2520 | 214 |
| Poppy | 1/0 | 7 | AA,A | 0.1228 | 0.368 | 0.0829 | 99 | 1,990 | 0.1640 | 0.2000 | 247 |
| Aster | 2/0 | 7 | AA,A | 0.1379 | 0.414 | 0.1045 | 125 | 2,510 | 0.1300 | 0.1590 | 286 |
| Phlox | 3/0 | 7 | AA,A | 0.1548 | 0.464 | 0.1318 | 158 | 3,040 | 0.1030 | 0.1260 | 331 |
| Oxlip | 4/0 | 7 | AA,A | 0.1739 | 0.522 | 0.1663 | 199 | 3,830 | 0.0817 | 0.0999 | 383 |
| Sneezewart | 250 | 7 | AA | 0.1890 | 0.567 | 0.1964 | 235 | 4,520 | 0.0691 | 0.0846 | 425 |
| Valerian | 250 | 19 | A | 0.1147 | 0.574 | 0.1964 | 235 | 4,660 | 0.0691 | 0.0846 | 425 |
| Daisy | 266.8 | 7 | AA | 0.1953 | 0.586 | 0.2095 | 251 | 4,830 | 0.0648 | 0.0793 | 443 |
| Laurel | 266.8 | 19 | A | 0.1185 | 0.593 | 0.2095 | 251 | 4,970 | 0.0648 | 0.0793 | 444 |
| Peony | 300 | 19 | A | 0.1257 | 0.629 | 0.2358 | 281 | 5,480 | 0.0578 | 0.0706 | 478 |
| Tulip | 336.4 | 19 | A | 0.1331 | 0.666 | 0.2644 | 316 | 6,150 | 0.0514 | 0.0630 | 513 |
| Daffodil | 350 | 19 | A | 0.1357 | 0.679 | 0.2749 | 329 | 6,390 | 0.0494 | 0.0605 | 526 |
| Canna | 397.5 | 19 | AA,A | 0.1447 | 0.724 | 0.3122 | 373 | 7,110 | 0.0435 | 0.0534 | 570 |
| Goldentuft | 450 | 19 | AA | 0.1539 | 0.769 | 0.3534 | 422 | 7,890 | 0.0384 | 0.0472 | 616 |
| Cosmos | 477 | 19 | AA | 0.1584 | 0.793 | 0.3746 | 448 | 8,360 | 0.0362 | 0.0445 | 639 |
| Syringa | 477 | 37 | A | 0.1135 | 0.795 | 0.3746 | 448 | 8,690 | 0.0362 | 0.0445 | 639 |
| Zinnia | 500 | 19 | AA | 0.1622 | 0.811 | 0.3927 | 469 | 8,760 | 0.0346 | 0.0425 | 658 |
| Hyacinth | 500 | 37 | A | 0.1162 | 0.813 | 0.3924 | 469 | 9,110 | 0.0346 | 0.0425 | 658 |
| Dahlia | 556.5 | 19 | AA | 0.1711 | 0.856 | 0.4371 | 522 | 9,750 | 0.0311 | 0.0382 | 703 |
| Mistletoe | 556.5 | 37 | A | 0.1226 | 0.858 | 0.4371 | 522 | 9,940 | 0.0311 | 0.0382 | 704 |
| Meadowsweet | 600 | 37 | AA,A | 0.1273 | 0.891 | 0.4712 | 563 | 10,700 | 0.0288 | 0.0355 | 738 |
| Orchid | 636 | 37 | AA,A | 0.1311 | 0.918 | 0.4995 | 597 | 11,400 | 0.0272 | 0.0335 | 765 |
| Heuchera | 650 | 37 | AA | 0.1326 | 0.928 | 0.5105 | 610 | 11,600 | 0.0266 | 0.0328 | 775 |
| Verbena | 700 | 37 | AA | 0.1375 | 0.963 | 0.5498 | 657 | 12,500 | 0.0247 | 0.0305 | 812 |
| Flag | 700 | 61 | A | 0.1071 | 0.964 | 0.5498 | 657 | 12,900 | 0.0247 | 0.0305 | 812 |
| Violet | 715.5 | 37 | AA | 0.1391 | 0.974 | 0.5623 | 672 | 12,800 | 0.0242 | 0.0299 | 823 |

(Continued on page 2)

1-800-945-5542

www.PriorityWire.com



AAC - All Aluminum Conductor

| Code Word | Conductor Size | Stranding | | Diameter | | Cross Sectional Area | Weight | Rated Breaking Strength | Resistance** | | Ampacity* |
|------------|----------------|--------------|-------|---------------|-------------|----------------------|---------|-------------------------|--------------|-----------|-----------|
| | | No. of Wires | Class | Indiv. Strand | Comp. Cable | | | | DC @ 20°C | AC @ 75°C | |
| | AWG/kcmil | | | inches | inches | Sq. In. | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps |
| Nasturtium | 715.5 | 61 | A | 0.1083 | 0.975 | 0.5619 | 672 | 13,100 | 0.0242 | 0.0299 | 823 |
| Petunia | 750 | 37 | AA | 0.1424 | 0.997 | 0.5893 | 705 | 13,100 | 0.0230 | 0.0286 | 847 |
| Cattail | 750 | 61 | A | 0.1109 | 0.998 | 0.5892 | 704 | 13,500 | 0.0230 | 0.0286 | 847 |
| Arbutus | 795 | 37 | AA | 0.1466 | 1.026 | 0.6245 | 746 | 13,900 | 0.0217 | 0.0271 | 878 |
| Lilac | 795 | 61 | A | 0.1142 | 1.028 | 0.6248 | 746 | 14,300 | 0.0217 | 0.0270 | 879 |
| Cockscomb | 900 | 37 | AA | 0.1560 | 1.092 | 0.7072 | 845 | 15,400 | 0.0192 | 0.0239 | 948 |
| Snapdragon | 900 | 61 | A | 0.1215 | 1.094 | 0.7073 | 845 | 15,900 | 0.0192 | 0.0239 | 948 |
| Magnolia | 954 | 37 | AA | 0.1606 | 1.124 | 0.7495 | 896 | 16,400 | 0.0181 | 0.0226 | 982 |
| Goldenrod | 954 | 61 | A | 0.1251 | 1.126 | 0.7498 | 896 | 16,900 | 0.0181 | 0.0226 | 983 |
| Hawkweed | 1000 | 37 | AA | 0.1644 | 1.151 | 0.7854 | 939 | 17,200 | 0.0173 | 0.0216 | 1,010 |
| Camellia | 1000 | 61 | A | 0.1280 | 1.152 | 0.7849 | 939 | 17,700 | 0.0173 | 0.0216 | 1,011 |
| Bluebell | 1033.5 | 37 | AA | 0.1671 | 1.170 | 0.8114 | 970 | 17,700 | 0.0167 | 0.0210 | 1,031 |
| Larkspur | 1033.5 | 61 | A | 0.1302 | 1.172 | 0.8122 | 970 | 18,300 | 0.0167 | 0.0210 | 1,032 |
| Marigold | 1113 | 61 | AA,A | 0.1351 | 1.216 | 0.8744 | 1,045 | 19,700 | 0.0155 | 0.0195 | 1,079 |
| Hawthorn | 1192.5 | 61 | AA,A | 0.1398 | 1.258 | 0.9366 | 1,119 | 21,100 | 0.0145 | 0.0183 | 1,124 |
| Narcissus | 1272 | 61 | AA,A | 0.1444 | 1.300 | 0.9990 | 1,194 | 22,000 | 0.0136 | 0.0173 | 1,169 |
| Columbine | 1351.5 | 61 | AA,A | 0.1489 | 1.340 | 1.0610 | 1,269 | 23,400 | 0.0128 | 0.0163 | 1,212 |
| Carnation | 1431 | 61 | AA,A | 0.1532 | 1.379 | 1.1244 | 1,343 | 24,300 | 0.0121 | 0.0155 | 1,253 |
| Gladiolus | 1510.5 | 61 | AA,A | 0.1574 | 1.417 | 1.1869 | 1,418 | 25,600 | 0.0144 | 0.0147 | 1,294 |
| Coreopsis | 1590 | 61 | AA | 0.1614 | 1.454 | 1.2490 | 1,493 | 27,000 | 0.0109 | 0.0141 | 1,333 |
| Jessamine | 1750 | 61 | AA | 0.1694 | 1.525 | 1.3748 | 1,643 | 29,700 | 0.0099 | 0.0129 | 1,408 |
| Cowslip | 2000 | 91 | A | 0.1482 | 1.630 | 1.5710 | 1,877 | 34,200 | 0.0086 | 0.0115 | 1,518 |
| Sagebrush | 2250 | 91 | A | 0.1572 | 1.729 | 1.7670 | 2,131 | 37,500 | 0.0078 | 0.0105 | 1,612 |
| Lupine | 2500 | 91 | A | 0.1657 | 1.823 | 1.9640 | 2,370 | 41,900 | 0.0070 | 0.0097 | 1,706 |
| Bitterroot | 2750 | 91 | A | 0.1739 | 1.913 | 2.1600 | 2,607 | 46,100 | 0.0064 | 0.0090 | 1,793 |
| Trillium | 3000 | 127 | A | 0.1537 | 1.998 | 2.3564 | 2,844 | 50,300 | 0.0058 | 0.0083 | 1,874 |
| Bluebonnet | 3500 | 127 | A | 0.1660 | 2.158 | 2.7490 | 3,350 | 58,700 | 0.0050 | 0.0076 | 2,024 |

All values are nominal and subject to correction

* Current ratings are based on 75°C conductor temperature, 25°C ambient, 2ft/s wind, in sun, .05 coefficients of emissivity and absorption.

** Resistance is calculated using ASTM standard increments of stranding and metal conductivity of 61.2% IACS, AC resistance at 60 Hz.

1-800-945-5542

www.PriorityWire.com



AAAC - All Aluminum Alloy (6201) Conductor

APPLICATION: Bare overhead conductor used for primary and secondary transmission and distribution. Designed utilizing a high-strength aluminum alloy to achieve a high strength-to-weight ratio; better sag characteristics. AAAC has higher resistance to corrosion than ACSR.

CONSTRUCTION: Standard 6201-T81 high strength aluminum conductors, conforming to ASTM specification B399, are concentric-lay-stranded, similar in construction and appearance to 1350 grade aluminum conductors. Conductors of the 6201-T81 alloy have a greater resistance to abrasion than conductors of 1350-H19 grade aluminum.

SPECIFICATIONS: AAAC bare conductor meets or exceeds the following ASTM specifications:

B-398 Aluminum Alloy 6201-T81 and 6201-T83 Wire for Electrical Purposes

B-399 Concentric-Lay-Stranded Aluminum Alloy 6201-T81 Conductors

RUS ACCEPTED

| Code Word | Conductor Size | No. of Wires | Equivalent ACSR | | Diameter | | Cross Sectional Area | Weight | Rated Breaking Strength | Resistance** | | Ampacity* |
|-----------|----------------|--------------|-----------------|-----------|---------------|-------------|----------------------|---------|-------------------------|--------------|-----------|-----------|
| | | | Size | Stranding | Indiv. Strand | Comp. Cable | | | | DC @ 20°C | AC @ 75°C | |
| | kcmil | | AWG/kcmil | AL/Steel | inches | inches | Sq. In. | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps |
| Akron | 30.58 | 7 | 6 | 6/1 | 0.0661 | 0.1980 | 0.0240 | 29 | 1,110 | 0.6588 | 0.7850 | 107 |
| Alton | 48.69 | 7 | 4 | 6/1 | 0.0834 | 0.2500 | 0.0382 | 45 | 1,760 | 0.4139 | 0.4930 | 143 |
| Ames | 77.47 | 7 | 2 | 6/1 | 0.1052 | 0.3160 | 0.0608 | 72 | 2,800 | 0.2601 | 0.3100 | 191 |
| Azusa | 123.3 | 7 | 1/0 | 6/1 | 0.1327 | 0.3980 | 0.0968 | 115 | 4,270 | 0.1635 | 0.1950 | 256 |
| Anaheim | 155.4 | 7 | 2/0 | 6/1 | 0.1490 | 0.4470 | 0.1221 | 145 | 5,390 | 0.1297 | 0.1540 | 296 |
| Amherst | 195.7 | 7 | 3/0 | 6/1 | 0.1672 | 0.5020 | 0.1537 | 183 | 6,790 | 0.1030 | 0.1230 | 342 |
| Alliance | 246.9 | 7 | 4/0 | 6/1 | 0.1878 | 0.5630 | 0.1939 | 230 | 8,560 | 0.0816 | 0.0973 | 395 |
| Butte | 312.8 | 19 | 266.8 | 26/7 | 0.1283 | 0.6420 | 0.2456 | 292 | 10,500 | 0.0644 | 0.0769 | 460 |
| Canton | 394.5 | 19 | 336.4 | 26/7 | 0.1441 | 0.7210 | 0.3098 | 368 | 13,300 | 0.0511 | 0.0610 | 532 |
| Cairo | 465.4 | 19 | 397.5 | 26/7 | 0.1565 | 0.7830 | 0.3655 | 434 | 15,600 | 0.0433 | 0.0518 | 590 |
| Darien | 559.5 | 19 | 477.0 | 26/7 | 0.1716 | 0.8580 | 0.4394 | 522 | 18,800 | 0.0360 | 0.0420 | 663 |
| Elgin | 652.4 | 19 | 556.5 | 26/7 | 0.1853 | 0.9270 | 0.5124 | 608 | 21,900 | 0.0309 | 0.0371 | 729 |
| Flint | 740.8 | 37 | 636.0 | 26/7 | 0.1414 | 0.9910 | 0.5818 | 691 | 24,400 | 0.0272 | 0.0327 | 790 |
| Greeley | 927.2 | 37 | 795.0 | 26/7 | 0.1583 | 1.1080 | 0.7282 | 865 | 30,500 | 0.0217 | 0.0263 | 908 |

All values are nominal and subject to correction

* Current ratings are based on 75°C conductor temperature, 25°C ambient, 2ft/s wind, in sun, .05 coefficients of emissivity and absorption.

** Resistance is calculated using ASTM standard increments of stranding and metal conductivity of 52.5% IACS, AC resistance at 60 Hz.

1-800-945-5542

www.PriorityWire.com



ACAR - Aluminum Conductor Aluminum Reinforced

APPLICATION: Bare overhead conductor used as transmission cable and as primary and secondary distribution cable. A good strength-to-weight ratio makes ACAR applicable where both ampacity and strength are prime considerations in line design; for equal weight, ACAR offers higher strength and ampacity than ACSR.

CONSTRUCTION: Aluminum alloy 1350--H19 wires, concentrically stranded around an aluminum alloy 6201 core. Although the alloy strands generally comprise the core of the cable, in some constructions they are distributed in layers throughout the aluminum alloy 1350-H19 strands.

SPECIFICATIONS: ACAR bare conductor meets or exceeds the following ASTM specifications:

B-230 Aluminum 1350-H19 Wire for Electrical Purposes

B-398 Aluminum-Alloy 6201-T81 Wire for Electrical Purposes

B-524 Concentric-Lay-Stranded Aluminum Conductors, Aluminum Alloy Reinforced (ACAR, 1350/6201)

| Conductor Size | Stranding | Diameter (in) | | Comp. Cable | Weight lbs/kft | Rated Strength lbs | Resistance** | | Allowable Ampacity* amps |
|----------------|-----------|-------------------|--------|-------------|-------------------|-----------------------|-----------------------|-----------------------|-----------------------------|
| | | Individual Strand | | | | | DC @ 20°C Ohms/kft | AC @ 75°C Ohms/kft | |
| kcmil | 1350/6201 | 1350 | 6201 | | | | | | |
| 355.0 | 12/7 | 0.1367 | 0.1367 | 0.683 | 332 | 8,500 | 0.0514 | 0.0624 | 519 |
| 465.9 | 12/7 | 0.1566 | 0.1566 | 0.783 | 436 | 11,000 | 0.0392 | 0.0477 | 616 |
| 503.6 | 12/7 | 0.1628 | 0.1628 | 0.814 | 471 | 11,900 | 0.0362 | 0.0441 | 646 |
| 653.1 | 12/7 | 0.1854 | 0.1854 | 0.927 | 611 | 15,400 | 0.0279 | 0.0342 | 760 |
| 739.8 | 30/7 | 0.1414 | 0.1414 | 0.99 | 693 | 15,300 | 0.0240 | 0.0296 | 831 |
| 739.8 | 18/19 | 0.1414 | 0.1414 | 0.99 | 692 | 18,800 | 0.0252 | 0.0308 | 814 |
| 853.7 | 30/7 | 0.1519 | 0.1519 | 1.063 | 799 | 17,500 | 0.0208 | 0.0257 | 907 |
| 853.7 | 18/19 | 0.1519 | 0.1519 | 1.063 | 798 | 21,500 | 0.0218 | 0.0268 | 890 |
| 927.2 | 30/7 | 0.1583 | 0.1583 | 1.108 | 868 | 19,000 | 0.0192 | 0.0238 | 955 |
| 927.2 | 18/19 | 0.1583 | 0.1583 | 1.108 | 867 | 23,400 | 0.0201 | 0.0247 | 936 |
| 1024.5 | 30/7 | 0.1664 | 0.1664 | 1.165 | 959 | 20,900 | 0.0173 | 0.0216 | 1,015 |
| 1024.5 | 18/19 | 0.1664 | 0.1664 | 1.165 | 958 | 25,800 | 0.0182 | 0.0225 | 995 |
| 1081.0 | 30/7 | 0.1709 | 0.1709 | 1.196 | 1,012 | 22,100 | 0.0164 | 0.0205 | 1,048 |
| 1081.0 | 18/19 | 0.1709 | 0.1709 | 1.196 | 1,011 | 27,200 | 0.0172 | 0.0213 | 1,028 |
| 1109.0 | 30/7 | 0.1731 | 0.1731 | 1.212 | 1,038 | 22,700 | 0.0160 | 0.0200 | 1,065 |
| 1109.0 | 18/19 | 0.1731 | 0.1731 | 1.212 | 1,037 | 27,900 | 0.0168 | 0.0208 | 1,044 |
| 1172.0 | 30/7 | 0.1780 | 0.1780 | 1.246 | 1,097 | 24,000 | 0.0152 | 0.0190 | 1,101 |
| 1172.0 | 18/19 | 0.1780 | 0.1780 | 1.246 | 1,096 | 29,500 | 0.0159 | 0.0198 | 1,080 |
| 1197.0 | 30/7 | 0.1799 | 0.1799 | 1.259 | 1,121 | 24,500 | 0.0148 | 0.0187 | 1,115 |
| 1197.0 | 18/19 | 0.1799 | 0.1799 | 1.259 | 1,119 | 30,200 | 0.0156 | 0.0194 | 1,094 |
| 1280.0 | 30/7 | 0.1860 | 0.1860 | 1.302 | 1,199 | 26,200 | 0.0139 | 0.0175 | 1,160 |
| 1280.0 | 18/19 | 0.1860 | 0.1860 | 1.302 | 1,197 | 32,200 | 0.0146 | 0.0182 | 1,139 |
| 1361.0 | 42/19 | 0.1494 | 0.1494 | 1.344 | 1,274 | 30,300 | 0.0133 | 0.0168 | 1,196 |
| 1527.0 | 42/19 | 0.1582 | 0.1582 | 1.424 | 1,429 | 33,600 | 0.0118 | 0.0151 | 1,314 |
| 1703.0 | 42/19 | 0.1671 | 0.1671 | 1.504 | 1,594 | 37,500 | 0.0106 | 0.0137 | 1,363 |
| 1933.0 | 42/19 | 0.1780 | 0.1780 | 1.602 | 1,809 | 42,500 | 0.00936 | 0.0123 | 1,465 |
| 2267.0 | 42/19 | 0.1928 | 0.1928 | 1.735 | 2,142 | 49,900 | 0.00806 | 0.0108 | 1,594 |
| 2493.0 | 72/19 | 0.1655 | 0.1655 | 1.821 | 2,357 | 50,400 | 0.00722 | 0.0099 | 1,687 |
| 2493.0 | 54/37 | 0.1655 | 0.1655 | 1.821 | 2,355 | 57,600 | 0.00743 | 0.0101 | 1,670 |

All values are nominal and subject to correction

*Current ratings are based on 75°C conductor temperature, 25°C ambient temperature, with 2ft./sec. wind in the sun.

**DC resistance is based on electrical resistivity of 16.946 ohm.cmil/ft @ 20c (61.2% IACS) for 1350-H19 wires and 19.755 ohm.cmil/ft @ 20c (52.5% IACS) for 6201 wires.

1-800-945-5542

www.PriorityWire.com



ACSR - Aluminum Conductor Steel Reinforced

APPLICATION: Used as bare overhead transmission cable and as primary and secondary distribution cable. ACSR offers optimal strength for line design. Variable steel core stranding for desired strength to be achieved without sacrificing ampacity.

CONSTRUCTION: Aluminum alloy 1350-H19 wires, concentrically stranded around a steel core. Core wire for ACSR is available with class A, B or C galvanizing; aluminum coated (AZ); or aluminum-clad steel core (AL). Additional corrosion protection is available through the application of grease to the core or infusion of the complete cable with grease. Also available with Non Specular surface finish.

SPECIFICATIONS: ACSR bare conductor meets or exceeds the following ASTM specifications:

B-230 Aluminum wire, 1350-H19 for Electrical Purposes

B-232 Aluminum Conductors, Concentric-Lay-Stranded, Coated Steel Reinforced (ACSR)

B-341 Aluminum-Coated Steel Core Wire for Aluminum Conductors, Steel Reinforced (ACSR/AZ)

B-498 Zinc-Coated Steel Core Wire for Aluminum Conductors, Steel Reinforced (ACSR)

B-500 Metallic Coated Stranded Steel Core for Aluminum Conductors, Steel Reinforced (ACSR)

RUS ACCEPTED

| Code Word | Conductor Size | Stranding (AL/STL) | Individual Strand Diameter | | | Comp. Cable OD | Weight | | | Content % | | Rated Breaking Strength | Resistance** | | Ampacity* |
|-----------|----------------|--------------------|----------------------------|--------|------------|----------------|---------|---------|---------|-----------|----------|-------------------------|--------------|-----------|-----------|
| | | | AL | STL | Steel Core | | AL | STL | Total | AL | STL | | DC @ 20°C | AC @ 75°C | |
| | AWG/kcmil | | inches | inches | inches | inches | lbs/kft | lbs/kft | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps | | |
| Turkey | 6 | 6/1 | 0.0661 | 0.0661 | 0.0664 | 0.198 | 24.5 | 11.6 | 36 | 67.90 | 32.10 | 1,190 | 0.6410 | 0.806 | 105 |
| Swan | 4 | 6/1 | 0.0834 | 0.0834 | 0.0834 | 0.250 | 39.0 | 18.4 | 57 | 67.90 | 32.10 | 1,860 | 0.4030 | 0.515 | 140 |
| Swanate | 4 | 7/1 | 0.0772 | 0.1029 | 0.1029 | 0.257 | 39.0 | 28.0 | 67 | 58.13 | 41.87 | 2,360 | 0.3990 | 0.519 | 140 |
| Sparrow | 2 | 6/1 | 0.1052 | 0.1052 | 0.1052 | 0.316 | 62.0 | 29.3 | 91 | 67.90 | 32.10 | 2,850 | 0.2540 | 0.332 | 184 |
| Sparate | 2 | 7/1 | 0.0974 | 0.1299 | 0.1299 | 0.325 | 62.0 | 44.7 | 107 | 58.13 | 41.87 | 3,640 | 0.2510 | 0.338 | 184 |
| Robin | 1 | 6/1 | 0.1181 | 0.1181 | 0.1181 | 0.354 | 78.2 | 36.9 | 115 | 67.90 | 32.10 | 3,550 | 0.2010 | 0.268 | 212 |
| Raven | 1/0 | 6/1 | 0.1327 | 0.1327 | 0.1327 | 0.398 | 98.7 | 46.6 | 145 | 67.90 | 32.10 | 4,380 | 0.1590 | 0.217 | 242 |
| Quail | 2/0 | 6/1 | 0.1489 | 0.1489 | 0.1489 | 0.447 | 124.3 | 58.7 | 183 | 67.90 | 32.10 | 5,300 | 0.1260 | 0.176 | 276 |
| Pigeon | 3/0 | 6/1 | 0.1672 | 0.1672 | 0.1672 | 0.502 | 156.7 | 74.0 | 231 | 67.90 | 32.10 | 6,620 | 0.1000 | 0.144 | 315 |
| Penguin | 4/0 | 6/1 | 0.1878 | 0.1878 | 0.1878 | 0.563 | 197.7 | 93.4 | 291 | 67.90 | 32.10 | 8,350 | 0.0795 | 0.119 | 357 |
| Waxwing | 266.8 | 18/1 | 0.1217 | 0.1217 | 0.1217 | 0.609 | 250.3 | 39.2 | 290 | 86.45 | 13.55 | 6,880 | 0.0643 | 0.079 | 449 |
| Partridge | 266.8 | 26/7 | 0.1013 | 0.0788 | 0.2364 | 0.642 | 251.7 | 115.5 | 367 | 68.53 | 31.47 | 11,130 | 0.0637 | 0.078 | 475 |
| Ostrich | 300.0 | 26/7 | 0.1074 | 0.0835 | 0.2505 | 0.680 | 282.9 | 129.8 | 413 | 68.53 | 31.47 | 12,700 | 0.0567 | 0.069 | 492 |
| Merlin | 336.4 | 18/1 | 0.1367 | 0.1367 | 0.1367 | 0.683 | 315.8 | 49.5 | 365 | 86.45 | 13.55 | 8,680 | 0.0510 | 0.063 | 519 |
| Linnet | 336.4 | 26/7 | 0.1137 | 0.0884 | 0.2652 | 0.720 | 317.1 | 145.4 | 463 | 68.53 | 31.47 | 14,100 | 0.0505 | 0.062 | 529 |
| Oriole | 336.4 | 30/7 | 0.1059 | 0.1059 | 0.3177 | 0.741 | 318.2 | 208.9 | 527 | 60.35 | 39.65 | 17,300 | 0.0502 | 0.061 | 535 |
| Chickadee | 397.5 | 18/1 | 0.1486 | 0.1486 | 0.1486 | 0.743 | 373.1 | 58.5 | 432 | 86.45 | 13.55 | 9,940 | 0.0432 | 0.053 | 576 |
| Brant | 397.5 | 24/7 | 0.1287 | 0.0858 | 0.2574 | 0.772 | 375.0 | 137.0 | 512 | 73.23 | 26.77 | 14,600 | 0.0430 | 0.053 | 584 |
| Ibis | 397.5 | 26/7 | 0.1236 | 0.0961 | 0.2882 | 0.783 | 374.7 | 171.9 | 547 | 68.53 | 31.47 | 16,300 | 0.0428 | 0.052 | 587 |
| Lark | 397.5 | 30/7 | 0.1151 | 0.1151 | 0.3453 | 0.806 | 375.8 | 246.8 | 623 | 60.35 | 39.65 | 20,300 | 0.0425 | 0.052 | 594 |
| Pelican | 477.0 | 18/1 | 0.1628 | 0.1628 | 0.1628 | 0.814 | 447.8 | 70.2 | 518 | 86.45 | 13.55 | 11,800 | 0.0360 | 0.044 | 646 |
| Flicker | 477.0 | 24/7 | 0.1410 | 0.0940 | 0.2820 | 0.846 | 450.1 | 164.4 | 615 | 73.23 | 26.77 | 17,200 | 0.0358 | 0.044 | 655 |
| Hawk | 477.0 | 26/7 | 0.1354 | 0.1053 | 0.3159 | 0.858 | 449.6 | 206.4 | 656 | 68.53 | 31.47 | 19,500 | 0.0356 | 0.044 | 659 |
| Hen | 477.0 | 30/7 | 0.1261 | 0.1261 | 0.3783 | 0.883 | 451.1 | 296.2 | 747 | 60.35 | 39.65 | 23,800 | 0.0354 | 0.043 | 666 |
| Osprey | 556.5 | 18/1 | 0.1758 | 0.1758 | 0.1758 | 0.879 | 522.2 | 81.8 | 604 | 86.45 | 13.55 | 13,700 | 0.0308 | 0.038 | 711 |
| Parakeet | 556.5 | 24/7 | 0.1523 | 0.1015 | 0.3045 | 0.914 | 525.1 | 191.7 | 717 | 73.23 | 26.77 | 19,800 | 0.0307 | 0.038 | 721 |
| Dove | 556.5 | 26/7 | 0.1463 | 0.1138 | 0.3414 | 0.927 | 525.0 | 241.0 | 766 | 68.53 | 31.47 | 22,600 | 0.0306 | 0.038 | 726 |
| Eagle | 556.5 | 30/7 | 0.1362 | 0.1362 | 0.4086 | 0.953 | 526.3 | 345.6 | 872 | 60.35 | 39.75 | 27,800 | 0.0303 | 0.037 | 734 |

(Continued on page 6)

1-800-945-5542

www.PriorityWire.com



ACSR - Aluminum Conductor Steel Reinforced

CONTINUED

| Code Word | Conductor Size | Stranding (AL/STL) | Individual Strand Diameter | | | Comp. Cable OD | Weight | | | Content % | | Rated Breaking Strength | Resistance** | | Ampacity* |
|------------|----------------|--------------------|----------------------------|--------|------------|----------------|---------|---------|---------|-----------|----------|-------------------------|--------------|-----------|-----------|
| | | | AL | STL | Steel Core | | AL | STL | Total | AL | STL | | DC @ 20°C | AC @ 75°C | |
| | AWG/kcmil | | inches | inches | inches | inches | lbs/kft | lbs/kft | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps | | |
| Peacock | 605.0 | 24/7 | 0.1588 | 0.1059 | 0.3177 | 0.953 | 570.9 | 208.7 | 780 | 73.23 | 26.77 | 21,600 | 0.0282 | 0.035 | 760 |
| Squab | 605.0 | 26/7 | 0.1525 | 0.1186 | 0.3558 | 0.966 | 570.4 | 261.8 | 832 | 68.53 | 31.47 | 24,300 | 0.0281 | 0.035 | 765 |
| Wood Duck | 605.0 | 30/7 | 0.1420 | 0.1420 | 0.4260 | 0.994 | 572.0 | 375.6 | 948 | 60.35 | 39.55 | 28,900 | 0.0279 | 0.034 | 774 |
| Teal | 605.0 | 30/19 | 0.1420 | 0.0852 | 0.4260 | 0.994 | 572.0 | 367.4 | 939 | 60.89 | 39.11 | 30,000 | 0.0278 | 0.034 | 773 |
| KingBird | 636.0 | 18/1 | 0.1880 | 0.1880 | 0.1880 | 0.940 | 597.2 | 93.6 | 691 | 86.45 | 13.55 | 15,700 | 0.0270 | 0.033 | 773 |
| Swift | 636.0 | 36/1 | 0.1329 | 0.1329 | 0.1329 | 0.930 | 596.9 | 46.8 | 644 | 92.80 | 7.20 | 13,800 | 0.0271 | 0.033 | 769 |
| Rook | 636.0 | 24/7 | 0.1628 | 0.1085 | 0.3255 | 0.977 | 600.0 | 219.1 | 819 | 73.23 | 26.77 | 22,600 | 0.0268 | 0.033 | 784 |
| Grosbeak | 636.0 | 26/7 | 0.1564 | 0.1216 | 0.3648 | 0.990 | 599.9 | 276.2 | 876 | 68.53 | 31.47 | 25,200 | 0.0267 | 0.033 | 789 |
| Scoter | 636.0 | 30/7 | 0.1456 | 0.1456 | 0.4368 | 1.019 | 601.4 | 394.9 | 996 | 60.35 | 39.65 | 30,400 | 0.0256 | 0.033 | 798 |
| Egret | 636.0 | 30/19 | 0.1456 | 0.0874 | 0.4370 | 1.019 | 601.4 | 386.6 | 988 | 60.89 | 39.11 | 31,500 | 0.0266 | 0.033 | 798 |
| Flamingo | 666.6 | 24/7 | 0.1667 | 0.1110 | 0.3330 | 1.000 | 629.1 | 229.7 | 859 | 73.23 | 26.77 | 23,700 | 0.0256 | 0.032 | 807 |
| Gannet | 666.6 | 26/7 | 0.1601 | 0.1245 | 0.3735 | 1.014 | 628.7 | 288.5 | 917 | 68.53 | 31.47 | 26,400 | 0.0255 | 0.031 | 812 |
| Stilt | 715.5 | 24/7 | 0.1727 | 0.1151 | 0.3453 | 1.036 | 675.2 | 246.5 | 922 | 73.23 | 26.77 | 25,500 | 0.0239 | 0.029 | 844 |
| Starling | 715.5 | 26/7 | 0.1659 | 0.1290 | 0.3870 | 1.051 | 675.0 | 309.7 | 985 | 68.53 | 31.47 | 28,400 | 0.0238 | 0.029 | 849 |
| Redwing | 715.5 | 30/19 | 0.1544 | 0.0926 | 0.4630 | 1.081 | 676.3 | 434.0 | 1,110 | 60.89 | 39.11 | 34,600 | 0.0236 | 0.029 | 859 |
| Coot | 795.0 | 36/1 | 0.1486 | 0.1486 | 0.1486 | 1.040 | 746.2 | 58.5 | 805 | 92.80 | 7.20 | 16,800 | 0.0217 | 0.027 | 894 |
| Cuckoo | 795.0 | 24/7 | 0.1820 | 0.1213 | 0.3640 | 1.092 | 749.9 | 273.8 | 1,024 | 72.23 | 26.77 | 27,900 | 0.0215 | 0.027 | 901 |
| Drake | 795.0 | 26/7 | 0.1749 | 0.1360 | 0.4080 | 1.108 | 750.3 | 344.2 | 1,094 | 68.53 | 31.47 | 31,500 | 0.0214 | 0.026 | 907 |
| Tern | 795.0 | 45/7 | 0.1329 | 0.0886 | 0.2660 | 1.063 | 749.8 | 146.1 | 896 | 83.69 | 16.31 | 22,100 | 0.0216 | 0.027 | 887 |
| Condor | 795.0 | 54/7 | 0.1213 | 0.1213 | 0.3639 | 1.092 | 749.5 | 273.6 | 1,023 | 73.25 | 26.75 | 28,200 | 0.0215 | 0.027 | 889 |
| Mallard | 795.0 | 30/19 | 0.1628 | 0.0977 | 0.4885 | 1.140 | 751.9 | 483.1 | 1,235 | 60.89 | 39.11 | 38,400 | 0.0213 | 0.026 | 918 |
| Chutepoke | 850.0 | 45/7 | 0.1375 | 0.0917 | 0.2751 | 1.100 | 804.5 | 159.6 | 964 | 83.40 | 16.60 | 23,192 | 0.0204 | 0.025 | 935 |
| Les Boules | 864.9 | 42/7 | 0.1435 | 0.0797 | 0.2391 | 1.102 | 813.4 | 121.1 | 935 | 87.04 | 12.96 | 22,480 | 0.0201 | 0.025 | 950 |
| Ruddy | 900.0 | 45/7 | 0.1414 | 0.0943 | 0.2829 | 1.131 | 848.7 | 165.5 | 1,014 | 83.69 | 16.31 | 24,400 | 0.0191 | 0.024 | 958 |
| Canary | 900.0 | 54/7 | 0.1291 | 0.1291 | 0.3873 | 1.162 | 849.0 | 309.9 | 1,159 | 73.25 | 26.75 | 31,900 | 0.0190 | 0.024 | 961 |
| Rail | 954.0 | 45/7 | 0.1456 | 0.0971 | 0.2913 | 1.165 | 899.9 | 175.5 | 1,075 | 83.69 | 16.31 | 25,900 | 0.0180 | 0.023 | 993 |
| Cardinal | 954.0 | 54/7 | 0.1329 | 0.1329 | 0.3987 | 1.196 | 900.7 | 328.4 | 1,228 | 73.25 | 26.75 | 33,800 | 0.0179 | 0.023 | 996 |
| Ortolan | 1033.5 | 45/7 | 0.1515 | 0.1010 | 0.3030 | 1.212 | 974.3 | 189.8 | 1,164 | 83.69 | 16.31 | 27,700 | 0.0167 | 0.021 | 1,043 |
| Curlew | 1033.5 | 54/7 | 0.1383 | 0.1383 | 0.4149 | 1.245 | 974.3 | 355.6 | 1,330 | 73.25 | 26.75 | 36,600 | 0.0165 | 0.021 | 1,047 |
| Beaumont | 1113.0 | 42/7 | 0.1628 | 0.0904 | 0.2712 | 1.250 | 1046.5 | 155.5 | 1,202 | 87.06 | 12.94 | 28,300 | 0.0156 | 0.020 | 990 |
| Bluejay | 1113.0 | 45/7 | 0.1573 | 0.1049 | 0.3147 | 1.259 | 1050.0 | 204.8 | 1,255 | 83.69 | 16.31 | 29,800 | 0.0155 | 0.019 | 1,092 |
| Finch | 1113.0 | 54/19 | 0.1436 | 0.0862 | 0.4310 | 1.293 | 1056.0 | 376.0 | 1,432 | 73.75 | 26.25 | 39,100 | 0.0154 | 0.020 | 1,093 |
| Bunting | 1192.5 | 45/7 | 0.1628 | 0.1085 | 0.3255 | 1.302 | 1125.0 | 219.1 | 1,344 | 83.69 | 16.31 | 32,000 | 0.0144 | 0.018 | 1,139 |
| Grackle | 1192.5 | 54/19 | 0.1486 | 0.0892 | 0.4460 | 1.338 | 1130.0 | 402.7 | 1,533 | 73.75 | 26.25 | 41,900 | 0.0144 | 0.018 | 1,140 |
| Bittern | 1272.0 | 45/7 | 0.1681 | 0.1121 | 0.3363 | 1.345 | 1200.0 | 233.9 | 1,434 | 83.69 | 16.31 | 34,100 | 0.0135 | 0.017 | 1,184 |
| Pheasant | 1272.0 | 54/19 | 0.1535 | 0.0921 | 0.4605 | 1.382 | 1206.0 | 429.3 | 1,635 | 73.75 | 26.25 | 43,600 | 0.0135 | 0.017 | 1,187 |
| Dipper | 1351.5 | 45/7 | 0.1733 | 0.1155 | 0.3465 | 1.386 | 1275.0 | 248.3 | 1,523 | 83.69 | 16.31 | 36,200 | 0.0127 | 0.016 | 1,229 |

(Continued on page 7)

1-800-945-5542

www.PriorityWire.com



ACSR - Aluminum Conductor Steel Reinforced

CONTINUED

| Code Word | Conductor Size | Stranding (AL/STL) | Individual Strand Diameter | | | Comp. Cable OD | Weight | | | Content % | | Rated Breaking Strength | Resistance** | | Ampacity* |
|---------------------------------|----------------|--------------------|----------------------------|--------|------------|----------------|---------|---------|---------|-----------|----------|-------------------------|--------------|-----------|-----------|
| | | | AL | STL | Steel Core | | AL | STL | Total | AL | STL | | DC @ 20°C | AC @ 75°C | |
| | AWG/kcmil | | inches | inches | inches | inches | lbs/kft | lbs/kft | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps | | |
| Martin | 1351.5 | 54/19 | 0.1582 | 0.0949 | 0.4745 | 1.424 | 1281.0 | 455.8 | 1,737 | 72.75 | 26.25 | 46,300 | 0.0127 | 0.016 | 1,232 |
| Bobolink | 1431.0 | 45/7 | 0.1783 | 0.1189 | 0.3567 | 1.427 | 1350.0 | 263.1 | 1,613 | 83.69 | 16.31 | 38,300 | 0.0120 | 0.015 | 1,272 |
| Plover | 1431.0 | 54/19 | 0.1628 | 0.0977 | 0.4885 | 1.465 | 1357.0 | 483.1 | 1,840 | 73.75 | 26.25 | 49,100 | 0.0120 | 0.016 | 1,275 |
| Nuthatch | 1510.5 | 45/7 | 0.1832 | 0.1221 | 0.3663 | 1.465 | 1425.0 | 277.4 | 1,702 | 83.69 | 16.31 | 40,100 | 0.0114 | 0.015 | 1,313 |
| Parrot | 1510.5 | 54/19 | 0.1672 | 0.1003 | 0.5015 | 1.505 | 1431.0 | 509.2 | 1,940 | 73.75 | 26.25 | 51,700 | 0.0114 | 0.015 | 1,318 |
| Lapwing | 1590.0 | 45/7 | 0.1880 | 0.1253 | 0.3759 | 1.504 | 1500.0 | 292.2 | 1,792 | 83.69 | 16.31 | 42,200 | 0.0108 | 0.014 | 1,354 |
| Falcon | 1590.0 | 54/19 | 0.1716 | 0.1030 | 0.5150 | 1.545 | 1507.0 | 537.0 | 2,044 | 73.75 | 26.25 | 54,500 | 0.0108 | 0.014 | 1,359 |
| Chukar | 1780.0 | 84/19 | 0.1456 | 0.0874 | 0.4370 | 1.602 | 1688.0 | 386.6 | 2,075 | 81.30 | 18.70 | 51,000 | 0.0097 | 0.013 | 1,453 |
| Bluebird | 2156.0 | 84/19 | 0.1602 | 0.0961 | 0.4805 | 1.762 | 2044.0 | 467.4 | 2,511 | 81.30 | 18.70 | 60,300 | 0.0081 | 0.011 | 1,623 |
| Kiwi | 2167.0 | 72/7 | 0.1735 | 0.1157 | 0.3471 | 1.735 | 2055.0 | 248.9 | 2,304 | 89.20 | 10.80 | 49,800 | 0.0080 | 0.011 | 1,607 |
| Thrasher | 2312.0 | 76/19 | 0.1744 | 0.0814 | 0.4070 | 1.802 | 2191.0 | 335.4 | 2,527 | 86.73 | 13.27 | 56,700 | 0.0075 | 0.010 | 1,673 |
| Joree | 2515.0 | 76/19 | 0.1819 | 0.0849 | 0.4245 | 1.880 | 2384.0 | 364.8 | 2,749 | 86.73 | 13.27 | 61,700 | 0.0069 | 0.009 | 1,751 |
| High Mechanical Strength | | | | | | | | | | | | | | | |
| Grouse | 80.0 | 8/1 | 0.1000 | 0.1670 | 0.1670 | 0.367 | 75.1 | 73.9 | 149 | 50.56 | 49.44 | 5,200 | 0.2070 | 0.261 | 204 |
| Petrel | 101.8 | 12/7 | 0.0921 | 0.0921 | 0.2763 | 0.461 | 96.0 | 158.0 | 254 | 37.79 | 62.21 | 10,400 | 0.1580 | 0.239 | 237 |
| Minorca | 110.8 | 12/7 | 0.0961 | 0.0961 | 0.2883 | 0.481 | 103.9 | 172.1 | 276 | 37.79 | 62.21 | 11,300 | 0.1450 | 0.223 | 246 |
| Leghorn | 134.6 | 12/7 | 0.1059 | 0.1059 | 0.3177 | 0.530 | 127.0 | 209.0 | 336 | 37.79 | 62.21 | 13,600 | 0.1200 | 0.189 | 273 |
| Guinea | 159.0 | 12/7 | 0.1151 | 0.1151 | 0.3453 | 0.576 | 149.2 | 246.8 | 396 | 37.79 | 62.21 | 16,000 | 0.1010 | 0.165 | 297 |
| Dotterel | 176.9 | 12/7 | 0.1214 | 0.1214 | 0.3642 | 0.607 | 166.4 | 274.6 | 441 | 37.79 | 62.21 | 17,300 | 0.0911 | 0.151 | 312 |
| Dorking | 190.8 | 12/7 | 0.1261 | 0.1261 | 0.3783 | 0.631 | 179.7 | 296.3 | 476 | 37.79 | 62.21 | 18,700 | 0.0845 | 0.142 | 324 |
| Brahma | 203.2 | 16/19 | 0.1127 | 0.0977 | 0.4885 | 0.714 | 190.0 | 485.0 | 675 | 28.33 | 71.67 | 28,400 | 0.0764 | 0.135 | 341 |
| Cochin | 211.3 | 12/7 | 0.1327 | 0.1327 | 0.3981 | 0.664 | 198.8 | 328.2 | 527 | 37.79 | 62.21 | 30,700 | 0.0764 | 0.131 | 340 |

All values are nominal and subject to correction

* Current ratings based on 75°C conductor temperature, 25°C ambient temperature, emissivity 0.5, 2ft/sec wind in sun.

** Resistance is calculated using ASTM standard increments of stranding, and metal conductivity of 61.2% IACS for AL (1350) and 8% IACS for steel. AC (60Hz) resistance includes current dependent hysteresis loss factor for 1 and 3 layer constructions.

Aluminum Tie and Ground Wire

APPLICATION: Generally used in overhead transmission and distribution line construction to mechanically secure components such as conductors to pin insulators. Also used for grounding applications in line construction.

CONSTRUCTION: Solid, soft 1350-0 aluminum conductor

SPECIFICATIONS: Meets or exceeds standard ASTM: B-609 Aluminum 1350 Round Wire, Annealed and Intermediate Tempers for Electrical Purposes

| Conductor Size | Stranding | Diameter | Weight |
|----------------|-----------|----------|---------|
| AWG | | inches | lbs/kft |
| 6 | Solid | 0.1620 | 24.1 |
| 4 | Solid | 0.2043 | 38.4 |
| 2 | Solid | 0.2576 | 61.0 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



ACSR/AW

APPLICATION: Used as bare overhead transmission and as primary and secondary distribution cable. ACSR/AW offers strength characteristics similar to ACSR, along with slightly greater ampacity and resistance to corrosion due to aluminum-cladding of the steel core wires.

CONSTRUCTION: Aluminum alloy 1350-H19 wires, concentrically stranded around an aluminum-clad steel core.

SPECIFICATIONS: ACSR/AW bare conductor meets or exceeds the following ASTM specifications:

B-230 Aluminum wire, 1350-H19 for Electrical Purposes

B-502 Aluminum-Clad Steel Core Wire for Aluminum Conductors, Aluminum-Clad Steel Reinforced.

B-549 Aluminum Conductors, Concentric-Lay-Stranded, Aluminum-Clad Steel Reinforced (ACSR/AW).

| Code Word | Conductor Size | Stranding (AL/AW) | Individual Strand Diameter | | | Comp. Cable OD | Weight | | | Rated Breaking Strength | Resistance** | | Ampacity* |
|--------------|----------------|-------------------|----------------------------|--------|---------|----------------|---------|---------|---------|-------------------------|--------------|-----------|-----------|
| | | | AL | AW | AW Core | | AL | AW | Total | | DC @ 20°C | AC @ 75°C | |
| | AWG/kcmil | | inches | inches | inches | inches | lbs/kft | lbs/kft | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps |
| Swan/Aw | 4 | 6/1 | 0.0834 | 0.0834 | 0.0834 | 0.250 | 39 | 16 | 55 | 1,780 | 0.3917 | 0.477 | 145 |
| Swanate/Aw | 4 | 7/1 | 0.0772 | 0.103 | 0.1030 | 0.257 | 39 | 24 | 63 | 2,280 | 0.3814 | 0.4642 | 148 |
| Sparrow/Aw | 2 | 6/1 | 0.1052 | 0.1052 | 0.1052 | 0.316 | 62 | 25 | 87 | 2,760 | 0.2462 | 0.2997 | 194 |
| Sparate/Aw | 2 | 7/1 | 0.0974 | 0.1298 | 0.1298 | 0.325 | 62 | 38 | 100 | 3,510 | 0.2396 | 0.2917 | 198 |
| Robin/Aw | 1 | 6/1 | 0.1181 | 0.1181 | 0.1181 | 0.354 | 78 | 31 | 109 | 3,450 | 0.1950 | 0.2373 | 225 |
| Raven/Aw | 1/0 | 6/1 | 0.1327 | 0.1327 | 0.1327 | 0.398 | 99 | 39 | 138 | 4,250 | 0.1547 | 0.1884 | 260 |
| Quail/Aw | 2/0 | 6/1 | 0.1489 | 0.1489 | 0.1489 | 0.447 | 124 | 50 | 174 | 5,130 | 0.1227 | 0.1494 | 301 |
| Pigeon/Aw | 3/0 | 6/1 | 0.1672 | 0.1672 | 0.1672 | 0.502 | 156 | 63 | 219 | 6,300 | 0.09747 | 0.1188 | 347 |
| Penguin/Aw | 4/0 | 6/1 | 0.1878 | 0.1878 | 0.1878 | 0.563 | 197 | 79 | 277 | 7,690 | 0.07726 | 0.09422 | 402 |
| Waxwing/Aw | 266.8 | 18/1 | 0.1217 | 0.1217 | 0.1217 | 0.609 | 250 | 33 | 283 | 6,820 | 0.06364 | 0.07776 | 451 |
| Partridge/Aw | 266.8 | 26/7 | 0.1013 | 0.0788 | 0.2363 | 0.642 | 251 | 98 | 349 | 10,800 | 0.06169 | 0.07541 | 465 |
| Ostrich/Aw | 300.0 | 26/7 | 0.1074 | 0.0835 | 0.2506 | 0.680 | 283 | 110 | 393 | 12,100 | 0.05489 | 0.06712 | 500 |
| Merlin/Aw | 336.4 | 18/1 | 0.1367 | 0.1367 | 0.1367 | 0.684 | 315 | 42 | 357 | 8,540 | 0.05044 | 0.06175 | 522 |
| Linnet/Aw | 336.4 | 26/7 | 0.1137 | 0.0885 | 0.2654 | 0.720 | 317 | 123 | 440 | 13,500 | 0.04897 | 0.05989 | 537 |
| Oriole/Aw | 336.4 | 30/7 | 0.1059 | 0.1059 | 0.3177 | 0.741 | 318 | 177 | 494 | 16,700 | 0.04795 | 0.05861 | 547 |
| Chickadee/Aw | 397.5 | 18/1 | 0.1486 | 0.1486 | 0.1486 | 0.743 | 373 | 50 | 422 | 9,780 | 0.04268 | 0.0523 | 580 |
| Brant/Aw | 397.5 | 24/7 | 0.1287 | 0.0858 | 0.2574 | 0.772 | 374 | 116 | 490 | 14,100 | 0.04185 | 0.05124 | 592 |
| Ibis/Aw | 397.5 | 26/7 | 0.1236 | 0.0962 | 0.2885 | 0.783 | 374 | 146 | 520 | 15,800 | 0.04144 | 0.05072 | 597 |
| Lark/Aw | 397.5 | 30/7 | 0.1151 | 0.1151 | 0.3453 | 0.806 | 375 | 209 | 584 | 19,600 | 0.04059 | 0.04965 | 608 |
| Pelican/Aw | 477.0 | 18/1 | 0.1628 | 0.1628 | 0.1628 | 0.814 | 447 | 59 | 507 | 11,500 | 0.03556 | 0.04344 | 651 |
| Flicker/Aw | 477.0 | 24/7 | 0.1410 | 0.0940 | 0.2819 | 0.846 | 449 | 139 | 589 | 16,700 | 0.03487 | 0.04273 | 663 |
| Hawk/Aw | 477.0 | 26/7 | 0.1354 | 0.1053 | 0.3160 | 0.858 | 449 | 175 | 624 | 18,900 | 0.03453 | 0.04231 | 669 |
| Hen/Aw | 477.0 | 30/7 | 0.1261 | 0.1261 | 0.3783 | 0.883 | 450 | 251 | 701 | 23,400 | 0.03382 | 0.04139 | 682 |
| Osprey/Aw | 556.5 | 18/1 | 0.1758 | 0.1758 | 0.1758 | 0.879 | 522 | 69 | 591 | 13,200 | 0.03050 | 0.03749 | 715 |
| Parakeet/Aw | 556.5 | 24/7 | 0.1523 | 0.1015 | 0.3045 | 0.914 | 524 | 163 | 687 | 19,300 | 0.02989 | 0.03667 | 731 |
| Dove/Aw | 556.5 | 26/7 | 0.1463 | 0.1138 | 0.3413 | 0.927 | 524 | 204 | 728 | 21,900 | 0.02958 | 0.03627 | 737 |
| Eagle/Aw | 556.5 | 30/7 | 0.1362 | 0.1362 | 0.4086 | 0.953 | 525 | 293 | 818 | 26,800 | 0.02899 | 0.03551 | 751 |
| Peacock/Aw | 605.0 | 24/7 | 0.1588 | 0.1059 | 0.3175 | 0.953 | 570 | 177 | 746 | 21,000 | 0.02749 | 0.03377 | 770 |
| Squab/Aw | 605.0 | 26/7 | 0.1525 | 0.1186 | 0.3559 | 0.966 | 570 | 222 | 792 | 23,600 | 0.02588 | 0.03341 | 777 |
| Teal/Aw | 605.0 | 30/19 | 0.1420 | 0.0852 | 0.4260 | 0.994 | 571 | 311 | 883 | 28,500 | 0.02672 | 0.03274 | 791 |

(Continued on page 9)

1-800-945-5542

www.PriorityWire.com



ACSR/AW

CONTINUED

| Code Word | Conductor Size | Stranding (AL/AW) | Individual Strand Diameter | | | Comp. Cable OD | Weight | | | Rated Breaking Strength | Resistance** | | Ampacity* |
|---------------------------------|----------------|-------------------|----------------------------|--------|---------|----------------|---------|---------|---------|-------------------------|--------------|-----------|-----------|
| | | | AL | AW | AW Core | | AL | AW | Total | | DC @ 20°C | AC @ 75°C | |
| | AWG/kcmil | | inches | inches | inches | inches | lbs/kft | lbs/kft | lbs/kft | lbs | Ohms/kft | Ohms/kft | amps |
| Kingbird/Aw | 636.0 | 18/1 | 0.1880 | 0.1880 | 0.1880 | 0.94 | 596 | 79 | 675 | 15,000 | 0.02667 | 0.03286 | 778 |
| Rook/Aw | 636.0 | 24/7 | 0.1628 | 0.1085 | 0.3256 | 0.977 | 599 | 186 | 785 | 22,000 | 0.02616 | 0.03216 | 794 |
| Grosbeak/Aw | 636.0 | 26/7 | 0.1564 | 0.1216 | 0.3649 | 0.991 | 599 | 233 | 832 | 24,800 | 0.02588 | 0.03179 | 801 |
| Flamingo/Aw | 666.6 | 24/7 | 0.1667 | 0.1111 | 0.3333 | 1.000 | 628 | 195 | 823 | 23,100 | 0.02495 | 0.03069 | 818 |
| Gannet/Aw | 666.6 | 26/7 | 0.1601 | 0.1245 | 0.3736 | 1.014 | 628 | 245 | 872 | 26,000 | 0.02470 | 0.03034 | 825 |
| Starling/Aw | 715.5 | 26/7 | 0.1659 | 0.1290 | 0.3871 | 1.051 | 674 | 263 | 936 | 27,500 | 0.02300 | 0.0283 | 863 |
| Redwing/Aw | 715.5 | 30/19 | 0.1544 | 0.0927 | 0.4633 | 1.081 | 676 | 368 | 1,044 | 33,400 | 0.02260 | 0.02777 | 878 |
| Cuckoo/Aw | 795.0 | 24/7 | 0.1820 | 0.1213 | 0.3640 | 1.092 | 749 | 232 | 981 | 27,500 | 0.02093 | 0.02582 | 913 |
| Drake/Aw | 795.0 | 26/7 | 0.1749 | 0.1360 | 0.4080 | 1.107 | 749 | 292 | 1,040 | 30,500 | 0.0207 | 0.02549 | 922 |
| Tern/Aw | 795.0 | 45/7 | 0.1329 | 0.0886 | 0.2658 | 1.063 | 749 | 124 | 873 | 21,500 | 0.02135 | 0.02638 | 896 |
| Condor/Aw | 795.0 | 54/7 | 0.1213 | 0.1213 | 0.3640 | 1.092 | 749 | 232 | 981 | 27,800 | 0.02091 | 0.02578 | 913 |
| Mallard/Aw | 795.0 | 30/19 | 0.1628 | 0.0977 | 0.4884 | 1.139 | 751 | 409 | 1,160 | 37,100 | 0.02033 | 0.02500 | 938 |
| Ruddy/Aw | 900.0 | 45/7 | 0.1414 | 0.0943 | 0.2828 | 1.131 | 848 | 140 | 988 | 24,000 | 0.01886 | 0.02330 | 970 |
| Canary/Aw | 900.0 | 54/7 | 0.1291 | 0.1291 | 0.3873 | 1.162 | 848 | 263 | 1,111 | 31,000 | 0.01849 | 0.02286 | 986 |
| Rail/Aw | 954.0 | 45/7 | 0.1456 | 0.0971 | 0.2912 | 1.165 | 899 | 149 | 1,047 | 25,400 | 0.01779 | 0.02210 | 1,003 |
| Cardinal/Aw | 954.0 | 54/7 | 0.1329 | 0.1329 | 0.3987 | 1.196 | 899 | 279 | 1,177 | 32,900 | 0.01744 | 0.02161 | 1,022 |
| Ortolan/Aw | 1033.5 | 45/7 | 0.1515 | 0.1010 | 0.3031 | 1.212 | 973 | 161 | 1,134 | 27,200 | 0.01641 | 0.02044 | 1,054 |
| Curlew/Aw | 1033.5 | 54/7 | 0.1383 | 0.1383 | 0.4150 | 1.245 | 973 | 302 | 1,275 | 35,200 | 0.01609 | 0.01997 | 1,074 |
| Bluejay/Aw | 1113 | 45/7 | 0.1573 | 0.1048 | 0.3145 | 1.258 | 1,048 | 173 | 1,222 | 29,300 | 0.01606 | 0.01905 | 1,103 |
| Pheasant/Aw | 1272 | 54/19 | 0.1535 | 0.0921 | 0.4604 | 1.381 | 1,204 | 364 | 1,568 | 42,400 | 0.01315 | 0.01646 | 1,216 |
| Bobolink/Aw | 1431 | 45/7 | 0.1783 | 0.1189 | 0.3566 | 1.427 | 1,348 | 223 | 1,571 | 37,600 | 0.01186 | 0.01503 | 1,283 |
| Lapwing/Aw | 1590 | 45/7 | 0.1880 | 0.1253 | 0.3759 | 1.504 | 1,498 | 248 | 1,745 | 41,800 | 0.01069 | 0.01366 | 1,365 |
| High Mechanical Strength | | | | | | | | | | | | | |
| Grouse/Aw | 80.0 | 8/1 | 0.1000 | 0.1670 | 0.1670 | 0.367 | 75 | 63 | 138 | 4,890 | 0.1942 | 0.2357 | 227 |
| Petrel/Aw | 101.8 | 12/7 | 0.0921 | 0.0921 | 0.2763 | 0.460 | 96 | 134 | 230 | 9,910 | 0.1425 | 0.1736 | 281 |
| Minorca/Aw | 110.8 | 12/7 | 0.0961 | 0.0961 | 0.2883 | 0.481 | 105 | 146 | 251 | 10,800 | 0.1326 | 0.1594 | 297 |
| Leghorn/Aw | 134.6 | 12/7 | 0.1059 | 0.1059 | 0.3177 | 0.530 | 127 | 177 | 304 | 13,000 | 0.1078 | 0.1313 | 335 |
| Guinea/Aw | 159.0 | 12/7 | 0.1151 | 0.1151 | 0.3453 | 0.576 | 150 | 209 | 359 | 15,300 | 0.09123 | 0.1112 | 372 |
| Dotterel/Aw | 176.9 | 12/7 | 0.1214 | 0.1214 | 0.3642 | 0.607 | 167 | 233 | 400 | 16,900 | 0.08201 | 0.09988 | 398 |
| Dorking/Aw | 190.8 | 12/7 | 0.1261 | 0.1261 | 0.3783 | 0.631 | 180 | 251 | 431 | 18,300 | 0.07601 | 0.09261 | 418 |
| Brahma/Aw | 203.2 | 16/19 | 0.1127 | 0.0977 | 0.4885 | 0.714 | 192 | 411 | 603 | 27,100 | 0.06570 | 0.07994 | 464 |
| Cochin/Aw | 211.3 | 12/7 | 0.1327 | 0.1327 | 0.3981 | 0.664 | 199 | 278 | 477 | 19,800 | 0.06863 | 0.08364 | 445 |

All values are nominal and subject to correction

*Conductor temperature of 75°C ambient temperature of 25°C, emissivity 0.5, wind 2 ft/sec, in sun.

** Resistance is calculated using ASTM standard increments of stranding, and metal conductivity of 61.2% IACS for AL (1350) and 8% IACS for steel. AC (60Hz) resistance includes current dependent hysteresis loss factor for 1 and 3 layer constructions.

1-800-945-5542

www.PriorityWire.com



ACSR/TP Bare Overhead Conductor

APPLICATION: ACSR/TP has become highly popular; it resists galloping with changing wind-attack profile, and shows low Aeolian vibration and sub-conductor oscillation. ACSR/TP conductors are used for overhead distribution and transmission lines which are subject to wind induced motion damage.

CONSTRUCTION: ACSR/TP is a pair of identical stranded aluminum, steel reinforced, conductors twisted around each other with a long lay (6.5 or 9 foot intervals). ACSR/TP conductors are manufactured in accordance with the latest applicable issue of ASTM B911. The sizes and stranding listed are those most frequently used for overhead lines. The steel core wires are protected by galvanizing, aluminizing or aluminum cladding. The standard Class A zinc coating is usually adequate for ordinary environments. For greater protection, Class B and C galvanized coatings, aluminized or Aluminum Clad steel cores may be specified.

RUS ACCEPTED

| Code Word | Conductor Size | Component | | | Total Cross Sectional Area | | Outer Dimensions | Equiv. Diameter | Weight | | Rated Strength | Resistance** | | | Ampacity* |
|--------------|----------------|-----------|-----------------------|------------|----------------------------|------------|------------------|-----------------|------------|--------|----------------|--------------|-----------|-----------|-----------|
| | | Size | No. x Strand Diameter | | Total | AL | | | Total | AL | | DC @ 20°C | AC @ 25°C | AC @ 75°C | |
| | | | AL | Steel | | | | | | | | | | | |
| | | AWG/kcmil | AWG/kcmil | inches | inches | sq. inches | | | sq. inches | inches | | inches | lbs/mft | lbs/mft | |
| Swan/TP | 1 | 4 | 6 x 0.0834 | 1 x 0.0834 | 0.0765 | 0.0656 | 0.250 x 0.500 | 0.410 | 115 | 77.9 | 3,720 | 0.2016 | 0.2058 | 0.2465 | 245 |
| Swanate/TP | 1 | 4 | 7 x 0.0772 | 1 x 0.1029 | 0.0765 | 0.0656 | 0.257 x 0.514 | 0.421 | 134 | 77.9 | 4,720 | 0.2016 | 0.2035 | 0.2438 | 245 |
| Swallow/TP | 1/0 | 3 | 6 x 0.0937 | 1 x 0.0937 | 0.0964 | 0.0826 | 0.281 x 0.562 | 0.460 | 145 | 98.1 | 4,590 | 0.1600 | 0.1632 | 0.1955 | 280 |
| Sparrow/TP | 2/0 | 2 | 6 x 0.1052 | 1 x 0.1052 | 0.1216 | 0.1042 | 0.315 x 0.631 | 0.517 | 182 | 124 | 5,700 | 0.1268 | 0.1294 | 0.1551 | 325 |
| Sparate/TP | 2/0 | 2 | 7 x 0.0974 | 1 x 0.1299 | 0.1307 | 0.1042 | 0.325 x 0.649 | 0.531 | 213 | 124 | 7,280 | 0.1254 | 0.1280 | 0.1533 | 330 |
| Robin/TP | 3/0 | 1 | 6 x 0.1181 | 1 x 0.1181 | 0.1534 | 0.1315 | 0.354 x 0.709 | 0.580 | 230 | 156 | 7,110 | 0.1005 | 0.1207 | 0.1230 | 380 |
| Raven/TP | 4/0 | 1/0 | 6 x 0.1327 | 1 x 0.1327 | 0.1935 | 0.1659 | 0.398 x 0.796 | 0.651 | 290 | 197 | 8,760 | 0.0797 | 0.0814 | 0.0975 | 440 |
| Quail/TP | 266.2 | 2/0 | 6 x 0.1489 | 1 x 0.1489 | 0.2439 | 0.2091 | 0.447 x 0.894 | 0.731 | 366 | 248 | 10,600 | 0.0632 | 0.0646 | 0.0774 | 510 |
| Pigeon/TP | 335.6 | 3/0 | 6 x 0.1672 | 1 x 0.1672 | 0.3075 | 0.2636 | 0.502 x 1.003 | 0.821 | 461 | 313 | 13,200 | 0.0501 | 0.0513 | 0.0614 | 595 |
| Penguin/TP | 423.2 | 4/0 | 6 x 0.1878 | 1 x 0.1878 | 0.3878 | 0.3324 | 0.563 x 1.127 | 0.922 | 582 | 395 | 16,700 | 0.0398 | 0.0408 | 0.0488 | 690 |
| Jaeger/TP | 456.4 | 228.2 | 18 x 0.1126 | 1 x 0.1126 | 0.3784 | 0.3585 | 0.563 x 1.126 | 0.921 | 495 | 428 | 12,000 | 0.0376 | 0.0386 | 0.0462 | 710 |
| Waxwing/TP | 533.6 | 266.8 | 18 x 0.1217 | 1 x 0.1217 | 0.4424 | 0.4191 | 0.609 x 1.217 | 0.996 | 579 | 500 | 13,800 | 0.0322 | 0.0331 | 0.0395 | 785 |
| Spoonbill/TP | 533.6 | 266.8 | 22 x 0.1101 | 7 x 0.0612 | 0.4602 | 0.4191 | 0.624 x 1.248 | 1.021 | 642 | 503 | 17,400 | 0.0321 | 0.0330 | 0.0395 | 795 |
| Scaup/TP | 533.6 | 266.8 | 24 x 0.1054 | 7 x 0.0703 | 0.4734 | 0.4191 | 0.633 x 1.265 | 1.035 | 687 | 503 | 20,000 | 0.0320 | 0.0329 | 0.0393 | 800 |
| Partridge/TP | 533.6 | 266.8 | 26 x 0.1013 | 7 x 0.0788 | 0.4873 | 0.4191 | 0.642 x 1.283 | 1.050 | 734 | 503 | 22,600 | 0.0319 | 0.0327 | 0.0391 | 805 |
| Junco/TP | 533.6 | 266.8 | 30 x 0.0943 | 7 x 0.0943 | 0.5169 | 0.4191 | 0.660 x 1.320 | 1.080 | 835 | 504 | 27,900 | 0.0316 | 0.0325 | 0.0389 | 815 |
| Ostrich/TP | 600 | 300 | 26 x 0.1074 | 7 x 0.0835 | 0.5480 | 0.4172 | 0.680 x 1.361 | 1.113 | 825 | 565 | 25,400 | 0.0283 | 0.0292 | 0.0348 | 865 |
| Merlin/TP | 672.8 | 336.4 | 18 x 0.1367 | 1 x 0.1367 | 0.5578 | 0.5284 | 0.684 x 1.367 | 1.119 | 730 | 631 | 17,400 | 0.0255 | 0.0264 | 0.0315 | 915 |
| Trogon/TP | 672.8 | 336.4 | 20 x 0.1297 | 7 x 0.0576 | 0.5649 | 0.5284 | 0.692 x 1.383 | 1.132 | 757 | 634 | 18,900 | 0.0256 | 0.0264 | 0.0315 | 915 |
| Woodcock/TP | 672.8 | 336.4 | 22 x 0.1237 | 7 x 0.0687 | 0.5803 | 0.5284 | 0.701 x 1.401 | 1.147 | 809 | 634 | 21,800 | 0.0255 | 0.0263 | 0.0314 | 920 |
| Widgeon/TP | 672.8 | 336.4 | 24 x 0.1184 | 7 x 0.0789 | 0.5969 | 0.5284 | 0.710 x 1.421 | 1.163 | 866 | 634 | 25,000 | 0.0254 | 0.0262 | 0.0313 | 925 |
| Linnet/TP | 672.8 | 336.4 | 26 x 0.1137 | 7 x 0.0884 | 0.6145 | 0.5284 | 0.720 x 1.441 | 1.179 | 925 | 634 | 28,200 | 0.0253 | 0.0261 | 0.0311 | 930 |
| Oriole/TP | 672.8 | 336.4 | 30 x 0.1059 | 7 x 0.1059 | 0.6517 | 0.5284 | 0.741 x 1.483 | 1.213 | 1053 | 635 | 34,700 | 0.0251 | 0.0258 | 0.0309 | 945 |
| Chickadee/TP | 795 | 397.5 | 18 x 0.1486 | 1 x 0.1486 | 0.6591 | 0.6244 | 0.743 x 1.486 | 1.216 | 862 | 745 | 19,900 | 0.0216 | 0.0224 | 0.0267 | 1015 |
| Ptarmigan/TP | 795 | 397.5 | 20 x 0.1410 | 7 x 0.0627 | 0.6676 | 0.6244 | 0.752 x 1.504 | 1.231 | 895 | 749 | 22,100 | 0.0216 | 0.0225 | 0.0268 | 1020 |
| Stork/TP | 795 | 397.5 | 22 x 0.1344 | 7 x 0.0747 | 0.6857 | 0.6244 | 0.762 x 1.523 | 1.247 | 956 | 749 | 25,700 | 0.0216 | 0.0224 | 0.0267 | 1025 |
| Brant/TP | 795 | 397.5 | 24 x 0.1287 | 7 x 0.0858 | 0.7053 | 0.6244 | 0.772 x 1.544 | 1.264 | 1023 | 749 | 29,300 | 0.0215 | 0.0222 | 0.0265 | 1030 |
| Ibis/TP | 795 | 397.5 | 26 x 0.1236 | 7 x 0.0961 | 0.7261 | 0.6244 | 0.783 x 1.566 | 1.282 | 1093 | 749 | 32,600 | 0.0214 | 0.0221 | 0.0264 | 1040 |
| Lark/TP | 795 | 397.5 | 30 x 0.1151 | 7 x 0.1151 | 0.7701 | 0.6244 | 0.806 x 1.612 | 1.319 | 1244 | 751 | 40,700 | 0.0212 | 0.0219 | 0.0262 | 1050 |
| Pelican/TP | 954 | 477 | 18 x 0.1628 | 1 x 0.1628 | 0.7909 | 0.7493 | 0.814 x 1.628 | 1.332 | 1035 | 894 | 23,500 | 0.0181 | 0.0189 | 0.0224 | 1140 |

(Continued on page 11)

1-800-945-5542

www.PriorityWire.com



CONTINUED

ACSR/TP Bare Overhead Conductor

| Code Word | Conductor Size | Component | | | Total Cross Sectional Area | | Outer Dimensions | Equiv. Diameter | Weight | | Rated Strength | Resistance** | | | Ampacity* |
|----------------|----------------|-----------|-----------------------|------------|----------------------------|------------|------------------|-----------------|---------|---------|----------------|--------------|-----------|-----------|-----------|
| | | Size | No. x Strand Diameter | | Total | AL | | | Total | AL | | DC @ 20°C | AC @ 25°C | AC @ 75°C | |
| | AWG/kcmil | AWG/kcmil | AL | Steel | sq. inches | sq. inches | inches | inches | lbs/mft | lbs/mft | lbs | Ohms/mft | Ohms/mft | Ohms/mft | amps |
| | | | inches | inches | | | | | | | | | | | |
| Tailorbird/TP | 954 | 477 | 20 x 0.1544 | 7 x 0.0686 | 0.8011 | 0.7493 | 0.824 x 1.647 | 1.348 | 1074 | 899 | 26,200 | 0.0180 | 0.0189 | 0.0224 | 1145 |
| Tocan/TP | 954 | 477 | 22 x 0.1472 | 7 x 0.0818 | 0.8229 | 0.7493 | 0.834 x 1.669 | 1.366 | 1148 | 899 | 30,500 | 0.0180 | 0.0188 | 0.0223 | 1150 |
| Flicker/TP | 954 | 477 | 24 | 7 | 0.8464 | 0.7493 | 0.846 | 1.384 | 1227 | 899 | 34,300 | 0.0179 | 0.0187 | 0.0222 | 1160 |
| Hawk/TP | 954 | 477 | 26 | 7 | 0.8713 | 0.7493 | 0.858 | 1.404 | 1312 | 899 | 39,100 | 0.0178 | 0.0186 | 0.0221 | 1170 |
| Hen/TP | 954 | 477 | 30 | 7 | 0.9241 | 0.7493 | 0.883 | 1.445 | 1493 | 901 | 47,600 | 0.0177 | 0.0184 | 0.0219 | 1185 |
| Heron/TP | 1000 | 500 | 30 | 7 | 0.9687 | 0.7854 | 0.904 | 1.479 | 1565 | 944 | 49,900 | 0.0169 | 0.0176 | 0.0209 | 1220 |
| Nightingale/TP | 1034 | 517 | 18 | 1 | 0.8572 | 0.8121 | 0.847 | 1.387 | 1121 | 969 | 25,500 | 0.0166 | 0.0175 | 0.0207 | 1200 |
| Creeper/TP | 1034 | 517 | 20 | 7 | 0.8682 | 0.8121 | 0.857 | 1.403 | 1164 | 974 | 28,400 | 0.0166 | 0.0175 | 0.0208 | 1205 |
| Osprey/TP | 1113 | 556.5 | 18 | 1 | 0.9227 | 0.8741 | 0.879 | 1.439 | 1207 | 1043 | 27,400 | 0.0154 | 0.0163 | 0.0193 | 1260 |
| Tody/TP | 1113 | 556.5 | 20 | 7 | 0.9346 | 0.8741 | 0.890 | 1.456 | 1253 | 1048 | 30,500 | 0.0155 | 0.0163 | 0.0194 | 1260 |
| Sapsucker/TP | 1113 | 556.5 | 22 | 7 | 0.9600 | 0.8741 | 0.901 | 1.475 | 1339 | 1048 | 35,200 | 0.0154 | 0.0162 | 0.0192 | 1270 |
| Parakeet/TP | 1113 | 556.5 | 24 | 7 | 0.9875 | 0.8741 | 0.914 | 1.495 | 1432 | 1048 | 39,600 | 0.0153 | 0.0161 | 0.0191 | 1280 |
| Dove/TP | 1113 | 556.5 | 26 | 7 | 1.0165 | 0.8741 | 0.927 | 1.516 | 1530 | 1048 | 45,200 | 0.0153 | 0.0160 | 0.0190 | 1290 |
| Eagle/TP | 1113 | 556.5 | 30 | 7 | 1.0781 | 0.8741 | 0.953 | 1.560 | 1741 | 1051 | 55,600 | 0.0152 | 0.0159 | 0.0189 | 1305 |
| Kittiwake/TP | 1192 | 596 | 18 | 1 | 0.9882 | 0.9362 | 0.091 | 1.489 | 1293 | 1117 | 29,400 | 0.0144 | 0.0153 | 0.0181 | 1315 |
| Skua/TP | 1210 | 605 | 20 | 7 | 1.0160 | 0.9503 | 0.928 | 1.518 | 1362 | 1140 | 33,200 | 0.0142 | 0.0151 | 0.0179 | 1330 |
| Peacock/TP | 1210 | 605 | 24 | 7 | 1.0735 | 0.9503 | 0.953 | 1.559 | 1557 | 1140 | 43,100 | 0.0141 | 0.0149 | 0.0177 | 1350 |
| Squab/TP | 1210 | 605 | 26 | 7 | 1.1051 | 0.9503 | 0.966 | 1.581 | 1664 | 1140 | 48,700 | 0.0140 | 0.0148 | 0.0177 | 1360 |
| Wood Duck/TP | 1210 | 605 | 30 | 7 | 1.1721 | 0.9503 | 0.994 | 1.627 | 1893 | 1142 | 57,800 | 0.0140 | 0.0146 | 0.0174 | 1375 |
| Teal/TP | 1210 | 605 | 30 | 19 | 1.6700 | 0.9503 | 0.994 | 1.627 | 1877 | 1142 | 59,900 | 0.0140 | 0.0147 | 0.0174 | 1375 |
| Swift/TP | 1272 | 636 | 36 | 1 | 1.0268 | 0.9990 | 0.930 | 1.523 | 1286 | 1192 | 27,600 | 0.0135 | 0.0141 | 0.0168 | 1375 |
| Kingbird/TP | 1272 | 636 | 18 | 1 | 1.0545 | 0.9990 | 0.940 | 1.538 | 1379 | 1192 | 31,400 | 0.0135 | 0.0144 | 0.0170 | 1365 |
| Turacos/TP | 1272 | 636 | 20 | 7 | 1.0681 | 0.9990 | 0.951 | 1.557 | 1432 | 1198 | 34,900 | 0.0135 | 0.0144 | 0.0171 | 1370 |
| Rook/TP | 1272 | 636 | 24 | 7 | 1.1285 | 0.9990 | 0.977 | 1.599 | 1637 | 1198 | 45,300 | 0.0135 | 0.0142 | 0.0168 | 1385 |
| Grosbeak/TP | 1272 | 636 | 26 | 7 | 1.1617 | 0.9990 | 0.991 | 1.621 | 1749 | 1198 | 50,400 | 0.0134 | 0.0141 | 0.0167 | 1395 |
| Scoter/TP | 1272 | 636 | 30 | 7 | 1.2320 | 0.9990 | 1.019 | 1.668 | 1990 | 1201 | 60,800 | 0.0133 | 0.0140 | 0.0166 | 1410 |
| Egret/TP | 1272 | 636 | 30 | 19 | 1.2268 | 0.9990 | 1.019 | 1.668 | 1974 | 1201 | 63,000 | 0.0133 | 0.0140 | 0.0166 | 1420 |
| Siskin/TP | 1333.2 | 666.6 | 20 | 7 | 1.1195 | 1.0471 | 0.974 | 1.594 | 1501 | 1256 | 36,600 | 0.0129 | 0.0138 | 0.0163 | 1415 |
| Flamingo/TP | 1333.2 | 666.6 | 24 | 7 | 1.8280 | 1.0471 | 1.000 | 1.637 | 1715 | 1256 | 47,500 | 0.0128 | 0.0136 | 0.0161 | 1435 |
| Gannet/TP | 1333.2 | 666.6 | 26 | 7 | 1.2176 | 1.0471 | 1.014 | 1.660 | 1833 | 1256 | 52,800 | 0.0128 | 0.0135 | 0.0160 | 1445 |
| Dunlin/TP | 1431 | 715.5 | 20 | 7 | 1.2016 | 1.1239 | 1.009 | 1.651 | 1611 | 1348 | 39,300 | 0.0120 | 0.0129 | 0.0153 | 1475 |
| Stilt/TP | 1431 | 715.5 | 24 | 7 | 1.2696 | 1.1239 | 1.036 | 1.696 | 1841 | 1348 | 51,000 | 0.0119 | 0.0126 | 0.0151 | 1500 |
| Startling/TP | 1431 | 715.5 | 26 | 7 | 1.3070 | 1.1239 | 1.051 | 1.719 | 1968 | 1348 | 56,700 | 0.0119 | 0.0127 | 0.0150 | 1510 |
| Redwing/TP | 1431 | 715.5 | 30 | 19 | 1.3802 | 1.1239 | 1.081 | 1.769 | 2220 | 1351 | 69,200 | 0.0118 | 0.0125 | 0.0148 | 1530 |
| Coot/TP | 1590 | 795 | 36 | 1 | 1.2835 | 1.2488 | 1.040 | 1.702 | 1607 | 1490 | 33,500 | 0.0108 | 0.0114 | 0.0135 | 1585 |
| Macaw/TP | 1590 | 795 | 42 | 7 | 1.3130 | 1.2488 | 1.055 | 1.726 | 1715 | 1498 | 40,100 | 0.0108 | 0.0113 | 0.0135 | 1595 |
| Turbit/TP | 1590 | 795 | 20 | 7 | 1.3351 | 1.2488 | 1.063 | 1.740 | 1790 | 1498 | 43,600 | 0.0108 | 0.0118 | 0.0139 | 1575 |
| Tern/TP | 1590 | 795 | 45 | 7 | 1.3351 | 1.2488 | 1.063 | 1.740 | 1790 | 1498 | 44,200 | 0.0108 | 0.0118 | 0.0139 | 1570 |

(Continued on page 12)

1-800-945-5542

www.PriorityWire.com



ACSR/TP Bare Overhead Conductor

| Code Word | Conductor Size | Component | | | | Total Cross Sectional Area | | Outer Dimensions | Equiv. Diameter | Weight | | Rated Strength | Resistance** | | | Ampacity* |
|---------------|----------------|-----------------------|-----------|--------|--------|----------------------------|------------|------------------|-----------------|-----------|-----------|----------------|--------------|------------|------------|-----------|
| | | No. x Strand Diameter | | Total | AL | Total | AL | | | DC @ 20°C | AC @ 25°C | | AC @ 75°C | | | |
| | | AL | Steel | | | | | | | | | | | sq. inches | sq. inches | |
| | | AWG/kcmil | AWG/kcmil | inches | inches | sq. inches | sq. inches | | | inches | inches | | lbs/mft | lbs/mft | lbs | |
| Puffin/TP | 1590 | 795 | 22 | 7 | 1.3714 | 1.2488 | 1.077 | 1.763 | 1913 | 1498 | 49,700 | 0.0108 | 0.0117 | 0.0138 | 1590 | |
| Cuckoo/TP | 1590 | 795 | 24 | 7 | 1.4107 | 1.2488 | 1.092 | 1.787 | 2046 | 1498 | 55,800 | 0.0107 | 0.0116 | 0.0137 | 1600 | |
| Condor/TP | 1590 | 795 | 54 | 7 | 1.4107 | 1.2488 | 1.092 | 1.787 | 2046 | 1498 | 56,400 | 0.0107 | 0.0116 | 0.0140 | 1580 | |
| Drake/TP | 1590 | 795 | 26 | 7 | 1.4522 | 1.2488 | 1.107 | 1.812 | 2186 | 1498 | 63,000 | 0.0107 | 0.0115 | 0.0136 | 1615 | |
| Mallard/TP | 1590 | 795 | 30 | 19 | 1.5335 | 1.2488 | 1.140 | 1.865 | 2467 | 1501 | 76,900 | 0.0106 | 0.0114 | 0.0134 | 1635 | |
| Surfbird/TP | 1749 | 874.5 | 20 | 7 | 1.4686 | 1.3737 | 1.115 | 1.825 | 1969 | 1647 | 47,500 | 0.0098 | 0.0109 | 0.0127 | 1670 | |
| Turnstone/TP | 1800 | 900 | 20 | 7 | 1.5115 | 1.4137 | 1.131 | 1.852 | 2026 | 1695 | 48,300 | 0.0096 | 0.0106 | 0.0124 | 1700 | |
| Ruddy/TP | 1800 | 900 | 45 | 7 | 1.5115 | 1.4137 | 1.131 | 1.852 | 2026 | 1695 | 48,900 | 0.0096 | 0.0106 | 0.0125 | 1695 | |
| Canary/TP | 1800 | 900 | 54 | 7 | 1.5970 | 1.4137 | 1.162 | 1.902 | 2316 | 1695 | 63,800 | 0.0095 | 0.0104 | 0.0125 | 1705 | |
| Catbird/TP | 1908 | 954 | 36 | 1 | 1.5402 | 1.4985 | 1.140 | 1.865 | 1929 | 1788 | 39,500 | 0.0090 | 0.0096 | 0.0114 | 1780 | |
| Phoenix/TP | 1908 | 954 | 42 | 7 | 1.5756 | 1.4985 | 1.155 | 1.891 | 2058 | 1797 | 46,800 | 0.0090 | 0.0095 | 0.0113 | 1790 | |
| Corncake/TP | 1908 | 954 | 20 | 7 | 1.6021 | 1.4985 | 1.165 | 1.906 | 2148 | 1797 | 51,200 | 0.0090 | 0.0101 | 0.0118 | 1760 | |
| Rail/TP | 1908 | 954 | 45 | 7 | 1.6021 | 1.4985 | 1.165 | 1.906 | 2148 | 1797 | 51,800 | 0.0090 | 0.0101 | 0.0118 | 1755 | |
| Towhee/TP | 1908 | 954 | 48 | 7 | 1.6307 | 1.4985 | 1.175 | 1.923 | 2245 | 1797 | 56,900 | 0.0090 | 0.0094 | 0.0112 | 1810 | |
| Redbird/TP | 1908 | 954 | 24 | 7 | 1.6928 | 1.4985 | 1.196 | 1.958 | 2455 | 1797 | 67,000 | 0.0089 | 0.0099 | 0.0116 | 1790 | |
| Cardinal/TP | 1908 | 954 | 54 | 7 | 1.6928 | 1.4985 | 1.196 | 1.958 | 2455 | 1797 | 67,700 | 0.0089 | 0.0099 | 0.0119 | 1770 | |
| Canvasback/TP | 1908 | 954 | 30 | 19 | 1.8402 | 1.4985 | 1.248 | 2.043 | 2961 | 1802 | 92,200 | 0.0089 | 0.0097 | 0.0113 | 1830 | |
| Snowbird/TP | 2067 | 1033.5 | 42 | 7 | 1.7069 | 1.6234 | 1.203 | 1.968 | 2230 | 1947 | 50,700 | 0.0083 | 0.0088 | 0.0105 | 1885 | |
| Ortolan/TP | 2067 | 1033.5 | 45 | 7 | 1.7357 | 1.6234 | 1.212 | 1.984 | 2327 | 1947 | 55,400 | 0.0083 | 0.0094 | 0.0110 | 1840 | |
| Whooper/TP | 2067 | 1033.5 | 48 | 7 | 1.7666 | 1.6234 | 1.223 | 2.001 | 2432 | 1947 | 61,600 | 0.0083 | 0.0087 | 0.0103 | 1905 | |
| Curlew/TP | 2067 | 1033.5 | 54 | 7 | 1.8339 | 1.6234 | 1.245 | 2.038 | 2659 | 1947 | 73,300 | 0.0083 | 0.0092 | 0.0110 | 1855 | |
| Avocet/TP | 2226 | 1113 | 42 | 7 | 1.8382 | 1.7483 | 1.248 | 2.043 | 2401 | 2097 | 54,200 | 0.0077 | 0.0082 | 0.0098 | 1975 | |
| Bluejay/TP | 2226 | 1113 | 45 | 7 | 1.8692 | 1.7483 | 1.258 | 2.059 | 2506 | 2097 | 59,600 | 0.0077 | 0.0089 | 0.0104 | 1920 | |
| Bullfinch/TP | 2226 | 1113 | 48 | 7 | 1.9025 | 1.7483 | 1.269 | 2.077 | 2619 | 2097 | 65,600 | 0.0077 | 0.0081 | 0.0096 | 2000 | |
| Finch/TP | 2226 | 1113 | 54 | 19 | 1.9697 | 1.7483 | 1.292 | 2.115 | 2858 | 2107 | 78,100 | 0.0077 | 0.0087 | 0.0104 | 1940 | |

All values are nominal and subject to correction

*Ampacity based on conductor temperature rise of 50°C over 25°C ambient, 2ft/sec crosswind, 0.5 coefficient of emissivity, no sun, @60 Hz. Ampacity for single-layer conductors does not include the effect of core magnetization.

**Resistance is based on conductivity of 61.2% IACS @20°C for aluminum and 8% IACS at 20°C for the steel core. AC resistance values for single-layer conductors do not include the effect of core magnetization.

Note: Twisting lay length of ACSR/TP: 6.5 feet for sizes up to 4/0AWG, and 9 foot for 250kcmil and larger.

Packing Note: Must have 18" of cable exposed and secured at inner end. Three clamps over twisted pair at each end of shipping reel.



ACSS - Aluminum Conductor Steel Supported

APPLICATION: Used for Overhead distribution and transmission lines, new line applications that require high emergency loading, and where vibration is a problem. ACSS operates continuously at high temperatures up to 250°C full strength. Although similar to standard ACSR, ACSS sags less and is self-damping during installation. It also carries a higher current than standard ACSR.

CONSTRUCTION: Aluminum alloy 1350 wires, concentrically stranded around a steel core. Non-Specular finish available on request.

SPECIFICATIONS: ACSS bare conductors meet or exceed the following ASTM specifications: B-498 Zinc-Coated Steel Core Wire for Aluminum Conductors, Steel Reinforced (ACSR) • B-606 High-Strength Zinc-Coated (Galvanized) Steel Core Wire for Aluminum and Aluminum-Alloy Conductors, Steel Reinforced • B-609 Aluminum 1350 Round Wire, Annealed and Intermediate Tempers, for Electrical Purposes • B-802 Zinc-5% Aluminum-Mischmetal Alloy-Coated Steel Core Wire for Aluminum Conductors, Steel Reinforced (ACSR) • B-803 High-Strength Zinc-5 % Aluminum-Mischmetal Alloy-Coated Steel Core Wire for Use in Overhead Electrical Conductors • B-856 Concentric Lay-Stranded Aluminum Conductors, Coated Steel Supported (ACSS)

| Code Word | Conductor Size | Stranding (AL/STL) | Diameter | | | Comp. Cable O.D. | Weight | | | Rated Strength | | Resistance* | | Ampacity* @ 200°C |
|----------------|----------------|--------------------|-----------------|--------|------------|------------------|--------|-----|-------|----------------|---------------|-------------|-----------|-------------------|
| | | | Individual Wire | | Steel Core | | AL | STL | Total | Standard | High Strength | DC @ 20°C | AC @ 75°C | |
| | AL | | STL | inches | | lbs/kft | | | | | | | | |
| | inches | | inches | | amps | | | | | | | | | |
| Partridge/ACSS | 266.8 | 26/7 | 0.1013 | 0.0788 | 0.236 | 0.642 | 252 | 116 | 367 | 8880 | 9730 | 0.0619 | 0.0761 | 812 |
| Junco/ACSS | 266.8 | 30/7 | 0.0943 | 0.0943 | 0.283 | 0.660 | 252 | 166 | 418 | 11700 | 13000 | 0.0615 | 0.0756 | 822 |
| Ostrich/ACSS | 300.0 | 26/7 | 0.1074 | 0.0835 | 0.251 | 0.680 | 283 | 130 | 413 | 10000 | 10900 | 0.0551 | 0.0677 | 877 |
| Linnet/ACSS | 336.4 | 26/7 | 0.1137 | 0.0885 | 0.265 | 0.720 | 317 | 146 | 463 | 11200 | 12300 | 0.0491 | 0.0604 | 945 |
| Oriole/ACSS | 336.4 | 30/7 | 0.1059 | 0.1059 | 0.318 | 0.741 | 318 | 209 | 527 | 14800 | 16300 | 0.0488 | 0.0600 | 957 |
| Brant/ACSS | 397.5 | 24/7 | 0.1287 | 0.0858 | 0.257 | 0.772 | 375 | 137 | 512 | 11000 | 12100 | 0.0417 | 0.0514 | 1047 |
| Ibis/ACSS | 397.5 | 26/7 | 0.1236 | 0.0962 | 0.289 | 0.783 | 375 | 172 | 547 | 13000 | 14200 | 0.0416 | 0.0512 | 1054 |
| Lark/ACSS | 397.5 | 30/7 | 0.1151 | 0.1151 | 0.345 | 0.806 | 376 | 247 | 622 | 17500 | 19300 | 0.0413 | 0.0508 | 1068 |
| Flicker/ACSS | 477.0 | 24/7 | 0.1410 | 0.0940 | 0.282 | 0.846 | 450 | 164 | 614 | 1300 | 14200 | 0.0348 | 0.0429 | 1180 |
| Hawk/ACSS | 477.0 | 26/7 | 0.1354 | 0.1053 | 0.316 | 0.858 | 450 | 207 | 657 | 15600 | 17100 | 0.0346 | 0.0427 | 1188 |
| Hen/ACSS | 477.0 | 30/7 | 0.1261 | 0.1261 | 0.378 | 0.883 | 451 | 296 | 747 | 21000 | 22700 | 0.0344 | 0.0424 | 1204 |
| Parakeet/ACSS | 556.5 | 24/7 | 0.1523 | 0.1015 | 0.305 | 0.914 | 522 | 192 | 714 | 15200 | 16600 | 0.0298 | 0.0368 | 1306 |
| Dove/ACSS | 556.5 | 26/7 | 0.1463 | 0.1138 | 0.341 | 0.927 | 525 | 241 | 766 | 18200 | 19900 | 0.0297 | 0.0366 | 1315 |
| Eagle/ACSS | 556.5 | 30/7 | 0.1362 | 0.1362 | 0.409 | 0.953 | 526 | 345 | 871 | 24500 | 26500 | 0.0295 | 0.0363 | 1331 |
| Peacock/ACSS | 605.0 | 24/7 | 0.1588 | 0.1058 | 0.318 | 0.953 | 571 | 209 | 779 | 16500 | 18100 | 0.0274 | 0.0339 | 1379 |
| Squab/ACSS | 605.0 | 26/7 | 0.1525 | 0.1186 | 0.356 | 0.966 | 571 | 262 | 833 | 19700 | 21300 | 0.0273 | 0.0345 | 1389 |
| Wood Duck/ACSS | 605.0 | 30/7 | 0.1420 | 0.1420 | 0.426 | 0.994 | 572 | 375 | 947 | 26000 | 28300 | 0.0271 | 0.0337 | 1407 |
| Teal/ACSS | 605.0 | 30/19 | 0.1420 | 0.0852 | 0.426 | 0.994 | 572 | 367 | 940 | 26600 | 29300 | 0.0272 | 0.0335 | 1406 |
| Rook/ACSS | 636.0 | 24/7 | 0.1628 | 0.1085 | 0.326 | 0.977 | 600 | 219 | 819 | 17300 | 19000 | 0.0261 | 0.0322 | 1425 |
| Grosbeak/ACSS | 636.0 | 26/7 | 0.1564 | 0.1216 | 0.365 | 0.991 | 600 | 275 | 875 | 20700 | 22400 | 0.0260 | 0.0321 | 1435 |
| Scoter/ACSS | 636.0 | 24/7 | 0.1456 | 0.1456 | 0.437 | 1.019 | 601 | 395 | 996 | 27400 | 29700 | 0.0258 | 0.0318 | 1454 |
| Egret/ACSS | 636.0 | 26/7 | 0.1456 | 0.0874 | 0.437 | 1.019 | 601 | 387 | 988 | 28000 | 30900 | 0.0258 | 0.0319 | 1453 |
| Flamingo/ACSS | 666.6 | 24/7 | 0.1667 | 0.1111 | 0.333 | 1.000 | 629 | 230 | 859 | 18200 | 19900 | 0.0249 | 0.0308 | 1470 |
| Gannet/ACSS | 666.6 | 26/7 | 0.1601 | 0.1245 | 0.374 | 1.014 | 629 | 289 | 917 | 21700 | 23400 | 0.0248 | 0.0306 | 1480 |
| Stilt/ACSS | 715.5 | 24/7 | 0.1727 | 0.1151 | 0.345 | 1.036 | 675 | 247 | 921 | 19500 | 21300 | 0.0232 | 0.0287 | 1540 |
| Starling/ACSS | 715.5 | 26/7 | 0.1659 | 0.1290 | 0.387 | 1.051 | 375 | 310 | 985 | 23300 | 25200 | 0.0231 | 0.0286 | 1550 |
| Redwing/ACSS | 715.5 | 30/19 | 0.1544 | 0.0927 | 0.463 | 1.081 | 677 | 435 | 1111 | 30800 | 34000 | 0.0230 | 0.0284 | 1570 |
| Cuckoo/ACSS | 795.0 | 24/7 | 0.1820 | 0.1213 | 0.364 | 1.092 | 750 | 274 | 1024 | 21700 | 23300 | 0.0209 | 0.0259 | 1650 |
| Drake/ACSS | 795.0 | 26/7 | 0.1749 | 0.1360 | 0.408 | 1.107 | 750 | 344 | 1094 | 25900 | 28000 | 0.0209 | 0.0257 | 1662 |
| Macaw/ACSS | 795.0 | 42/7 | 0.1376 | 0.0764 | 0.229 | 1.055 | 750 | 109 | 859 | 11800 | 12600 | 0.0211 | 0.0262 | 1662 |

(Continued on page 14)

1-800-945-5542

www.PriorityWire.com



CONTINUED

ACSS - Aluminum Conductor Steel Supported

| Code Word | Conductor Size | Stranding (AL/STL) | Diameter | | | Comp. Cable O.D. | Weight | | | Rated Strength | | Resistance* | | Ampacity* @ 200°C |
|------------------|----------------|--------------------|-----------------|--------|------------|------------------|--------|-----|-------|----------------|---------------|-------------|-----------|-------------------|
| | | | Individual Wire | | Steel Core | | AL | STL | Total | Standard | High Strength | DC @ 20°C | AC @ 75°C | |
| | AL | | STL | inches | | inches | | | | | | | | inches |
| | inches | | inches | | | | | | | | | | | |
| Tern/ACSS | 795.0 | 45/7 | 0.1329 | 0.0886 | 0.266 | 1.063 | 750 | 146 | 896 | 14200 | 15200 | 0.0210 | 0.0263 | 1618 |
| Condor/ACSS | 795.0 | 54/7 | 0.1213 | 0.1213 | 0.364 | 1.092 | 750 | 274 | 1024 | 21700 | 23300 | 0.0209 | 0.0266 | 1618 |
| Mallard/ACSS | 795.0 | 30/19 | 0.1628 | 0.0977 | 0.488 | 1.139 | 752 | 483 | 1235 | 34300 | 37900 | 0.0207 | 0.0255 | 1683 |
| Ruddy/ACSS | 900.0 | 45/7 | 0.1414 | 0.0943 | 0.283 | 1.131 | 849 | 165 | 1014 | 15800 | 17000 | 0.0186 | 0.0233 | 1755 |
| Canary/ACSS | 900.0 | 54/7 | 0.1291 | 0.1291 | 0.387 | 1.162 | 849 | 310 | 1159 | 24600 | 26400 | 0.0184 | 0.0238 | 1756 |
| Redbird/ACSS | 900.0 | 24/7 | 0.1994 | 0.1329 | 0.399 | 1.198 | 900 | 329 | 1229 | 26000 | 28000 | 0.0174 | 0.0217 | 1859 |
| Rail/ACSS | 954.0 | 45/7 | 0.1456 | 0.0971 | 0.291 | 1.165 | 900 | 175 | 1075 | 16700 | 18000 | 0.0175 | 0.0220 | 1824 |
| Towhee/ACSS | 954.0 | 48/7 | 0.1410 | 0.1097 | 0.329 | 1.175 | 900 | 224 | 1124 | 19700 | 21300 | 0.0150 | 0.0218 | 1842 |
| Cardinal/ACSS | 954.0 | 54/7 | 0.1329 | 0.1329 | 0.399 | 1.196 | 900 | 329 | 1229 | 26000 | 28000 | 0.0174 | 0.0233 | 996 |
| Canvasback/ACSS | 954.0 | 30/19 | 0.1783 | 0.1070 | 0.535 | 1.248 | 902 | 580 | 1482 | 41100 | 45400 | 0.0172 | 0.0214 | 1897 |
| Snowbird/ACSS | 1033.5 | 42/7 | 0.1569 | 0.0871 | 0.261 | 1.203 | 975 | 141 | 1116 | 15400 | 16500 | 0.0162 | 0.0204 | 1924 |
| Ortolan/ACSS | 1033.5 | 45/7 | 0.1515 | 0.1010 | 0.303 | 1.212 | 975 | 190 | 1165 | 18100 | 19500 | 0.0162 | 0.0204 | 1921 |
| Curlew/ACSS | 1033.5 | 54/7 | 0.1383 | 0.1383 | 0.415 | 1.245 | 975 | 356 | 1331 | 28200 | 30300 | 0.0161 | 0.0206 | 1924 |
| Grackle/ACSS | 1192.5 | 54/19 | 0.1486 | 0.0892 | 0.446 | 1.338 | 1120 | 409 | 1531 | 32600 | 35500 | 0.0140 | 0.0182 | 2085 |
| Bluejay/ACSS | 1113.0 | 45/7 | 0.1573 | 0.1048 | 0.315 | 1.258 | 1050 | 205 | 1254 | 19500 | 21100 | 0.0150 | 0.0190 | 2017 |
| Finch/ACSS | 1113.0 | 54/19 | 0.1436 | 0.0861 | 0.431 | 1.292 | 1055 | 376 | 1431 | 30400 | 33200 | 0.0150 | 0.0193 | 2015 |
| Bunting/ACSS | 1192.5 | 45/7 | 0.1628 | 0.1085 | 0.326 | 1.302 | 1125 | 219 | 1344 | 21400 | 23500 | 0.0140 | 0.0178 | 2110 |
| Bittern/ACSS | 1272.0 | 45/7 | 0.1681 | 0.1121 | 0.336 | 1.345 | 1200 | 234 | 1434 | 22300 | 24000 | 0.0131 | 0.0167 | 2200 |
| Pheasant/ACSS | 1272.0 | 54/19 | 0.1535 | 0.0921 | 0.460 | 1.381 | 1206 | 429 | 1635 | 34100 | 37300 | 0.0131 | 0.0169 | 2200 |
| Dipper/ACSS | 1351.0 | 45/7 | 0.1733 | 0.1155 | 0.347 | 1.386 | 1274 | 248 | 1523 | 23700 | 2500 | 0.0124 | 0.0158 | 2289 |
| Martin/ACSS | 1351.0 | 54/19 | 0.1582 | 0.0949 | 0.475 | 1.424 | 1281 | 456 | 1737 | 36200 | 39600 | 0.0123 | 0.0160 | 2288 |
| Bobolink/ACSS | 1431.0 | 45/7 | 0.1783 | 0.1189 | 0.357 | 1.427 | 1350 | 263 | 1613 | 25100 | 27000 | 0.0117 | 0.0150 | 2375 |
| Plover/ACSS | 1431.0 | 54/19 | 0.1628 | 0.0977 | 0.488 | 1.465 | 1356 | 483 | 1939 | 38400 | 41900 | 0.0117 | 0.0151 | 2375 |
| Nuthatch/ACSS | 1510.0 | 45/7 | 0.1832 | 0.1221 | 0.366 | 1.465 | 1424 | 278 | 1702 | 26500 | 28100 | 0.0111 | 0.0143 | 2459 |
| Parrot/ACSS | 1510.0 | 54/19 | 0.1672 | 0.1003 | 0.502 | 1.505 | 1431 | 510 | 1941 | 40400 | 44200 | 0.0110 | 0.0144 | 2460 |
| Ratite/ACSS | 1590.0 | 42/7 | 0.1946 | 0.1081 | 0.324 | 1.492 | 1500 | 217 | 1717 | 23400 | 25000 | 0.0105 | 0.0136 | 2543 |
| Lapwing/ACSS | 1590.0 | 45/7 | 0.1880 | 0.1253 | 0.376 | 1.504 | 1500 | 292 | 1792 | 27900 | 29600 | 0.0105 | 0.0136 | 2543 |
| Falcon/ACSS | 1590.0 | 54/19 | 0.1716 | 0.1030 | 0.515 | 1.544 | 1507 | 537 | 2044 | 42600 | 46600 | 0.0105 | 0.0137 | 2545 |
| Chukar/ACSS | 1780.0 | 84/19 | 0.1456 | 0.0873 | 0.437 | 1.601 | 1687 | 386 | 2073 | 35400 | 38200 | 0.0094 | 0.0122 | 2751 |
| Mockingbird/ACSS | 2034.5 | 72/7 | 0.1681 | 0.1121 | 0.336 | 1.681 | 1928 | 234 | 2162 | 7200 | 28900 | 0.0083 | 0.0110 | 2960 |
| Roadrunner/ACSS | 2057.0 | 76/19 | 0.1645 | 0.0768 | 0.384 | 1.700 | 1950 | 298 | 2248 | 31700 | 33900 | 0.0082 | 0.0108 | 2992 |
| Bluebird/ACSS | 2156.0 | 84/19 | 0.1602 | 0.0961 | 0.481 | 1.762 | 2044 | 468 | 2511 | 42100 | 45000 | 0.0078 | 0.0103 | 3106 |
| Kiwi/ACSS | 2167.0 | 72/7 | 0.1735 | 0.1157 | 0.347 | 1.735 | 2054 | 249 | 2303 | 29000 | 30800 | 0.0078 | 0.0104 | 3080 |
| Thrasher/ACSS | 2312.0 | 76/19 | 0.1744 | 0.0814 | 0.407 | 1.802 | 2191 | 335 | 2527 | 35600 | 38100 | 0.0073 | 0.0098 | 3218 |
| Joree/ACSS | 2515.0 | 76/19 | 0.1819 | 0.0849 | 0.425 | 1.880 | 2384 | 365 | 2749 | 38700 | 41400 | 0.0067 | 0.0092 | 3390 |

All values are nominal and subject to correction

*Resistance and ampacity based on an aluminum conductivity of 63%, IACS at 20°C, and a steel conductivity of 8% IACS at 20°C.

*Ampacity based on a 200°C conductor temperature, 25°C ambient temperature, 2ft/sec. Wind

Packing Note: Must have 18" of cable exposed and secured at inner end

1-800-945-5542

www.PriorityWire.com



ACSS/TW - Aluminum Conductor Steel Supported Trapezoidal Shaped Aluminum Strands

APPLICATION: Used as bare overhead transmission cable and as primary and secondary distribution cable. It is designed to continuously operate up to 250°C without losing strength.

CONSTRUCTION: Aluminum alloy 1350 wires, concentrically stranded around a steel core with one or more layers of 63% minimum average conductivity aluminum 1350-O wire stranded around it. The steel core carries most or the entire mechanical load of the conductor due to the fully annealed or soft temper aluminum. The steel core wires are protected from corrosion by a zinc-5% aluminum-mischmetal-alloy coating. Diameter or Area Equal to Standard ACSR Sizes.

SPECIFICATIONS: ACSS/TW bare conductors meet or exceed the following ASTM specifications: B-498 Zinc-Coated (Galvanized) Steel Core Wire for Use in Overhead Electrical Conductors • B-500 Metallic Coated Stranded Steel Core for Aluminum Conductors, Steel Reinforced • B-606 High-Strength Zinc-Coated (Galvanized) Steel Core Wire for Aluminum and Aluminum-Alloy Conductors, Steel Reinforced • B-609 Aluminum 1350 Round Wire, Annealed and Intermediate Tempers, for Electrical Purposes • B-802 Zinc-5% Aluminum-Mischmetal Alloy-Coated Steel Core Wire for Aluminum Conductors, Steel Reinforced • B-803 High Strength Zinc-5% Aluminum-Mischmetal Alloy-Coated Steel Core Wire for Aluminum and Aluminum-Alloy Conductors, Steel Reinforced • B-857 Shaped Wire Compact Concentric-Lay-Stranded Aluminum Conductors, Coated-Steel Supported (ACSS/TW) • B-957 Extra-High-Strength and Ultra-High-Strength Zinc-Coated (Galvanized) Steel Core Wire for Overhead Electrical Conductors • B-958 Extra-High-Strength and Ultra-High-Strength Class A Zinc-5% Aluminum-Mischmetal Alloy-Coated Steel Core Wire for Use in Overhead Electrical Conductors

| Code Word | Size | Type no. | Cross Sectional Area | | Stranding | | | Diameter | | Weight | | | Rated Breaking Strength | | |
|--------------------|---------|----------|----------------------|--------|--------------|----------------|--------------------|------------|----------------|---------|---------|-------|-------------------------|---------------|---------------------|
| | | | AL | Total | Layers of AL | AL Wires | Indiv. Steel Wires | Steel Core | Complete Cable | AL | STL | Total | Standard Strength | High Strength | Ultra High Strength |
| | sq. in. | | sq. in. | no. | no. | no. x diameter | inches | inches | lbs/kft | lbs/kft | lbs/kft | lbs | lbs | lbs | |
| Flicker ACSS/TW | 477 | 13 | 0.3747 | 0.4233 | 2 | 18 | 7 x 0.0940 | 0.282 | 0.776 | 448 | 165 | 612 | 13,000 | 14,200 | 16,400 |
| Hawk ACSS/TW | 477 | 16 | 0.3746 | 0.4356 | 2 | 18 | 7 x 0.1053 | 0.316 | 0.790 | 448 | 206 | 655 | 15,600 | 17,100 | 19,800 |
| Dove ACSS/TW | 556.5 | 16 | 0.4371 | 0.5083 | 2 | 20 | 7 x 0.1138 | 0.341 | 0.850 | 523 | 241 | 765 | 18,200 | 19,900 | 23,100 |
| Mystic ACSS/TW | 666.6 | 13 | 0.5236 | 0.5915 | 2 | 20 | 7 x 0.1111 | 0.333 | 0.910 | 626 | 230 | 856 | 18,200 | 19,900 | 22,900 |
| Maumee ACSS/TW | 768.2 | 13 | 0.6041 | 0.6826 | 2 | 20 | 7 x 0.1195 | 0.358 | 0.980 | 721 | 266 | 987 | 21,000 | 23,000 | 26,500 |
| Wabash ACSS/TW | 762.8 | 16 | 0.5992 | 0.6966 | 2 | 20 | 7 x 0.1331 | 0.399 | 0.990 | 717 | 330 | 1047 | 24,900 | 26,900 | 31,200 |
| Drake ACSS/TW | 795 | 16 | 0.6244 | 0.7261 | 2 | 20 | 7 x 0.1360 | 0.408 | 1.010 | 748 | 344 | 1092 | 25,900 | 28,000 | 32,500 |
| Rail ACSS/TW | 954.0 | 7 | 0.7493 | 0.8011 | 3 | 32 | 7 x 0.0971 | 0.291 | 1.060 | 899 | 176 | 1075 | 16,700 | 18,000 | 20,400 |
| Cardinal ACSS/TW | 954.0 | 13 | 0.7493 | 0.8464 | 2 | 20 | 7 x 0.1329 | 0.399 | 1.084 | 896 | 329 | 1225 | 26,000 | 28,000 | 32,300 |
| Suwannee ACSS/TW | 959.6 | 16 | 0.7537 | 0.8762 | 2 | 22 | 7 x 0.1493 | 0.448 | 1.108 | 903 | 415 | 1318 | 30,700 | 33,100 | 38,600 |
| Curlew ACSS/TW | 1033.5 | 13 | 0.8117 | 0.9169 | 2 | 21 | 7 x 0.1383 | 0.415 | 1.130 | 970 | 356 | 1326 | 28,200 | 30,300 | 35,000 |
| Hudson ACSS/TW | 1158.4 | 13 | 0.9092 | 1.0280 | 2 | 25 | 7 x 0.1467 | 0.440 | 1.196 | 1087 | 401 | 1488 | 31,100 | 33,500 | 38,800 |
| Grackle ACSS/TW | 1192.5 | 13 | 0.9366 | 1.0554 | 3 | 38 | 19 x 0.0892 | 0.446 | 1.225 | 1126 | 403 | 1529 | 32,600 | 35,500 | 41,500 |
| Pheasant ACSS/TW | 1272.0 | 13 | 0.9990 | 1.1250 | 3 | 39 | 19 x 0.0921 | 0.461 | 1.260 | 1201 | 429 | 1630 | 34,100 | 37,300 | 43,000 |
| Martin ACSS/TW | 1351.5 | 13 | 1.0620 | 1.1964 | 3 | 39 | 19 x 0.0949 | 0.470 | 1.300 | 1276 | 456 | 1732 | 36,200 | 39,600 | 45,600 |
| Merrimack ACSS/TW | 1433.6 | 13 | 1.1250 | 1.2677 | 3 | 39 | 19 x 0.0978 | 0.489 | 1.340 | 1356 | 484 | 1840 | 38,400 | 42,000 | 48,400 |
| Pecos ACSS/TW | 1622.0 | 13 | 1.2736 | 1.4425 | 3 | 39 | 19 x 0.1064 | 0.532 | 1.420 | 1531 | 573 | 2104 | 45,000 | 49,300 | 56,900 |
| Chukar ACSS/TW | 1780.0 | 8 | 1.3986 | 1.5126 | 3 | 37 | 19 x 0.0874 | 0.437 | 1.450 | 1673 | 388 | 2061 | 35,300 | 38,200 | 43,900 |
| Cumberland ACSS/TW | 1926.9 | 13 | 1.5134 | 1.7049 | 3 | 42 | 19 x 0.1133 | 0.567 | 1.545 | 1819 | 650 | 2469 | 51,600 | 56,400 | 65,000 |
| Santee ACSS/TW | 2627.3 | 8 | 2.0630 | 2.2317 | 4 | 64 | 19 x 0.1062 | 0.531 | 1.761 | 2492 | 571 | 3063 | 51,300 | 55,600 | 63,100 |

All values are nominal and subject to correction

Packing Note: Must have 18" of cable exposed and secured at inner end

1-800-945-5542

www.PriorityWire.com



Covered Line Wire Aluminum Conductor

APPLICATION: Used primarily for overhead secondary distribution lines. Not an electrically insulated conductor and is treated as bare conductor when installed.

CONSTRUCTION: Aluminum alloy 1350-H19, 6201-T81, or ACSR conductors, concentrically stranded and covered for protection against circuit interruption due to weather with polyethylene, high density polyethylene (HDPE) or cross-linked polyethylene (XLP).

SPECIFICATIONS: Covered Line Wire meets or exceeds the following ASTM specifications: B-230 Aluminum Wire, 1350-H19 for electrical purposes • B-231 Aluminum conductors, Concentric-lay-Stranded • B-232 Aluminum conductors, Concentric-lay-Stranded, Coated Steel Reinforced (ACSR) • B-399 Concentric-lay-Stranded, 6201-T81 Aluminum Alloy

| Code Word | Size AWG/kcmil | Stranding (AL/Steel) | Insulation Thickness inches | Outside Diameter inches | Rated Strength lbs | Weight | | Ampacity* |
|------------------------|-------------------|-------------------------|-----------------------------------|-------------------------------|--------------------------|----------------|-----------------|--------------|
| | | | | | | XLP lbs/kft | POLY lbs/kft | 75°C amps |
| ACSR Conductors | | | | | | | | |
| Walnut | 6 | 6/1 | 0.030 | 0.26 | 1,131 | 49 | 47 | 105 |
| Butternut | 4 | 6/1 | 0.030 | 0.30 | 1,760 | 72 | 70 | 135 |
| Hickory | 4 | 7/1 | 0.030 | 0.31 | 2,240 | 82 | 80 | 135 |
| Pignut | 2 | 6/1 | 0.045 | 0.40 | 2,710 | 118 | 115 | 180 |
| Beech | 2 | 7/1 | 0.045 | 0.41 | 3,460 | 134 | 131 | 180 |
| Chestnut | 1 | 6/1 | 0.045 | 0.43 | 3,370 | 146 | 142 | 210 |
| Almond | 1/0 | 6/1 | 0.060 | 0.51 | 4,160 | 190 | 185 | 235 |
| Pecan | 2/0 | 6/1 | 0.060 | 0.55 | 5,040 | 234 | 228 | 270 |
| Filbert | 3/0 | 6/1 | 0.060 | 0.61 | 6,290 | 289 | 281 | 305 |
| Buckeye | 4/0 | 6/1 | 0.060 | 0.67 | 7,930 | 366 | 349 | 345 |
| Hackberry | 266.8 | 18/1 | 0.060 | 0.71 | 6,540 | 355 | 347 | 435 |
| AAC Conductors | | | | | | | | |
| Apple | 6 | Solid | 0.030 | 0.22 | 445 | 33 | 32 | 105 |
| Pear | 4 | Solid | 0.030 | 0.26 | 675 | 49 | 47 | 135 |
| Apricot | 4 | 7 | 0.030 | 0.29 | 790 | 52 | 51 | 140 |
| Peach | 2 | 7 | 0.045 | 0.37 | 1,220 | 87 | 84 | 180 |
| Quince | 1/0 | 7 | 0.060 | 0.48 | 1,790 | 141 | 136 | 240 |
| Orange | 2/0 | 7 | 0.060 | 0.52 | 2,260 | 172 | 166 | 280 |
| Fig | 3/0 | 7 | 0.060 | 0.57 | 2,740 | 211 | 204 | 320 |
| Olive | 4/0 | 7 | 0.060 | 0.63 | 3,450 | 259 | 251 | 370 |
| Mulberry | 266.8 | 19 | 0.060 | 0.69 | 4,470 | 314 | 306 | 430 |
| Anona | 336.4 | 19 | 0.060 | 0.77 | 5,535 | 388 | 379 | 495 |
| Huckleberry | 477 | 37 | 0.080 | 0.93 | 7,820 | 550 | 538 | 610 |
| Paw Paw | 556.5 | 37 | 0.080 | 0.99 | 8,950 | 633 | 619 | 670 |

All values are nominal and subject to correction

NOTE: The code words as given apply to conventional high density polyethylene covered ACSR & AAC line wires.

Line wire with AAAC 6201-T81 conductor available upon request.

*Ampacity ratings are based on 75°C conductor temperature 25°C ambient temperature at sea level, emissivity 0.91, coefficient of absorption 0.95, thermal resistivity of covering -375°C-Cm2/watt-CM, wind speed 2ft./sec in sun.

1-800-945-5542

www.PriorityWire.com



Duplex Overhead Aluminum Conductor (Service Drop)

APPLICATION: To supply power aerial service for temporary service at construction sites, outdoor or street lighting. For service at 600 volts or lower at a conductor temperature of 75°C maximum for polyethylene insulation or 90°C maximum for cross linked insulation.

CONSTRUCTION: Concentrically stranded, compressed 1350-H19 aluminum conductor, cross-linked polyethylene (XLP) or polyethylene (PE) insulation, concentrically stranded AAC, ACSR, or AAAC 6201 alloy neutral messenger.

SPECIFICATIONS: Duplex service drop cable meets or exceeds the following ASTM specifications: B-230 Aluminum 1350-H19 Wire for Electrical Purposes • B-231 Concentric-Lay-Stranded Aluminum 1350 Conductors • B-232 Concentric-Lay-Stranded Aluminum Conductors, Coated-Steel Reinforced (ACSR) • B-399 Concentric-Lay-Stranded Aluminum-Alloy 6201-T81 Conductors • Service Drop cable meets or exceeds all applicable requirements of ICEA S-76-474

OPTIONS: Ridged Phase ID

| Code Word | Phase Conductor | | | Bare Neutral Messenger | | | Completed Cable | | | Ampacity* | |
|---------------------------------------|-----------------|----------------|----------------------|------------------------|----------------|-------------------|-----------------|---------|------|-----------|---------|
| | Size | No. of Strands | Insulation Thickness | Size | No. of Strands | Breaking Strength | Diameter | Weight | | XLP 90°C | PE 75°C |
| | | | | | | | | XLP | Poly | | |
| AWG/kcmil | | inches | AWG/kcmil | | lbs | inches | lbs/kft | lbs/kft | amps | amps | |
| AAC NEUTRAL MESSENGER | | | | | | | | | | | |
| Pekingese | 6 | Solid | 0.045 | 6 | 7 | 563 | 0.44 | 64 | 62 | 85 | 70 |
| Collie | 6 | 7 | 0.045 | 6 | 7 | 563 | 0.46 | 69 | 63 | 85 | 70 |
| Dachshund | 4 | Solid | 0.045 | 4 | 7 | 881 | 0.53 | 96 | 93 | 115 | 90 |
| Spaniel | 4 | 7 | 0.045 | 4 | 7 | 881 | 0.56 | 101 | 95 | 115 | 90 |
| Doberman | 2 | 7 | 0.045 | 2 | 7 | 1,350 | 0.68 | 153 | 146 | 150 | 120 |
| Malamute | 1/0 | 19 | 0.060 | 1/0 | 7 | 1,990 | 0.87 | 243 | 234 | 205 | 160 |
| ACSR NEUTRAL MESSENGER | | | | | | | | | | | |
| Setter | 6 | Solid | 0.045 | 6 | 6/1 | 1,190 | 0.46 | 75 | 73 | 85 | 70 |
| Shepherd | 6 | 7 | 0.045 | 6 | 6/1 | 1,190 | 0.48 | 78 | 75 | 85 | 70 |
| Eskimo | 4 | Solid | 0.045 | 4 | 6/1 | 1,860 | 0.55 | 114 | 112 | 115 | 90 |
| Terrier | 4 | 7 | 0.045 | 4 | 6/1 | 1,860 | 0.58 | 119 | 114 | 115 | 90 |
| Chow | 2 | 7 | 0.045 | 2 | 6/1 | 2,850 | 0.70 | 182 | 175 | 150 | 120 |
| Bull | 1/0 | 19 | 0.060 | 1/0 | 6/1 | 4,380 | 0.90 | 289 | 280 | 205 | 160 |
| 6201 ALLOY NEUTRAL MESSENGER** | | | | | | | | | | | |
| Chihuahua | 6 | Solid | 0.045 | 6 | 7 | 1,110 | 0.46 | 68 | 66 | 85 | 70 |
| Vizsla | 6 | 7 | 0.045 | 6 | 7 | 1,110 | 0.48 | 71 | 67 | 85 | 70 |
| Harrier | 4 | Solid | 0.045 | 4 | 7 | 1,760 | 0.55 | 102 | 100 | 115 | 90 |
| Whippet | 4 | 7 | 0.045 | 4 | 7 | 1,760 | 0.58 | 107 | 102 | 115 | 90 |
| Schnauzer | 2 | 7 | 0.045 | 2 | 7 | 2,800 | 0.70 | 163 | 156 | 150 | 120 |
| Heeler | 1/0 | 19 | 0.060 | 1/0 | 7 | 4,460 | 0.90 | 1259 | 251 | 205 | 160 |

All values are nominal and subject to correction

*Conductor temperature of 90°C for XLP, 75°C for PE; ambient temperature of 40°C, emissivity 0.9; 2ft/sec. wind in sun.

**Designated 6201 neutral sizes are ACSR 6/1 diameter equivalent, phase conductor resistivity equivalent per ASTM B399.

1-800-945-5542

www.PriorityWire.com



Triplex Overhead Aluminum Conductor (Service Drop)

APPLICATION: To supply power from the utility lines to the consumer weather head. For service at 600 volts or lower (phase to phase) at a conductor temperature of 90°C maximum for cross linked insulation or 75°C maximum for polyethylene insulation.

CONSTRUCTION: Concentrically stranded, compressed 1350-H19 aluminum conductor, cross-linked polyethylene (XLP) or polyethylene (PE) insulation, concentrically stranded AAC, ACSR or 6201 alloy bare neutral messenger.

SPECIFICATIONS: Triplex service drop cable meets or exceeds the following ASTM specifications: B-230 Aluminum 1350-H19 Wire for Electrical Purposes • B-231 Concentric-Lay-Stranded Aluminum 1350 Conductors • B-232 Concentric-Lay-Stranded Aluminum Conductors, Coated-Steel Reinforced (ACSR) • B-399 Concentric-Lay-Stranded Aluminum-Alloy 6201-T81 Conductors • Service Drop cable meets or exceeds all applicable requirements of ICEA S-76-474

OPTIONS: Ridged Phase ID

RUS ACCEPTED

| Code Word | Phase Conductor | | | Bare Neutral Messenger | | | Completed Cable | | | Ampacity* | |
|--|-------------------|----------------|--------------------------------|------------------------|----------------|--------------------------|--------------------|----------------|-----------------|---------------------|--------------------|
| | Size AWG/kcmil | No. of Strands | Insulation Thickness inches | Size AWG/kcmil | No. of Strands | Breaking Strength lbs | Diameter inches | Weight | | XLP 90°C amps | PE 75°C amps |
| | | | | | | | | XLP lbs/kft | Poly lbs/kft | | |
| 6201 ALLOY NEUTRAL MESSENGER* | | | | | | | | | | | |
| Minex | 6 | Solid | 0.045 | 6 | 7 | 1,110 | 0.53 | 107 | 103 | 85 | 70 |
| Hippa | 6 | 7 | 0.045 | 6 | 7 | 1,110 | 0.57 | 107 | 106 | 85 | 70 |
| Prawn | 4 | Solid | 0.045 | 4 | 7 | 1,760 | 0.62 | 158 | 154 | 115 | 90 |
| Barnacles | 4 | 7 | 0.045 | 4 | 7 | 1,760 | 0.67 | 160 | 157 | 115 | 90 |
| Shrimp | 2 | 7 | 0.045 | 2 | 7 | 2,800 | 0.80 | 243 | 238 | 150 | 120 |
| Gammarus | 1/0 | 7 | 0.060 | 1/0 | 7 | 4,460 | 1.02 | 390 | 384 | 205 | 160 |
| Leda | 1/0 | 19 | 0.060 | 1/0 | 7 | 4,460 | 1.03 | 384 | 378 | 205 | 160 |
| Dungeness | 2/0 | 7 | 0.060 | 2/0 | 7 | 5,390 | 1.11 | 481 | 474 | 235 | 185 |
| Cyclops | 2/0 | 19 | 0.060 | 2/0 | 7 | 5,390 | 1.12 | 473 | 467 | 235 | 185 |
| Flustra | 3/0 | 19 | 0.060 | 3/0 | 7 | 6,790 | 1.23 | 596 | 589 | 275 | 215 |
| Lepas | 4/0 | 19 | 0.060 | 4/0 | 7 | 8,560 | 1.35 | 725 | 716 | 315 | 245 |
| 6201 ALLOY REDUCED NEUTRAL MESSENGER* | | | | | | | | | | | |
| Artemia | 4 | Solid | 0.045 | 6 | 7 | 1,110 | 0.62 | 134 | 132 | 115 | 90 |
| Crab | 4 | 7 | 0.045 | 6 | 7 | 1,110 | 0.67 | 144 | 141 | 115 | 90 |
| Solaster | 2 | 7 | 0.045 | 4 | 7 | 1,760 | 0.80 | 216 | 212 | 150 | 120 |
| Sandcrab | 1/0 | 7 | 0.060 | 2 | 7 | 2,800 | 1.02 | 348 | 341 | 205 | 160 |
| Echinus | 1/0 | 19 | 0.060 | 2 | 7 | 2,800 | 1.03 | 342 | 336 | 205 | 160 |
| Crayfish | 2/0 | 7 | 0.060 | 1 | 7 | 3,530 | 1.11 | 453 | 423 | 235 | 185 |
| Sipho | 2/0 | 19 | 0.060 | 1 | 7 | 3,530 | 1.12 | 441 | 423 | 235 | 185 |
| Fulgar | 3/0 | 19 | 0.060 | 1/0 | 7 | 4,460 | 1.23 | 525 | 518 | 275 | 215 |
| Arca | 4/0 | 19 | 0.060 | 2/0 | 7 | 5,390 | 1.35 | 640 | 632 | 315 | 245 |
| AAC NEUTRAL MESSENGER | | | | | | | | | | | |
| Haiotis | 6 | Solid | 0.045 | 6 | 7 | 563 | 0.53 | 103 | 99 | 85 | 70 |
| Patella | 6 | 7 | 0.045 | 6 | 7 | 563 | 0.57 | 104 | 102 | 85 | 70 |
| Fusus | 4 | Solid | 0.045 | 4 | 7 | 881 | 0.62 | 152 | 148 | 115 | 90 |
| Oyster | 4 | 7 | 0.045 | 4 | 7 | 881 | 0.67 | 154 | 152 | 115 | 90 |

All values are nominal and subject to correction

*Designated 6201 neutral sizes are ACSR 6/1 diameter equivalent, phase conductor resistivity equivalent per ASTM B399

**Conductor temperature of 90°C for XLP, 75°C for Poly; ambient temperature of 40°C, emissivity 0.9, 2ft/sec. wind in sun.

(Continued on page 19)

1-800-945-5542

www.PriorityWire.com



Triplex Overhead Aluminum Conductor (Service Drop)

CONTINUED

| Code Word | Phase Conductor | | | Bare Neutral Messenger | | | Completed Cable | | | Ampacity* | |
|--|-----------------|----------------|----------------------|------------------------|----------------|-------------------|-----------------|-----------|-------|-----------|---------|
| | Size | No. of Strands | Insulation Thickness | Size | No. of Strands | Breaking Strength | Diameter | Weight | | XLP 90°C | PE 75°C |
| | AWG/kcmil | | | inches | | | | AWG/kcmil | lbs | | |
| AAC NEUTRAL MESSENGER (continued) | | | | | | | | | | | |
| Mussel | 2 | 7 | 0.045 | 4 | 7 | 881 | 0.80 | 208 | 204 | 150 | 120 |
| Clam | 2 | 7 | 0.045 | 2 | 7 | 1,350 | 0.80 | 232 | 228 | 150 | 120 |
| Snail | 1/0 | 7 | 0.060 | 2 | 7 | 1,350 | 1.02 | 336 | 329 | 205 | 160 |
| Murex | 1/0 | 7 | 0.060 | 1/0 | 7 | 1,990 | 1.02 | 374 | 367 | 205 | 160 |
| Purpura | 1/0 | 19 | 0.060 | 1/0 | 7 | 1,990 | 1.03 | 368 | 362 | 205 | 160 |
| Nassa | 2/0 | 7 | 0.060 | 2/0 | 7 | 2,510 | 1.11 | 461 | 453 | 235 | 185 |
| Melita | 3/0 | 19 | 0.060 | 3/0 | 19 | 3,310 | 1.23 | 585 | 563 | 275 | 215 |
| Portunus | 4/0 | 19 | 0.060 | 4/0 | 19 | 4,020 | 1.35 | 693 | 684 | 315 | 245 |
| Nannynose | 336.4 | 19 | 0.080 | 336.4 | 19 | 6,146 | 1.72 | 1,110 | 1,096 | 420 | 325 |
| ACSR FULL SIZE NEUTRAL MESSENGER | | | | | | | | | | | |
| Paludina | 6 | Solid | 0.045 | 6 | 6/1 | 1,190 | 0.53 | 114 | 113 | 85 | 70 |
| Voluta | 6 | 7 | 0.045 | 6 | 6/1 | 1,190 | 0.57 | 115 | 112 | 85 | 70 |
| Whelk | 4 | Solid | 0.045 | 4 | 6/1 | 1,860 | 0.62 | 163 | 161 | 115 | 90 |
| Periwinkle | 4 | 7 | 0.045 | 4 | 6/1 | 1,860 | 0.67 | 172 | 169 | 115 | 90 |
| Conch | 2 | 7 | 0.045 | 2 | 6/1 | 2,850 | 0.80 | 262 | 257 | 150 | 120 |
| Neritina | 1/0 | 7 | 0.060 | 1/0 | 6/1 | 4,380 | 1.02 | 420 | 414 | 205 | 160 |
| Genia | 1/0 | 19 | 0.060 | 1/0 | 6/1 | 4,380 | 1.03 | 414 | 408 | 205 | 160 |
| Runcina | 2/0 | 7 | 0.060 | 2/0 | 6/1 | 5,310 | 1.11 | 519 | 512 | 235 | 185 |
| Triton | 2/0 | 19 | 0.060 | 2/0 | 6/1 | 5,310 | 1.12 | 511 | 505 | 235 | 185 |
| Cherrystone | 3/0 | 7 | 0.060 | 3/0 | 6/1 | 6,620 | 1.22 | 656 | 643 | 275 | 215 |
| Mursia | 3/0 | 19 | 0.060 | 3/0 | 6/1 | 6,620 | 1.23 | 633 | 626 | 275 | 215 |
| Razor | 4/0 | 7 | 0.060 | 4/0 | 6/1 | 8,350 | 1.34 | 814 | 799 | 315 | 245 |
| Zuzara | 4/0 | 19 | 0.060 | 4/0 | 6/1 | 8,350 | 1.35 | 785 | 777 | 315 | 245 |
| Limpet | 336.4 | 19 | 0.080 | 336.4 | 18/1 | 8,680 | 1.72 | 1,161 | 1,147 | 420 | 325 |
| ACSR REDUCED SIZE NEUTRAL MESSENGER | | | | | | | | | | | |
| Scallop | 4 | Solid | 0.045 | 6 | 6/1 | 1,190 | 0.62 | 142 | 139 | 115 | 90 |
| Strombus | 4 | 7 | 0.045 | 6 | 6/1 | 1,190 | 0.67 | 151 | 148 | 115 | 90 |
| Cockle | 2 | 7 | 0.045 | 4 | 6/1 | 1,860 | 0.80 | 228 | 224 | 150 | 120 |
| Janthina | 1/0 | 7 | 0.060 | 2 | 6/1 | 2,850 | 1.02 | 367 | 360 | 205 | 160 |
| Ranella | 1/0 | 19 | 0.060 | 2 | 6/1 | 2,850 | 1.03 | 361 | 356 | 205 | 160 |
| Cavolinia | 2/0 | 7 | 0.060 | 1 | 6/1 | 3,550 | 1.11 | 452 | 444 | 235 | 185 |
| Clio | 2/0 | 19 | 0.060 | 1 | 6/1 | 3,550 | 1.12 | 444 | 437 | 235 | 185 |
| Sanddollar | 3/0 | 7 | 0.060 | 1/0 | 6/1 | 4,380 | 1.22 | 570 | 557 | 275 | 215 |
| Aega | 3/0 | 19 | 0.060 | 1/0 | 6/1 | 4,380 | 1.23 | 565 | 552 | 275 | 215 |
| Cuttlefish | 4/0 | 7 | 0.060 | 2/0 | 6/1 | 5,310 | 1.33 | 706 | 691 | 315 | 245 |
| Cerapus | 4/0 | 19 | 0.060 | 2/0 | 6/1 | 5,310 | 1.35 | 678 | 670 | 315 | 245 |
| Cowry | 336.4 | 19 | 0.080 | 4/0 | 6/1 | 8,350 | 1.72 | 1,135 | 1,093 | 420 | 325 |

All values are nominal and subject to correction

**Conductor temperature of 90°C for XLP, 75°C for Poly; ambient temperature of 40°C, emissivity 0.9, 2ft/sec. wind in sun.

1-800-945-5542

www.PriorityWire.com



Quadruplex Overhead Aluminum Conductor (Service Drop)

APPLICATION: Used to supply 3 phase power, usually from a pole-mounted transformer, to the user's service head where connection to the service entrance cable is made. To be used at voltages of 600 volts or less phase to phase and at conductor temperatures not to exceed 75°C for polyethylene insulated conductors or 90°C for cross-linked-polyethylene (XLP) insulated conductors.

CONSTRUCTION: Concentrically stranded, compressed 1350-H19 aluminum conductor, cross-linked polyethylene (XLP) or polyethylene (PE) insulation, concentrically stranded AAC, ACSR or 6201 alloy bare neutral messenger.

SPECIFICATIONS: Quadruplex service drop cable meets or exceeds the following ASTM specifications: B-230 Aluminum 1350-H19 Wire for Electrical Purposes • B-231 Concentric-Lay-Stranded Aluminum 1350 Conductors • B-232 Concentric-Lay-Stranded Aluminum Conductors, Coated-Steel Reinforced (ACSR) • B-399 Concentric-Lay-Stranded Aluminum-Alloy 6201-T81 Conductors • Service Drop cable meets or exceeds all applicable requirements of ICEA S-76-474

OPTIONS: Ridged Phase ID

RUS ACCEPTED

| Code Word | Phase Conductor | | | Bare Neutral Messenger | | | Completed Cable | | | Ampacity* | |
|-------------------------------|-----------------|----------------|----------------------|------------------------|----------------|-------------------|-----------------|---------|---------|-----------|---------|
| | Size | No. of Strands | Insulation Thickness | Size | No. of Strands | Breaking Strength | Diameter | Weight | | XLP 90°C | PE 75°C |
| | | | | | | | | XLP | Poly | | |
| | AWG/kcmil | | inches | AWG/kcmil | | lbs | inches | lbs/kft | lbs/kft | amps | amps |
| AAC NEUTRAL MESSENGER | | | | | | | | | | | |
| Clydesdale | 4 | Solid | 0.045 | 4 | 7 | 881 | 0.68 | 208 | 201 | 100 | 80 |
| Pinto | 4 | 7/w | 0.045 | 4 | 7 | 881 | 0.73 | 223 | 207 | 100 | 80 |
| Mustang | 2 | 7/w | 0.045 | 2 | 7 | 1,350 | 0.88 | 333 | 312 | 135 | 105 |
| Criollo | 1/0 | 19/w | 0.060 | 1/0 | 7 | 1,990 | 1.12 | 529 | 504 | 180 | 140 |
| Percheron | 2/0 | 19/w | 0.060 | 2/0 | 7 | 2,510 | 1.24 | 649 | 620 | 205 | 160 |
| Hanoverian | 3/0 | 19/w | 0.060 | 3/0 | 19 | 3,310 | 1.36 | 799 | 765 | 235 | 185 |
| Oldenburg | 4/0 | 19/w | 0.060 | 4/0 | 19 | 4,020 | 1.50 | 986 | 946 | 275 | 210 |
| Lippizaner | 336.4 | 19/w | 0.080 | 336.4 | 19 | 6,146 | 1.91 | 1,546 | 1,519 | 370 | 280 |
| ACSR NEUTRAL MESSENGER | | | | | | | | | | | |
| Morochuca | 6 | Solid | 0.045 | 6 | 6/1 | 1,190 | 0.58 | 152 | 147 | 75 | 60 |
| Chola | 6 | 7/W | 0.045 | 6 | 6/1 | 1,190 | 0.62 | 162 | 151 | 75 | 60 |
| Morgan | 4 | Solid | 0.045 | 4 | 6/1 | 1,860 | 0.69 | 226 | 220 | 100 | 80 |
| Hackney | 4 | 7/W | 0.045 | 4 | 6/1 | 1,860 | 0.74 | 241 | 226 | 100 | 80 |
| Palomino | 2 | 7/W | 0.045 | 2 | 6/1 | 2,850 | 0.89 | 362 | 342 | 135 | 105 |
| Costena | 1/0 | 19/W | 0.060 | 1/0 | 6/1 | 4,380 | 1.14 | 575 | 550 | 180 | 140 |
| Grullo | 2/0 | 19/W | 0.060 | 2/0 | 6/1 | 5,310 | 1.26 | 707 | 678 | 205 | 160 |
| Suffolk | 3/0 | 19/W | 0.060 | 3/0 | 6/1 | 6,620 | 1.38 | 872 | 838 | 235 | 180 |
| Appaloosa | 4/0 | 19/W | 0.060 | 4/0 | 6/1 | 8,350 | 1.52 | 1,079 | 1,039 | 275 | 210 |
| Bronco | 336.4 | 19/W | 0.080 | 336.4 | 18/1 | 8,580 | 1.92 | 1,613 | 1,568 | 370 | 280 |
| Gelding | 336.4 | 19/W | 0.080 | 4/0 | 6/1 | 8,350 | 1.85 | 1,548 | 1,494 | 370 | 280 |
| Hurricane | 500 | 37/w | 0.080 | 336.4 | 26/7 | 14,100 | 2.21 | 2,196 | 2,186 | 480 | 360 |

All values are nominal and subject to correction

*Conductor temperature of 90°C for XLP, 75°C for Poly; ambient temperature of 40°C, emissivity 0.9, 2ft/sec. wind in sun.

(Continued on page 21)

1-800-945-5542

www.PriorityWire.com



Quadruplex Overhead Aluminum Conductor (Service Drop)

CONTINUED

| Code Word | Phase Conductor | | | Bare Neutral Messenger | | | Completed Cable | | | Ampacity* | |
|---------------------------------------|-------------------|----------------|--------------------------------|------------------------|----------------|--------------------------|--------------------|----------------|-----------------|---------------------|--------------------|
| | Size AWG/kcmil | No. of Strands | Insulation Thickness inches | Size AWG/kcmil | No. of Strands | Breaking Strength lbs | Diameter inches | Weight | | XLP 90°C amps | PE 75°C amps |
| | | | | | | | | XLP lbs/kft | Poly lbs/kft | | |
| 6201 ALLOY NEUTRAL MESSENGER** | | | | | | | | | | | |
| Bay | 6 | Solid | 0.045 | 6 | 7 | 1,110 | 0.59 | 145 | 140 | 75 | 60 |
| French-Coach | 6 | 7/w | 0.045 | 6 | 7 | 1,110 | 0.63 | 155 | 144 | 75 | 60 |
| German-Coach | 4 | Solid | 0.045 | 4 | 7 | 1,760 | 0.69 | 214 | 208 | 100 | 80 |
| Arabian | 4 | 7/w | 0.045 | 4 | 7 | 1,760 | 0.74 | 229 | 214 | 100 | 80 |
| Belgian | 2 | 7/w | 0.045 | 2 | 7 | 2,800 | 0.89 | 344 | 323 | 135 | 105 |
| Shetland | 1/0 | 19/w | 0.060 | 1/0 | 7 | 4,460 | 1.14 | 546 | 521 | 180 | 140 |
| Thoroughbred | 2/0 | 19/w | 0.060 | 2/0 | 7 | 5,390 | 1.26 | 670 | 641 | 205 | 160 |
| Trotter | 3/0 | 19/w | 0.060 | 3/0 | 7 | 6,790 | 1.38 | 825 | 791 | 135 | 185 |
| Walking | 4/0 | 19/w | 0.060 | 4/0 | 7 | 8,560 | 1.52 | 1,019 | 979 | 275 | 210 |

All values are nominal and subject to correction

*Conductor temperature of 90°C for XLP, 75°C for Poly; ambient temperature of 40°C, emissivity 0.9, 2ft/sec. wind in sun.

**Designated 6201 neutral sizes are ACSR 6/1 diameter equivalent, phase conductor resistivity equivalent per ASTM B399.

1-800-945-5542

www.PriorityWire.com



15-35kV TR-XLPE URD

DESCRIPTION: Single conductor cable with solid or filled strand aluminum or copper conductors, triple extruded insulation system consisting of a thermosetting semiconducting conductor shield, high dielectric strength TRXLPE insulation, thermosetting semiconducting insulation shield, copper concentric neutral wires, water swellable agents, black encapsulating linear low-density polyethylene (LLDPE) jacket.

CONDUCTOR: Solid or Class B Compressed concentric strand aluminum alloy 1350 or soft drawn annealed copper per ASTM. Stranded conductors are water-blocked with conductor filling compound.

CONDUCTOR SHIELD: Extruded thermosetting semiconducting shield which is free stripping from the conductor and bonded to the insulation.

INSULATION: Natural high dielectric TRXLPE insulation, exhibiting an optimum balance of mechanical and electrical properties, assuring resistance to treeing.

INSULATION SHIELD: Extruded thermosetting semiconducting shield with controlled adhesion to the insulation providing the required balance between electrical integrity and ease of stripping.

METALLIC SHIELD: Solid bare copper wires, helically applied and uniformly spaced.

JACKET: Black insulating sunlight resistant linear low density polyethylene encapsulating the neutral wires with three extruded red stripes and NESC lightning bolt symbol. Sequential footage markings.

SPECIFICATIONS: Cable meets ICEA S-94-649, AEIC CS8. ASTM: B3, B5, B8, B230, B231, B609

RUS ACCEPTED

| Conductor | Insulation Thickness (mils) | Concentric Neutral | Conductor Diameter (in) | Insulation Diameter (in) | Insulation Shield Diameter (in) | Jacket Diameter (in) | Cable Weight (lbs/ft) | Minimum Bending Radius (in) | 90°C in Duct | | | 90°C Direct Buried | | | | | |
|---|-----------------------------|--------------------|-------------------------|--------------------------|---------------------------------|----------------------|-----------------------|-----------------------------|-----------------|--|---|---|-----------------|--|---|--|----|
| | | | | | | | | | Ampacity (amps) | +/- Sequence Impedance Reactance ($\mu\Omega/\text{ft}$) | +/- Sequence Impedance Resistance ($\mu\Omega/\text{ft}$) | Zero Sequence Impedance Reactance ($\mu\Omega/\text{ft}$) | Ampacity (Amps) | +/- Sequence Impedance Reactance ($\mu\Omega/\text{ft}$) | +/- Sequence Impedance Resistance ($\mu\Omega/\text{ft}$) | Zero Sequence Impedance Resistance ($\mu\Omega/\text{ft}$) | |
| 15KV 100% ALUMINUM SINGLE PHASE - FULL NEUTRAL | | | | | | | | | | | | | | | | | |
| 2 SOLID AL | 175 | 10-#14 | 0.258 | 0.65 | 0.72 | 0.96 | 456 | 8 | 123 | 663 | 29 | 663 | 169 | 663 | 29 | 663 | 30 |
| 2 AWG AL | 175 | 10-#14 | 0.284 | 0.68 | 0.75 | 0.99 | 475 | 8 | 124 | 669 | 30 | 669 | 170 | 669 | 30 | 669 | 31 |
| 1 SOLID AL | 175 | 13-#14 | 0.289 | 0.69 | 0.75 | 0.99 | 521 | 8 | 141 | 518 | 28 | 518 | 193 | 518 | 28 | 518 | 29 |
| 1 AWG AL | 175 | 13-#14 | 0.324 | 0.72 | 0.79 | 1.03 | 545 | 9 | 143 | 523 | 27 | 523 | 194 | 523 | 27 | 523 | 28 |
| 1/0 SOLID AL | 175 | 16-#14 | 0.325 | 0.72 | 0.79 | 1.03 | 593 | 9 | 160 | 415 | 27 | 415 | 219 | 415 | 27 | 415 | 27 |
| 1/0 AWG AL | 175 | 16-#14 | 0.364 | 0.76 | 0.83 | 1.07 | 621 | 9 | 162 | 420 | 26 | 420 | 220 | 420 | 26 | 420 | 26 |
| 2/0 AWG AL | 175 | 13-#12 | 0.408 | 0.80 | 0.87 | 1.14 | 748 | 10 | 186 | 328 | 25 | 328 | 251 | 328 | 25 | 328 | 25 |
| 3/0 AWG AL | 175 | 16-#12 | 0.458 | 0.85 | 0.92 | 1.19 | 864 | 10 | 212 | 263 | 24 | 263 | 284 | 263 | 24 | 263 | 24 |
| 4/0 AWG AL | 175 | 13-#10 | 0.515 | 0.91 | 0.98 | 1.29 | 1055 | 11 | 243 | 207 | 23 | 207 | 323 | 207 | 23 | 207 | 23 |
| 250 MCM AL | 175 | 16-#10 | 0.561 | 0.97 | 1.03 | 1.35 | 1228 | 11 | 270 | 171 | 22 | 171 | 358 | 171 | 22 | 171 | 22 |
| 350 MCM AL | 175 | 16-#9 | 0.664 | 1.07 | 1.16 | 1.49 | 1556 | 12 | 321 | 130 | 21 | 130 | 420 | 130 | 21 | 130 | 20 |
| 15KV 100% ALUMINUM THREE PHASE - ONE-THIRD NEUTRAL | | | | | | | | | | | | | | | | | |
| 2 SOLID AL | 175 | 6-#14 | 0.258 | 0.65 | 0.72 | 0.96 | 409 | 8 | 126 | 329 | 51 | 872 | 175 | 338 | 103 | 857 | 30 |
| 2 AWG AL | 175 | 6-#14 | 0.284 | 0.68 | 0.75 | 0.99 | 429 | 8 | 126 | 335 | 51 | 879 | 175 | 344 | 102 | 865 | 31 |
| 1 SOLID AL | 175 | 6-#14 | 0.289 | 0.69 | 0.75 | 0.99 | 440 | 8 | 143 | 261 | 49 | 805 | 199 | 270 | 100 | 791 | 29 |
| 1 AWG AL | 175 | 6-#14 | 0.324 | 0.72 | 0.79 | 1.03 | 463 | 9 | 144 | 266 | 48 | 811 | 199 | 275 | 98 | 798 | 28 |
| 1/0 SOLID AL | 175 | 6-#14 | 0.325 | 0.72 | 0.79 | 1.03 | 476 | 9 | 163 | 207 | 47 | 752 | 225 | 216 | 98 | 739 | 27 |
| 1/0 AWG AL | 175 | 6-#14 | 0.364 | 0.76 | 0.83 | 1.07 | 504 | 9 | 163 | 212 | 46 | 758 | 225 | 221 | 96 | 745 | 26 |
| 2/0 AWG AL | 175 | 7-#14 | 0.408 | 0.80 | 0.87 | 1.11 | 564 | 9 | 186 | 168 | 44 | 637 | 255 | 178 | 93 | 627 | 25 |
| 3/0 AWG AL | 175 | 9-#14 | 0.458 | 0.85 | 0.92 | 1.16 | 646 | 10 | 212 | 133 | 43 | 498 | 286 | 145 | 89 | 491 | 24 |
| 4/0 AWG AL | 175 | 11-#14 | 0.515 | 0.91 | 0.98 | 1.22 | 740 | 10 | 241 | 106 | 41 | 405 | 320 | 120 | 86 | 400 | 23 |
| 250 MCM AL | 175 | 13-#14 | 0.561 | 0.97 | 1.03 | 1.27 | 836 | 11 | 265 | 91 | 40 | 343 | 345 | 106 | 82 | 339 | 21 |
| 350 MCM AL | 175 | 18-#14 | 0.664 | 1.07 | 1.16 | 1.39 | 1068 | 12 | 319 | 66 | 38 | 247 | 398 | 84 | 76 | 245 | 19 |
| 500 MCM AL | 175 | 16-#12 | 0.794 | 1.20 | 1.29 | 1.56 | 1407 | 13 | 385 | 48 | 37 | 174 | 451 | 68 | 67 | 173 | 18 |
| 750 MCM AL | 175 | 24-#12 | 0.974 | 1.39 | 1.47 | 1.81 | 1985 | 15 | 468 | 35 | 35 | 117 | 507 | 57 | 55 | 116 | 16 |
| 1000 MCM AL | 175 | 20-#10 | 1.124 | 1.54 | 1.65 | 2.03 | 2568 | 17 | 529 | 28 | 33 | 89 | 549 | 49 | 47 | 88 | 16 |

| Conductor | Insulation Thickness (mil/s) | Concentric Neutral | Conductor Diameter (in) | Insulation Diameter (in) | Insulation Shield Diameter (in) | Jacket Diameter (in) | Cable Weight (lbs/ft) | Minimum Bending Radius (in) | 90°C InDuct | | | 90°C Direct Buried | | | | | |
|---|------------------------------|--------------------|-------------------------|--------------------------|---------------------------------|----------------------|-----------------------|-----------------------------|-----------------|---|--|--|---|--|--|-----|----|
| | | | | | | | | | Ampacity (amps) | +/- Sequence Impedance Resistance (μΩ/ft) | +/- Sequence Impedance Reactance (μΩ/ft) | Zero Sequence Impedance Resistance (μΩ/ft) | +/- Sequence Impedance Resistance (μΩ/ft) | +/- Sequence Impedance Reactance (μΩ/ft) | Zero Sequence Impedance Resistance (μΩ/ft) | | |
| 15 KV 133% ALUMINUM SINGLE PHASE - FULL NEUTRAL | | | | | | | | | | | | | | | | | |
| 2 SOLID AL | 220 | 10-#14 | 0.258 | 0.74 | 0.81 | 1.05 | 514 | 9 | 123 | 663 | 29 | 663 | 169 | 663 | 29 | 663 | 30 |
| 2 AWG AL | 220 | 10-#14 | 0.284 | 0.77 | 0.84 | 1.08 | 535 | 9 | 124 | 669 | 30 | 669 | 170 | 669 | 30 | 669 | 31 |
| 1 SOLID AL | 220 | 13-#14 | 0.289 | 0.78 | 0.84 | 1.08 | 581 | 9 | 141 | 518 | 28 | 518 | 193 | 518 | 28 | 518 | 29 |
| 1 AWG AL | 220 | 13-#14 | 0.324 | 0.81 | 0.88 | 1.12 | 607 | 9 | 143 | 523 | 27 | 523 | 194 | 523 | 27 | 523 | 28 |
| 1/0 SOLID AL | 220 | 16-#14 | 0.325 | 0.81 | 0.88 | 1.12 | 655 | 9 | 160 | 415 | 27 | 415 | 219 | 415 | 27 | 415 | 27 |
| 1/0 AWG AL | 220 | 16-#14 | 0.364 | 0.85 | 0.92 | 1.16 | 685 | 10 | 162 | 420 | 26 | 420 | 220 | 420 | 26 | 420 | 26 |
| 2/0 AWG AL | 220 | 13-#12 | 0.408 | 0.89 | 0.96 | 1.23 | 817 | 10 | 186 | 328 | 25 | 328 | 251 | 328 | 25 | 328 | 25 |
| 3/0 AWG AL | 220 | 16-#12 | 0.458 | 0.94 | 1.01 | 1.28 | 935 | 11 | 212 | 263 | 24 | 263 | 284 | 263 | 24 | 263 | 24 |
| 4/0 AWG AL | 220 | 13-#10 | 0.515 | 1.00 | 1.07 | 1.38 | 1132 | 12 | 243 | 207 | 23 | 207 | 323 | 207 | 23 | 207 | 23 |
| 250MCM AL | 220 | 16-#10 | 0.561 | 1.06 | 1.14 | 1.46 | 1330 | 12 | 270 | 171 | 22 | 171 | 358 | 171 | 22 | 171 | 22 |
| 350 MCM AL | 220 | 16-#9 | 0.664 | 1.16 | 1.25 | 1.58 | 1645 | 13 | 321 | 130 | 21 | 130 | 420 | 130 | 21 | 130 | 20 |
| 15KV 133% ALUMINUM THREE PHASE - ONE-THIRD NEUTRAL | | | | | | | | | | | | | | | | | |
| 2 SOLID AL | 220 | 6-#14 | 0.258 | 0.74 | 0.81 | 1.05 | 467 | 9 | 126 | 329 | 51 | 872 | 175 | 338 | 103 | 857 | 30 |
| 2 AWG AL | 220 | 6-#14 | 0.284 | 0.77 | 0.84 | 1.08 | 488 | 9 | 126 | 335 | 51 | 879 | 175 | 344 | 102 | 865 | 31 |
| 1 SOLID AL | 220 | 6-#14 | 0.289 | 0.78 | 0.84 | 1.08 | 499 | 9 | 143 | 261 | 49 | 805 | 199 | 270 | 100 | 791 | 29 |
| 1 AWG AL | 220 | 6-#14 | 0.324 | 0.81 | 0.88 | 1.12 | 525 | 9 | 144 | 266 | 48 | 811 | 199 | 275 | 98 | 798 | 28 |
| 1/0 SOLID AL | 220 | 6-#14 | 0.325 | 0.81 | 0.88 | 1.12 | 538 | 9 | 163 | 207 | 47 | 752 | 225 | 216 | 98 | 739 | 27 |
| 1/0 AWG AL | 220 | 6-#14 | 0.364 | 0.85 | 0.92 | 1.16 | 568 | 10 | 163 | 212 | 46 | 758 | 225 | 221 | 96 | 745 | 26 |
| 2/0 AWG AL | 220 | 7-#14 | 0.408 | 0.89 | 0.96 | 1.20 | 630 | 10 | 186 | 168 | 44 | 637 | 255 | 178 | 93 | 627 | 25 |
| 3/0 AWG AL | 220 | 9-#14 | 0.458 | 0.94 | 1.01 | 1.25 | 715 | 11 | 212 | 133 | 43 | 498 | 286 | 145 | 89 | 491 | 24 |
| 4/0 AWG AL | 220 | 11-#14 | 0.515 | 1.00 | 1.07 | 1.31 | 813 | 11 | 241 | 106 | 41 | 405 | 320 | 120 | 86 | 400 | 23 |
| 250 MCM AL | 220 | 13-#14 | 0.561 | 1.06 | 1.14 | 1.38 | 932 | 12 | 265 | 91 | 40 | 343 | 345 | 106 | 82 | 339 | 21 |
| 350 MCM AL | 220 | 18-#14 | 0.664 | 1.16 | 1.25 | 1.48 | 1150 | 12 | 319 | 66 | 38 | 247 | 398 | 84 | 76 | 245 | 19 |
| 500 MCM AL | 220 | 16-#12 | 0.794 | 1.29 | 1.38 | 1.71 | 1563 | 14 | 385 | 48 | 37 | 174 | 451 | 68 | 67 | 173 | 18 |
| 750 MCM AL | 220 | 24-#12 | 0.974 | 1.48 | 1.56 | 1.90 | 2091 | 16 | 468 | 35 | 35 | 117 | 507 | 57 | 55 | 116 | 16 |
| 1000 MCM AL | 220 | 20-#10 | 1.124 | 1.63 | 1.74 | 2.12 | 2687 | 17 | 529 | 28 | 33 | 89 | 549 | 49 | 47 | 88 | 16 |
| 25KV 100% ALUMINUM SINGLE PHASE - FULL NEUTRAL | | | | | | | | | | | | | | | | | |
| 1 SOLID AL | 260 | 13-#14 | 0.289 | 0.86 | 0.92 | 1.16 | 638 | 10 | 145 | 518 | 33 | 518 | 192 | 518 | 33 | 518 | 33 |
| 1 AWG AL | 260 | 13-#14 | 0.324 | 0.89 | 0.96 | 1.20 | 666 | 10 | 146 | 523 | 31 | 523 | 194 | 523 | 31 | 523 | 32 |
| 1/0 SOLID AL | 260 | 16-#14 | 0.325 | 0.89 | 0.96 | 1.20 | 714 | 10 | 165 | 415 | 31 | 415 | 218 | 415 | 31 | 415 | 31 |
| 1/0 AWG AL | 260 | 16-#14 | 0.364 | 0.93 | 1.00 | 1.24 | 746 | 10 | 166 | 420 | 30 | 420 | 219 | 420 | 30 | 420 | 30 |
| 2/0 AWG AL | 260 | 13-#12 | 0.408 | 0.97 | 1.04 | 1.31 | 882 | 11 | 190 | 328 | 29 | 328 | 250 | 328 | 29 | 328 | 29 |
| 3/0 AWG AL | 260 | 16-#12 | 0.458 | 1.02 | 1.11 | 1.38 | 1023 | 12 | 217 | 263 | 28 | 263 | 283 | 263 | 28 | 263 | 28 |
| 4/0 AWG AL | 260 | 13-#10 | 0.515 | 1.08 | 1.17 | 1.48 | 1227 | 12 | 248 | 207 | 26 | 207 | 322 | 207 | 26 | 207 | 27 |
| 250 MCM AL | 260 | 16-#10 | 0.561 | 1.14 | 1.22 | 1.54 | 1406 | 13 | 276 | 171 | 25 | 171 | 356 | 171 | 25 | 171 | 25 |
| 350 MCM AL | 260 | 16-#9 | 0.664 | 1.24 | 1.33 | 1.72 | 1792 | 14 | 326 | 130 | 23 | 130 | 416 | 130 | 23 | 130 | 23 |
| 25KV 100% ALUMINUM THREE PHASE - ONE-THIRD NEUTRAL | | | | | | | | | | | | | | | | | |
| 1 SOLID AL | 260 | 6-#14 | 0.289 | 0.86 | 0.92 | 1.16 | 556 | 10 | 146 | 261 | 53 | 801 | 196 | 269 | 101 | 766 | 33 |
| 1 AWG AL | 260 | 6-#14 | 0.324 | 0.89 | 0.96 | 1.20 | 584 | 10 | 146 | 266 | 52 | 807 | 196 | 274 | 99 | 792 | 32 |
| 1/0 SOLID AL | 260 | 6-#14 | 0.325 | 0.89 | 0.96 | 1.20 | 597 | 10 | 166 | 207 | 51 | 748 | 222 | 215 | 98 | 734 | 31 |

| Conductor | Insulation Thickness (mil) | Insulation Concentric Neutral | Conductor Diameter (in) | Insulation Diameter (in) | Insulation Shield Diameter (in) | Jacket Diameter (in) | Cable Weight (lbs/ft) | Minimum Bending Radius (in) | 90° C in Duct | | | 90° C Direct Buried | | | | | | |
|---|----------------------------|-------------------------------|-------------------------|--------------------------|---------------------------------|----------------------|-----------------------|-----------------------------|-------------------|---|--|--|-------------------|---|--|--|-----|----|
| | | | | | | | | | Amperacity (amps) | +/- Sequence Impedance Resistance (μΩ/ft) | +/- Sequence Impedance Reactance (μΩ/ft) | Zero Sequence Impedance Resistance (μΩ/ft) | Amperacity (amps) | +/- Sequence Impedance Resistance (μΩ/ft) | +/- Sequence Impedance Reactance (μΩ/ft) | Zero Sequence Impedance Resistance (μΩ/ft) | | |
| 25KV 100% ALUMINUM THREE PHASE - ONE-THIRD NEUTRAL (CONTINUED) | | | | | | | | | | | | | | | | | | |
| 1/0 AWG AL | 260 | 6-#14 | 0.364 | 0.93 | 1.00 | 1.24 | 629 | 10 | 166 | 212 | 50 | 754 | 30 | 222 | 220 | 96 | 740 | 30 |
| 2/0 AWG AL | 260 | 7-#14 | 0.408 | 0.97 | 1.04 | 1.28 | 684 | 11 | 189 | 168 | 48 | 634 | 29 | 251 | 177 | 93 | 622 | 29 |
| 3/0 AWG AL | 260 | 9-#14 | 0.458 | 1.02 | 1.11 | 1.35 | 801 | 11 | 216 | 133 | 46 | 495 | 27 | 283 | 144 | 90 | 487 | 27 |
| 4/0 AWG AL | 260 | 11-#14 | 0.515 | 1.08 | 1.17 | 1.41 | 902 | 12 | 245 | 106 | 45 | 403 | 26 | 317 | 119 | 86 | 397 | 26 |
| 250 MCM AL | 260 | 13-#14 | 0.561 | 1.14 | 1.22 | 1.46 | 1004 | 12 | 269 | 90 | 43 | 341 | 25 | 343 | 104 | 83 | 337 | 25 |
| 350 MCM AL | 260 | 18-#14 | 0.664 | 1.24 | 1.33 | 1.56 | 1228 | 13 | 322 | 66 | 41 | 246 | 23 | 397 | 82 | 76 | 244 | 23 |
| 500 MCM AL | 260 | 16-#12 | 0.794 | 1.37 | 1.46 | 1.79 | 1652 | 15 | 389 | 48 | 40 | 173 | 21 | 451 | 67 | 68 | 172 | 21 |
| 750 MCM AL | 260 | 24-#12 | 0.974 | 1.56 | 1.67 | 2.01 | 2234 | 17 | 473 | 34 | 37 | 116 | 19 | 513 | 55 | 57 | 116 | 19 |
| 1000 MCM AL | 260 | 20-#10 | 1.124 | 1.71 | 1.82 | 2.20 | 2797 | 18 | 533 | 28 | 35 | 88 | 18 | 555 | 48 | 49 | 88 | 18 |
| 25KV 133% ALUMINUM SINGLE PHASE - FULL NEUTRAL | | | | | | | | | | | | | | | | | | |
| 1 SOLID AL | 320 | 13-#14 | 0.289 | 0.98 | 1.05 | 1.29 | 735 | 11 | 145 | 518 | 33 | 518 | 33 | 192 | 518 | 33 | 518 | 33 |
| 1 AWG AL | 320 | 13-#14 | 0.324 | 1.01 | 1.08 | 1.32 | 765 | 11 | 146 | 523 | 31 | 523 | 32 | 194 | 523 | 31 | 523 | 32 |
| 1/0 SOLID AL | 320 | 16-#14 | 0.325 | 1.02 | 1.08 | 1.32 | 813 | 11 | 165 | 415 | 31 | 415 | 31 | 218 | 415 | 31 | 415 | 31 |
| 1/0 AWG AL | 320 | 16-#14 | 0.364 | 1.05 | 1.14 | 1.38 | 869 | 12 | 166 | 420 | 30 | 420 | 30 | 219 | 420 | 30 | 420 | 30 |
| 2/0 AWG AL | 320 | 13-#12 | 0.408 | 1.10 | 1.19 | 1.46 | 1012 | 12 | 190 | 328 | 29 | 328 | 29 | 250 | 328 | 29 | 328 | 29 |
| 3/0 AWG AL | 320 | 16-#12 | 0.458 | 1.15 | 1.24 | 1.51 | 1137 | 13 | 217 | 263 | 28 | 263 | 28 | 282 | 263 | 28 | 263 | 28 |
| 4/0 AWG AL | 320 | 13-#10 | 0.515 | 1.21 | 1.29 | 1.61 | 1349 | 13 | 248 | 207 | 26 | 207 | 27 | 322 | 207 | 26 | 207 | 27 |
| 250 MCM AL | 320 | 16-#10 | 0.561 | 1.26 | 1.35 | 1.72 | 1597 | 14 | 276 | 171 | 25 | 171 | 25 | 356 | 171 | 25 | 171 | 25 |
| 350 MCM AL | 320 | 16-#9 | 0.664 | 1.36 | 1.45 | 1.95 | 1934 | 15 | 326 | 130 | 23 | 130 | 23 | 416 | 130 | 23 | 130 | 23 |
| 25KV 133% ALUMINUM THREE PHASE - ONE-THIRD NEUTRAL | | | | | | | | | | | | | | | | | | |
| 1 SOLID AL | 320 | 6-#14 | 0.289 | 0.98 | 1.05 | 1.29 | 653 | 11 | 146 | 261 | 53 | 801 | 33 | 196 | 269 | 101 | 786 | 33 |
| 1 AWG AL | 320 | 6-#14 | 0.324 | 1.01 | 1.08 | 1.32 | 683 | 11 | 146 | 266 | 52 | 807 | 32 | 196 | 274 | 99 | 792 | 32 |
| 1/0 SOLID AL | 320 | 6-#14 | 0.325 | 1.02 | 1.08 | 1.32 | 696 | 11 | 166 | 207 | 51 | 748 | 31 | 222 | 215 | 98 | 734 | 31 |
| 1/0 AWG AL | 320 | 6-#14 | 0.364 | 1.05 | 1.14 | 1.38 | 752 | 12 | 166 | 212 | 50 | 754 | 30 | 222 | 220 | 96 | 740 | 30 |
| 2/0 AWG AL | 320 | 7-#14 | 0.408 | 1.10 | 1.19 | 1.42 | 821 | 12 | 189 | 168 | 48 | 634 | 29 | 251 | 177 | 93 | 622 | 29 |
| 3/0 AWG AL | 320 | 9-#14 | 0.458 | 1.15 | 1.24 | 1.47 | 912 | 12 | 216 | 133 | 46 | 495 | 27 | 283 | 144 | 90 | 487 | 27 |
| 4/0 AWG AL | 320 | 11-#14 | 0.515 | 1.21 | 1.29 | 1.53 | 1018 | 13 | 245 | 106 | 45 | 403 | 26 | 317 | 119 | 86 | 397 | 26 |
| 250 MCM AL | 320 | 13-#14 | 0.561 | 1.26 | 1.35 | 1.59 | 1125 | 13 | 269 | 90 | 43 | 341 | 25 | 343 | 104 | 83 | 337 | 25 |
| 350 MCM AL | 320 | 18-#14 | 0.664 | 1.36 | 1.45 | 1.75 | 1422 | 14 | 322 | 66 | 41 | 246 | 23 | 397 | 82 | 76 | 244 | 23 |
| 500 MCM AL | 320 | 16-#12 | 0.794 | 1.49 | 1.58 | 1.91 | 1797 | 16 | 389 | 48 | 40 | 173 | 21 | 451 | 67 | 68 | 172 | 21 |
| 750 MCM AL | 320 | 24-#12 | 0.974 | 1.68 | 1.80 | 2.13 | 2398 | 18 | 473 | 34 | 37 | 116 | 19 | 513 | 55 | 57 | 116 | 19 |
| 1000 MCM AL | 320 | 20-#10 | 1.124 | 1.83 | 1.95 | 2.32 | 2975 | 19 | 533 | 28 | 35 | 88 | 18 | 555 | 48 | 49 | 88 | 18 |
| 35KV 100% ALUMINUM SINGLE PHASE - FULL NEUTRAL | | | | | | | | | | | | | | | | | | |
| 1/0 SOLID AL | 345 | 16-#14 | 0.325 | 1.07 | 1.15 | 1.39 | 877 | 12 | 168 | 415 | 35 | 415 | 35 | 217 | 415 | 35 | 415 | 35 |
| 1/0 AWG AL | 345 | 16-#14 | 0.364 | 1.10 | 1.19 | 1.43 | 914 | 12 | 169 | 420 | 34 | 420 | 34 | 218 | 420 | 34 | 420 | 34 |
| 2/0 AWG AL | 345 | 13-#12 | 0.408 | 1.15 | 1.24 | 1.51 | 1059 | 13 | 194 | 328 | 32 | 328 | 33 | 249 | 328 | 32 | 328 | 33 |
| 3/0 AWG AL | 345 | 16-#12 | 0.458 | 1.20 | 1.29 | 1.56 | 1186 | 13 | 220 | 263 | 31 | 263 | 31 | 283 | 263 | 31 | 263 | 31 |
| 4/0 AWG AL | 345 | 13-#10 | 0.515 | 1.26 | 1.34 | 1.72 | 1465 | 14 | 252 | 207 | 30 | 207 | 30 | 321 | 207 | 30 | 207 | 30 |
| 250 MCM AL | 345 | 16-#10 | 0.561 | 1.31 | 1.40 | 1.77 | 1653 | 15 | 280 | 171 | 28 | 171 | 28 | 353 | 171 | 28 | 171 | 28 |
| 350 MCM AL | 345 | 16-#9 | 0.664 | 1.41 | 1.50 | 1.90 | 1993 | 16 | 331 | 130 | 26 | 130 | 26 | 416 | 130 | 26 | 130 | 26 |

| Conductor | Insulation Thickness (mils) | Insulation Concentric Neutral | Conductor Diameter (in) | Insulation Diameter (in) | Insulation Shield Diameter (in) | Jacket Diameter (in) | Cable Weight (lbs/ft) | Minimum Bending Radius (in) | Amperacity (amps) | 90°C inDuct | | | 90°C Direct Buried | | | | | |
|---|-----------------------------|-------------------------------|-------------------------|--------------------------|---------------------------------|----------------------|-----------------------|-----------------------------|-------------------|---|--|--|---|--|--|----|-----|----|
| | | | | | | | | | | +/- Sequence Impedance Resistance ($\mu\Omega/\text{ft}$) | +/- Sequence Impedance Reactance ($\mu\Omega/\text{ft}$) | Zero Sequence Impedance Resistance ($\mu\Omega/\text{ft}$) | +/- Sequence Impedance Resistance ($\mu\Omega/\text{ft}$) | +/- Sequence Impedance Reactance ($\mu\Omega/\text{ft}$) | Zero Sequence Impedance Resistance ($\mu\Omega/\text{ft}$) | | | |
| 35KV 100% ALUMINUM THREE PHASE - ONE-THIRD NEUTRAL | | | | | | | | | | | | | | | | | | |
| 1/0 SOLID AL | 345 | 6-#14 | 0.325 | 1.07 | 1.15 | 1.39 | 760 | 12 | 168 | 207 | 54 | 745 | 35 | 219 | 214 | 98 | 729 | 35 |
| 1/0 AWG AL | 345 | 6-#14 | 0.364 | 1.10 | 1.19 | 1.43 | 797 | 12 | 168 | 212 | 53 | 751 | 34 | 219 | 219 | 96 | 736 | 34 |
| 2/0 AWG AL | 345 | 7-#14 | 0.408 | 1.15 | 1.24 | 1.47 | 867 | 12 | 191 | 168 | 51 | 631 | 32 | 248 | 176 | 93 | 618 | 32 |
| 3/0 AWG AL | 345 | 9-#14 | 0.458 | 1.20 | 1.29 | 1.52 | 960 | 13 | 218 | 133 | 49 | 493 | 31 | 280 | 143 | 90 | 485 | 31 |
| 4/0 AWG AL | 345 | 11-#14 | 0.515 | 1.26 | 1.34 | 1.58 | 1068 | 13 | 247 | 106 | 47 | 401 | 29 | 314 | 117 | 86 | 395 | 29 |
| 250 MCM AL | 345 | 13-#14 | 0.561 | 1.31 | 1.40 | 1.70 | 1239 | 14 | 271 | 90 | 47 | 340 | 28 | 339 | 103 | 83 | 335 | 28 |
| 350 MCM AL | 345 | 18-#14 | 0.664 | 1.41 | 1.50 | 1.80 | 1478 | 15 | 325 | 66 | 44 | 245 | 25 | 394 | 81 | 77 | 243 | 25 |
| 500 MCM AL | 345 | 16-#12 | 0.794 | 1.54 | 1.66 | 1.99 | 1904 | 16 | 392 | 48 | 42 | 173 | 24 | 452 | 65 | 69 | 171 | 24 |
| 750 MCM AL | 345 | 24-#12 | 0.974 | 1.73 | 1.85 | 2.18 | 2466 | 18 | 476 | 34 | 39 | 116 | 21 | 517 | 54 | 59 | 115 | 21 |
| 1000 MCM AL | 345 | 20-#10 | 1.124 | 1.88 | 2.00 | 2.37 | 3050 | 19 | 536 | 28 | 37 | 88 | 20 | 560 | 47 | 51 | 88 | 20 |
| 35KV 133% ALUMINUM SINGLE PHASE - FULL NEUTRAL | | | | | | | | | | | | | | | | | | |
| 1/0 SOLID AL | 420 | 16-#14 | 0.325 | 1.22 | 1.31 | 1.55 | 1021 | 13 | 168 | 415 | 35 | 415 | 35 | 217 | 415 | 35 | 415 | 35 |
| 1/0 AWG AL | 420 | 16-#14 | 0.364 | 1.26 | 1.35 | 1.58 | 1062 | 13 | 169 | 420 | 34 | 420 | 34 | 218 | 420 | 34 | 420 | 34 |
| 2/0 AWG AL | 420 | 13-#12 | 0.408 | 1.30 | 1.39 | 1.72 | 1279 | 14 | 194 | 328 | 32 | 328 | 33 | 249 | 328 | 32 | 328 | 33 |
| 3/0 AWG AL | 420 | 16-#12 | 0.458 | 1.35 | 1.44 | 1.77 | 1412 | 15 | 220 | 263 | 31 | 263 | 31 | 283 | 263 | 31 | 263 | 31 |
| 4/0 AWG AL | 420 | 13-#10 | 0.515 | 1.41 | 1.50 | 1.87 | 1641 | 15 | 252 | 207 | 30 | 207 | 30 | 321 | 207 | 30 | 207 | 30 |
| 250 MCM AL | 420 | 16-#10 | 0.561 | 1.46 | 1.55 | 1.93 | 1834 | 16 | 280 | 171 | 28 | 171 | 28 | 353 | 171 | 28 | 171 | 28 |
| 350 MCM AL | 420 | 16-#9 | 0.664 | 1.57 | 1.68 | 2.08 | 2234 | 17 | 331 | 130 | 26 | 130 | 26 | 416 | 130 | 26 | 130 | 26 |
| 35KV 133% ALUMINUM THREE PHASE - ONE THIRD NEUTRAL | | | | | | | | | | | | | | | | | | |
| 1/0 SOLID AL | 420 | 6-#14 | 0.325 | 1.22 | 1.31 | 1.55 | 904 | 13 | 168 | 207 | 54 | 745 | 35 | 219 | 214 | 98 | 729 | 35 |
| 1/0 AWG AL | 420 | 6-#14 | 0.364 | 1.26 | 1.35 | 1.58 | 945 | 13 | 168 | 212 | 53 | 751 | 34 | 219 | 219 | 96 | 736 | 34 |
| 2/0 AWG AL | 420 | 7-#14 | 0.408 | 1.30 | 1.39 | 1.63 | 1019 | 14 | 191 | 168 | 51 | 631 | 32 | 248 | 176 | 93 | 618 | 32 |
| 3/0 AWG AL | 420 | 9-#14 | 0.458 | 1.35 | 1.44 | 1.74 | 1182 | 14 | 218 | 133 | 49 | 493 | 31 | 280 | 143 | 90 | 485 | 31 |
| 4/0 AWG AL | 420 | 11-#14 | 0.515 | 1.41 | 1.50 | 1.80 | 1297 | 15 | 247 | 106 | 47 | 401 | 29 | 314 | 117 | 86 | 395 | 29 |
| 250 MCM AL | 420 | 13-#14 | 0.561 | 1.46 | 1.55 | 1.85 | 1412 | 15 | 271 | 90 | 47 | 340 | 28 | 339 | 103 | 83 | 335 | 28 |
| 350 MCM AL | 420 | 18-#14 | 0.664 | 1.57 | 1.68 | 1.98 | 1706 | 16 | 325 | 66 | 44 | 245 | 25 | 394 | 81 | 77 | 243 | 25 |
| 500 MCM AL | 420 | 16-#12 | 0.794 | 1.70 | 1.81 | 2.15 | 2107 | 18 | 392 | 48 | 42 | 173 | 24 | 452 | 65 | 69 | 171 | 24 |
| 750 MCM AL | 420 | 24-#12 | 0.974 | 1.88 | 2.00 | 2.33 | 2687 | 19 | 476 | 34 | 39 | 116 | 21 | 517 | 54 | 59 | 115 | 21 |
| 1000 MCM AL | 420 | 20-#10 | 1.124 | 2.03 | 2.15 | 2.53 | 3290 | 21 | 536 | 28 | 37 | 88 | 20 | 560 | 47 | 51 | 88 | 20 |

All values are nominal and subject to correction

Single Phase Operation (Full Neutral Design)

In Duct: One single cable in plastic duct, direct-buried, 90°C conductor temperature, 20°C ambient temperature, earth RHO of 90°C-cm/Watt, 100% load factor, 36 inch depth of burial, and shields short-circuited.

Direct Buried: One single cable, direct-buried, 90°C conductor temperature, 20°C ambient temperature, earth RHO of 90°C-cm/Watt, 100% load factor, 36 inch depth of burial, and shields short-circuited.

Three Phase Operation (1/3 Neutral Design)

In Duct: Three single cables in plastic duct, direct-buried in a triangular configuration, 90°C conductor temperature, 20°C ambient temperature, earth RHO of 90°C-cm/Watt, 100% load factor, 36 inch depth of burial, and shields short-circuited.

Direct Buried: Three single cables, direct-buried, spaced 7.5 inches horizontally, 90°C conductor temperature, 20°C ambient temperature, earth RHO of 90°C-cm/Watt, 100% load factor, 36 inch depth of burial, and shields short-circuited.



Single Conductor 600 Volt URD Secondary Type UD Cable - Aluminum Conductor

APPLICATION: Directly buried or installed in ducts for 600 volt or less secondary distribution.

CONSTRUCTION: Concentric stranded or compressed 1350 series aluminum conductor, cross-linked polyethylene insulation.

SPECIFICATIONS: ASTM B-230, B-231, B-609, ICEA S-105-692, Federal Specification A-A-595544, UL 854.

OPTIONS: Cable in Duct (CIC) • Ruggedized • Ridged Phase ID

RUS ACCEPTED

| Code Word | Conductor Size | Insulation Thickness | Diameter | Weight | Ampacity** | |
|-----------|----------------|----------------------|----------|---------|---------------|---------|
| | | | | | Direct Burial | In Duct |
| | AWG/kcmil | inches | inches | lbs/kft | amps | amps |
| Princeton | 6* | 0.060 | 0.31 | 44 | 90 | 65 |
| Mercer | 4* | 0.060 | 0.36 | 63 | 120 | 85 |
| Clemson | 2 | 0.060 | 0.42 | 92 | 155 | 115 |
| Kenyon | 1 | 0.080 | 0.50 | 121 | 175 | 130 |
| Harvard | 1/0 | 0.080 | 0.54 | 146 | 200 | 150 |
| Yale | 2/0 | 0.080 | 0.59 | 177 | 225 | 170 |
| Tufts | 3/0 | 0.080 | 0.64 | 215 | 250 | 195 |
| Beloit | 4/0 | 0.080 | 0.70 | 263 | 290 | 225 |
| Hofstra | 250 | 0.095 | 0.77 | 314 | 320 | 250 |
| Gonzaga | 300 | 0.095 | 0.83 | 367 | 355 | 280 |
| Rutgers | 350 | 0.095 | 0.88 | 420 | 385 | 305 |
| Dartmouth | 400 | 0.095 | 0.92 | 476 | 415 | 330 |
| Emory | 500 | 0.095 | 1.01 | 577 | 465 | 370 |
| Duke | 600 | 0.110 | 1.12 | 697 | 510 | 410 |
| Furman | 700 | 0.110 | 1.20 | 804 | 550 | 440 |
| Sewanee | 750 | 0.110 | 1.23 | 853 | 580 | 470 |
| Fordham | 1000 | 0.110 | 1.38 | 1108 | 670 | 545 |

All values are nominal and subject to correction

*Not RUS accepted size

**Ratings for 3/C, 90°C conductor temperature, 20°C ambient earth temperature, RHO 90, 100% load factor. For NEC installations reference NEC article 310.15.

Duplex Conductor 600 Volt URD Secondary Type UD Cable - Aluminum Conductor

APPLICATION: Directly buried or installed in ducts for 600 volt or less secondary distribution.

CONSTRUCTION: Concentric stranded or compressed 1350 series aluminum conductor, cross linked polyethylene (XLP) insulation. Insulated conductors surface printed, neutral, yellow striped. One phase and one neutral conductor twisted together.

SPECIFICATIONS: ASTM B-230, B-231, B-609, B-901 and ICEA S-105-692. Federal specification A-A-595544A NEC. UL 854.

OPTIONS: Cable in Duct (CIC) • Ruggedized • Ridged Phase ID

| Code Word | Phase Conductor | | | Neutral | | | Diameter | | Weight | Ampacity** | |
|-----------|-----------------|----------------|----------------------|---------|----------------|----------------------|------------------------|----------------|---------|---------------|---------|
| | Size | No. of Strands | Insulation Thickness | Size | No. of Strands | Insulation Thickness | Single Phase Conductor | Complete Cable | | Direct Burial | In Duct |
| | AWG | | inches | AWG | | inches | inches | inches | lbs/kft | amps | amps |
| Bard | 8* | 7 | 0.060 | 8 | 7 | 0.060 | 0.26 | 0.52 | 69 | 70 | 55 |
| Clafin | 6* | 7 | 0.060 | 6 | 7 | 0.060 | 0.30 | 0.60 | 95 | 95 | 70 |
| Delgado | 4* | 7 | 0.060 | 4 | 7 | 0.060 | 0.35 | 0.69 | 135 | 125 | 90 |
| Everett | 2 | 7 | 0.060 | 2 | 7 | 0.060 | 0.40 | 0.80 | 189 | 165 | 120 |

All values are nominal and subject to correction

*Not RUS accepted size, **Ampacity 90°C conductor temperatures, 20°C ambient earth temperature. RHO 90. 100% load factor.

For NEC installations reference NEC article 310.15.

1-800-945-5542

www.PriorityWire.com



Triplex Conductor 600 Volt URD Secondary Type UD Cable - Aluminum Conductor

APPLICATION: Directly buried or installed in ducts for 600 volt or less secondary distribution.

CONSTRUCTION: Compact bare AA-8000 series aluminum alloy conductors, Class B stranded per ASTM, cross-linked polyethylene (XLP) insulation. Insulated conductors surface printed, neutral, yellow striped. Two phase and one neutral conductor twisted together.

SPECIFICATIONS: ASTM B-230, B-231, B-609, B-901, ICEA S-105-692, Federal Specification A-A-595544. UL 854.

OPTIONS: Cable in Duct (CIC) • Ruggedized • Ridged Phase ID

RUS ACCEPTED

| Code Word | Phase Conductor | | | Neutral | | | Diameter | | Weight lbs/kft | Ampacity** | |
|------------|-----------------|----------------|--------------------------------|-----------|----------------|--------------------------------|------------------------|----------------|-------------------|-----------------------|-----------------|
| | Size | No. of Strands | Insulation Thickness inches | Size | No. of Strands | Insulation Thickness inches | Single Phase Conductor | Complete Cable | | Direct Burial amps | In Duct amps |
| | AWG/kcmil | | | AWG/kcmil | | | inches | inches | | | |
| Erskine | 6* | 7 | 0.060 | 6 | 7 | 0.060 | 0.30 | 0.64 | 143 | 95 | 70 |
| Vassar | 4* | 7 | 0.060 | 4 | 7 | 0.060 | 0.35 | 0.75 | 202 | 125 | 90 |
| Stephens | 2 | 7 | 0.060 | 4 | 7 | 0.060 | 0.40 | 0.87 | 262 | 165 | 120 |
| Ramapo | 2 | 7 | 0.060 | 2 | 7 | 0.060 | 0.40 | 0.87 | 292 | 165 | 120 |
| Brenau | 1/0 | 19 | 0.080 | 2 | 7 | 0.060 | 0.51 | 1.11 | 406 | 215 | 160 |
| Bergen | 1/0 | 19 | 0.080 | 1/0 | 19 | 0.080 | 0.51 | 1.11 | 463 | 215 | 160 |
| Converse | 2/0 | 19 | 0.080 | 1 | 19 | 0.080 | 0.56 | 1.20 | 501 | 245 | 180 |
| Hunter | 2/0 | 19 | 0.080 | 2/0 | 19 | 0.080 | 0.56 | 1.20 | 559 | 245 | 180 |
| Hollins | 3/0 | 19 | 0.080 | 1/0 | 19 | 0.080 | 0.60 | 1.30 | 606 | 280 | 205 |
| Rockland | 3/0 | 19 | 0.080 | 3/0 | 19 | 0.080 | 0.60 | 1.30 | 677 | 280 | 205 |
| Sweetbriar | 4/0 | 19 | 0.080 | 2/0 | 19 | 0.080 | 0.66 | 1.42 | 737 | 315 | 240 |
| Monmouth | 4/0 | 19 | 0.080 | 4/0 | 19 | 0.080 | 0.66 | 1.42 | 826 | 315 | 240 |
| Pratt | 250 | 37 | 0.095 | 3/0 | 19 | 0.080 | 0.75 | 1.62 | 888 | 345 | 265 |
| Wesleyan | 350 | 37 | 0.095 | 4/0 | 19 | 0.080 | 0.85 | 1.84 | 1,157 | 415 | 320 |
| Holyoke | 500 | 37 | 0.095 | 300 | 37 | 0.095 | 0.98 | 2.12 | 1,591 | 495 | 395 |
| Rider | 500 | 37 | 0.095 | 350 | 37 | 0.095 | 0.98 | 2.12 | 1,646 | 495 | 395 |
| Fairfield | 750 | 61 | 0.110 | 500 | 37 | 0.095 | 1.19 | 2.40 | 2,289 | 620 | 495 |

All values are nominal and subject to correction

*Not RUS accepted size

*Ampacity: 90°C conductor temperature, 20°C ambient earth temperature, RHO 90, 100% load factor. Neutral carries unbalanced load only.

For NEC installations reference NEC article 310.15.

1-800-945-5542

www.PriorityWire.com



Quadruplex Conductor 600 Volt URD Secondary Type UD Cable - Aluminum Conductor

APPLICATION: Direct buried or installed in ducts for 600 volts or less secondary distribution.

CONSTRUCTION: Concentric stranded or compressed 1350 series aluminum conductors, cross-linked polyethylene (XLP) insulation. Insulated conductors surface printed, neutral, yellow striped. Three phase and one neutral conductor twisted together.

SPECIFICATIONS: ASTM B-230, B-231, B-609, B-901, ICEA S-105-692, Federal Specification A-A-59544 and NEC. UL 854.

OPTIONS: Cable in Duct (CIC) • Ruggedized • Ridged Phase ID

RUS ACCEPTED

| Code Word | Phase Conductor | | | Neutral | | | Diameter | | Weight lbs/kft | Ampacity** | |
|---------------|-----------------|----------------|--------------------------------|-----------|----------------|--------------------------------|------------------------|----------------|-------------------|-----------------------|-----------------|
| | Size | No. of Strands | Insulation Thickness inches | Size | No. of Strands | Insulation Thickness inches | Single Phase Conductor | Complete Cable | | Direct Burial amps | In Duct amps |
| | AWG/kcmil | | | AWG/kcmil | | | inches | inches | | | |
| Tulsa | 4* | 7 | 0.060 | 4 | 7 | 0.060 | 0.35 | 0.83 | 269 | 120 | 85 |
| Dyke | 2 | 7 | 0.060 | 4 | 7 | 0.060 | 0.40 | 0.97 | 359 | 155 | 115 |
| Wittenberg | 2 | 7 | 0.060 | 2 | 7 | 0.060 | 0.40 | 0.97 | 389 | 155 | 115 |
| Notre Dame | 1/0 | 19 | 0.080 | 2 | 7 | 0.060 | 0.51 | 1.24 | 560 | 200 | 150 |
| Purdue | 1/0 | 19 | 0.080 | 1/0 | 19 | 0.080 | 0.51 | 1.24 | 617 | 200 | 150 |
| Syracuse | 2/0 | 19 | 0.080 | 1 | 19 | 0.080 | 0.56 | 1.34 | 687 | 225 | 170 |
| Lafayette | 2/0 | 19 | 0.080 | 2/0 | 19 | 0.080 | 0.56 | 1.34 | 745 | 225 | 170 |
| Swarthmore | 3/0 | 19 | 0.080 | 1/0 | 19 | 0.080 | 0.60 | 1.46 | 832 | 250 | 195 |
| Davidson | 3/0 | 19 | 0.080 | 3/0 | 19 | 0.080 | 0.60 | 1.46 | 903 | 250 | 195 |
| Wake Forest | 4/0 | 19 | 0.080 | 2/0 | 19 | 0.080 | 0.66 | 1.59 | 1,012 | 290 | 225 |
| Earlham | 4/0 | 19 | 0.080 | 4/0 | 19 | 0.080 | 0.66 | 1.59 | 1,101 | 290 | 225 |
| Rust | 250 | 37 | 0.095 | 3/0 | 19 | 0.080 | 0.75 | 1.81 | 1,215 | 320 | 250 |
| Slippery Rock | 350 | 37 | 0.095 | 4/0 | 19 | 0.080 | 0.85 | 2.05 | 1,598 | 385 | 305 |
| Niagara | 350 | 37 | 0.095 | 350 | 37 | 0.095 | 0.85 | 2.08 | 1,695 | 385 | 305 |
| Wofford | 500 | 37 | 0.095 | 350 | 37 | 0.095 | 0.98 | 2.35 | 2,174 | 465 | 370 |
| Windham | 750 | 61 | 0.110 | 500 | 37 | 0.095 | 1.19 | 2.78 | 3,305 | 580 | 460 |

All values are nominal and subject to correction

*Not RUS accepted size

**Ampacity: 90°C conductor temperature, 20°C ambient earth temperature, RHO 90, 100% load factor for three current carrying conductors with neutral carrying only unbalanced load.

For NEC installations reference NEC article 310.15.

1-800-945-5542

www.PriorityWire.com



Triplex Conductor 600 Volt 8000 Series URD Secondary Type UD Cable RHH or RHW-2 or USE-2 600V-Aluminum Conductor

APPLICATION: Secondary distribution and underground service at 600 volts or less and in temperatures not to exceed 90°C in wet and dry locations, either direct burial or in ducts, where increased flexibility is needed.

CONSTRUCTION: Compressed stranded AA-8000 series Aluminum Alloy or concentric stranded conductors insulated with cross-linked polyethylene (XLP). A triplex construction consists of two-phase conductors and one neutral. The neutral conductor contains yellow extruded stripes and sequential footage marks. Conductors are surface printed for identification.

SPECIFICATIONS: Triplex Type RHH or RHW-2 or USE-2 600 volt cable meets or exceeds the following applicable standards/specifications: ASTM B800 8000 Series Aluminum Alloy Wire for Electrical Purposes • ASTM B801 Compressed Conductors of 8000 Series Aluminum Alloy for Subsequent Covering or Insulations • ASTM B901 Compressed Round Stranded Aluminum Conductors Using Single Input Wire Construction • ICEA S-105-682 for cross-linked polyethylene insulated conductors, UL 44 for type RHW-2, and UL 854 for Type USE-2.

OPTIONS: Cable in Duct (CIC) • Ruggedized • Ridged Phase ID

| Code Word | Phase Conductor | | | Neutral | | | Diameter | | Weight | Ampacity* | |
|---------------|-----------------|----------------|----------------------|---------|----------------|----------------------|------------------------|----------------|---------|---------------|---------|
| | Size | No. of Strands | Insulation Thickness | Size | No. of Strands | Insulation Thickness | Single Phase Conductor | Complete Cable | | Direct Burial | In Duct |
| | AWG/kcmil | | inches | AWG | | inches | inches | inches | lbs/kft | amps | amps |
| Vassar/8k | 4 | 7 | 0.060 | 4 | 7 | 0.060 | 0.35 | 0.75 | 202 | 125 | 85 |
| Stephens/8k | 2 | 7 | 0.060 | 4 | 7 | 0.060 | 0.40 | 0.87 | 262 | 165 | 120 |
| Ramapo/8k | 2 | 7 | 0.060 | 2 | 7 | 0.060 | 0.40 | 0.87 | 292 | 165 | 120 |
| Brenau/8k | 1/0 | 19 | 0.080 | 2 | 7 | 0.060 | 0.51 | 1.11 | 406 | 215 | 160 |
| Converse/8k | 2/0 | 19 | 0.080 | 1 | 19 | 0.080 | 0.56 | 1.20 | 501 | 245 | 180 |
| Sweetbriar/8k | 4/0 | 19 | 0.080 | 2/0 | 19 | 0.080 | 0.66 | 1.42 | 737 | 315 | 240 |
| Monmouth/8k | 4/0 | 19 | 0.080 | 4/0 | 19 | 0.080 | 0.66 | 1.42 | 826 | 315 | 240 |
| Pratt/8k | 250 | 37 | 0.095 | 3/0 | 19 | 0.080 | 0.75 | 1.62 | 888 | 345 | 265 |
| Wesleyan/8k | 350 | 37 | 0.095 | 4/0 | 19 | 0.080 | 0.85 | 1.84 | 1,157 | 415 | 320 |

All values are nominal and subject to correction

*Ampacity: 90°C conductor temperature, 20°C ambient earth temperature, RHO 90, 100% load factor. Neutral carries unbalanced load only.

For NEC installations reference NEC article 310.15.

1-800-945-5542

www.PriorityWire.com



General Purpose Control Cable Unshielded

APPLICATION: General Purpose Control Cable which is used in industrial and utility applications, for distribution or control circuits and for the interconnection of operation of protective devices. It can be installed in open air, in ducts or conduit, in trays or troughs, and direct burial for circuits up to 600 volts and temperatures up to 75°C.

CONSTRUCTION: Stranded annealed bare copper conductor, per ASTM B3 & B8. Heat and moisture resistant E-1 colored combination insulation of polyethylene (PE) and polyvinyl chloride (PVC). Black polyvinyl chloride (PVC) jacket, which is heat, moisture and sunlight resistant.

SPECIFICATIONS: • Rated 600 Volts at 75°C. • ICEA S-73-532/NEMA WC57 • ASTM B3, B8 • Sunlight resistant • Direct Burial • RoHS compliant • REACH compliant

| Conductor Size | No. of Conductors | Insulation Thickness | Overall Jacket Thickness | Overall Diameter | Approx. Weight |
|--------------------------------|-------------------|----------------------|--------------------------|------------------|----------------|
| AWG | | PE/PVC inches | inches | inches | lbs/kft |
| 15/10 PE/PVC - 7 Strand | | | | | |
| 18 | 3 | 0.015 / 0.010 | 0.045 | 0.294 | 47 |
| 18 | 4 | 0.015 / 0.010 | 0.045 | 0.319 | 58 |
| 18 | 7 | 0.015 / 0.010 | 0.045 | 0.378 | 89 |
| 18 | 12 | 0.015 / 0.010 | 0.045 | 0.490 | 142 |
| 20/10 PE/PVC - 7 Strand | | | | | |
| 14 | 4 | 0.020 / 0.010 | 0.045 | 0.411 | 106 |
| 14 | 7 | 0.020 / 0.010 | 0.045 | 0.492 | 170 |
| 14 | 12 | 0.020 / 0.010 | 0.060 | 0.678 | 299 |
| 12 | 2 | 0.020 / 0.010 | 0.045 | 0.393 | 93 |
| 12 | 3 | 0.020 / 0.010 | 0.045 | 0.415 | 121 |
| 12 | 4 | 0.020 / 0.010 | 0.045 | 0.454 | 147 |
| 12 | 7 | 0.020 / 0.010 | 0.060 | 0.591 | 256 |
| 12 | 8 | 0.020 / 0.010 | 0.060 | 0.622 | 291 |
| 12 | 9 | 0.020 / 0.010 | 0.060 | 0.690 | 330 |
| 12 | 12 | 0.020 / 0.010 | 0.060 | 0.749 | 413 |
| 10 | 2 | 0.020 / 0.010 | 0.045 | 0.439 | 128 |
| 10 | 3 | 0.020 / 0.010 | 0.045 | 0.465 | 128 |
| 10 | 4 | 0.020 / 0.010 | 0.045 | 0.513 | 214 |
| 10 | 5 | 0.020 / 0.010 | 0.060 | 0.609 | 286 |
| 10 | 7 | 0.020 / 0.010 | 0.060 | 0.642 | 356 |
| 10 | 8 | 0.020 / 0.010 | 0.060 | 0.696 | 409 |
| 10 | 9 | 0.020 / 0.010 | 0.060 | 0.749 | 451 |
| 10 | 12 | 0.020 / 0.010 | 0.080 | 0.884 | 629 |
| 30/15 PE/PVC - 7 Strand | | | | | |
| 18 | 2 | 0.030 / 0.015 | 0.045 | 0.390 | 62 |
| 14 | 6 | 0.030 / 0.015 | 0.060 | 0.635 | 220 |
| 12 | 2 | 0.030 / 0.015 | 0.045 | 0.470 | 102 |
| 12 | 4 | 0.030 / 0.015 | 0.060 | 0.580 | 188 |
| 10 | 4 | 0.030 / 0.015 | 0.060 | 0.640 | 250 |
| 10 | 8 | 0.030 / 0.015 | 0.080 | 0.900 | 490 |
| 6 | 4 | 0.030 / 0.015 | 0.060 | 0.800 | 495 |

| Conductor Size | No. of Conductors | Insulation Thickness | Overall Jacket Thickness | Overall Diameter | Approx. Weight |
|--------------------------------|-------------------|----------------------|--------------------------|------------------|----------------|
| AWG | | PE/PVC inches | inches | inches | lbs/kft |
| 45/15 PE/PVC - 7 Strand | | | | | |
| 8 | 2 | 0.045 / 0.015 | 0.060 | 0.645 | 238 |
| 8 | 3 | 0.045 / 0.015 | 0.060 | 0.684 | 309 |
| 8 | 12 | 0.045 / 0.015 | 0.080 | 1.249 | 1066 |
| 45/25 PE/PVC - 7 Strand | | | | | |
| 6 | 2 | 0.045 / 0.025 | 0.060 | 0.774 | 351 |
| 6 | 3 | 0.045 / 0.025 | 0.080 | 0.863 | 500 |
| 4 | 3 | 0.045 / 0.025 | 0.080 | 0.966 | 673 |
| 45/30 PE/PVC - 7 Strand | | | | | |
| 4 | 1 | 0.045 / 0.030 | --- | 0.382 | 171 |
| 2 | 1 | 0.045 / 0.030 | --- | 0.435 | 254 |

*All values are nominal and subject to correction
Color Coding per ICEA S-73-532, Method 1, Table E-1*

1-800-945-5542

www.PriorityWire.com



General Purpose Control Cable Shielded

APPLICATION: General Purpose Control Cable which is used in industrial and utility applications, for distribution or control circuits and for the interconnection of operation of protective devices. It can be installed in open air, in ducts or conduit, in trays or troughs, and direct burial for circuits up to 600 volts and temperatures up to 75°C.

CONSTRUCTION: Stranded annealed bare copper conductor, per ASTM B3 & B8. Heat and moisture resistant E-1 colored combination insulation of polyethylene (PE) and polyvinyl chloride (PVC). Black polyvinyl chloride (PVC) jacket, which is heat, moisture and sunlight resistant. 0.005" Helical bare copper tape with 20% nominal overlap shield.

SPECIFICATIONS: • Rated 600 Volts at 75°C. • ICEA S-73-532/NEMA WC57 • ASTM B3, B8 • Sunlight resistant • Direct Burial • RoHS compliant • REACH compliant

| Conductor Size | No. of Conductors | Insulation Thickness | Overall Jacket Thickness | Overall Diameter | Approx. Weight |
|--------------------------------|-------------------|----------------------|--------------------------|------------------|----------------|
| AWG | | PE/PVC inches | inches | inches | lbs/kft |
| 15/10 PE/PVC - 7 Strand | | | | | |
| 18 | 3 | 0.015 / 0.010 | 0.045 | 0.307 | 76 |
| 18 | 4 | 0.015 / 0.010 | 0.045 | 0.332 | 89 |
| 18 | 7 | 0.015 / 0.010 | 0.045 | 0.388 | 116 |
| 18 | 12 | 0.015 / 0.010 | 0.045 | 0.497 | 177 |
| 20/10 PE/PVC - 7 Strand | | | | | |
| 14 | 7 | 0.020 / 0.010 | 0.045 | 0.499 | 206 |
| 12 | 2 | 0.020 / 0.010 | 0.045 | 0.403 | 128 |
| 10 | 2 | 0.020 / 0.010 | 0.045 | 0.449 | 154 |
| 10 | 3 | 0.020 / 0.010 | 0.045 | 0.475 | 202 |
| 10 | 4 | 0.020 / 0.010 | 0.060 | 0.550 | 267 |
| 10 | 5 | 0.020 / 0.010 | 0.060 | 0.969 | 719 |
| 10 | 8 | 0.020 / 0.010 | 0.060 | 0.706 | 458 |
| 10 | 9 | 0.020 / 0.010 | 0.060 | 0.759 | 505 |
| 10 | 12 | 0.020 / 0.010 | 0.080 | 0.891 | 688 |
| 30/15 PE/PVC - 7 Strand | | | | | |
| 18 | 2 | 0.030 / 0.015 | 0.045 | 0.400 | 87 |
| 14 | 6 | 0.030 / 0.015 | 0.060 | 0.650 | 259 |
| 12 | 2 | 0.030 / 0.015 | 0.045 | 0.478 | 142 |
| 10 | 2 | 0.030 / 0.015 | 0.060 | 0.570 | 201 |
| 10 | 4 | 0.030 / 0.015 | 0.060 | 0.650 | 307 |
| 10 | 8 | 0.030 / 0.015 | 0.080 | 0.910 | 581 |
| 6 | 4 | 0.030 / 0.015 | 0.060 | 0.820 | 571 |

| Conductor Size | No. of Conductors | Insulation Thickness | Overall Jacket Thickness | Overall Diameter | Approx. Weight |
|--------------------------------|-------------------|----------------------|--------------------------|------------------|----------------|
| AWG | | PE/PVC inches | inches | inches | lbs/kft |
| 45/15 PE/PVC - 7 Strand | | | | | |
| 8 | 2 | 0.045 / 0.015 | 0.060 | 0.655 | 272 |
| 8 | 3 | 0.045 / 0.015 | 0.060 | 0.694 | 357 |
| 8 | 5 | 0.045 / 0.015 | 0.080 | 0.878 | 570 |
| 45/25 PE/PVC - 7 Strand | | | | | |
| 6 | 2 | 0.045 / 0.025 | 0.060 | 0.778 | 411 |
| 6 | 3 | 0.045 / 0.025 | 0.080 | 0.870 | 563 |
| 6 | 9 | 0.045 / 0.025 | 0.080 | 1.346 | 1374 |
| 4 | 3 | 0.045 / 0.025 | 0.080 | 0.976 | 738 |
| 45/30 PE/PVC - 7 Strand | | | | | |
| 4 | 1 | 0.045 / 0.030 | 0.045 | 0.487 | 291 |
| 2 | 1 | 0.045 / 0.030 | 0.045 | 0.535 | 382 |

*All values are nominal and subject to correction
Color Coding per ICEA S-73-532, Method 1, Table E-1*

1-800-945-5542

www.PriorityWire.com



Tinned Copper XLP/CPE Multi Conductor Control Cable 600V (Industrial Tray Cable)

APPLICATION/INSTALLATION: For use as a 600 volt, multi conductor control cable where flame-retardance, and moisture/chemical resistance is critical. Cable can be installed in cable trays, supported by messenger in open air, raceways, channels, conduits and ducts. The cable is also UL approved for wet or dry locations as well as Class 1 Division II industrial hazardous locations per NEC.

CONDUCTOR: Fully annealed tinned copper Class B compressed strand per ASTM B33 and ASTM B8.

INSULATION: Flame retardant Cross-linked Polyethylene (FR-XLPE).

ASSEMBLY: Conductors are cabled together with or without fillers as required to form a round, compact cable core with a binder tape.

COLOR CODE: ICEA S-58-679 Method 1, Table E-2

JACKET: Flame and sunlight resistant black thermoplastic Cross-linked Chlorinated Polyethylene (XL-CPE).

OPTIONS: Class K standing per ASTM B174. Class H standing per ASTM B173. Bare copper conductors. Copper tape sheilded. ICEA Method 1, Table E-1 color code.

FEATURES AND BENEFITS: Temperature rating of 90°C (wet or dry). Insulation provides excellent electrical, thermal, and physical properties, excellent flame resistance that allows the jacket to burn to an ash and does not exhibit the thermoplastic drip characteristic, resistance to crush, compression, cuts and heat deformation. Also conductor insulation provides good low temperature (-25°C) cold bend characteristics

| Conductor Size AWG | No. of Conductors | No. of Strands | Insulation Thickness | | Jacket Thickness | | Overall Diameter | Weight |
|-----------------------|-------------------|----------------|----------------------|------|------------------|------|------------------|---------|
| | | | inches | mm | inches | mm | inches | lbs/kft |
| 14 | 2 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.36 | 71 |
| 14 | 3 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.38 | 93 |
| 14 | 4 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.41 | 116 |
| 14 | 5 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.45 | 140 |
| 14 | 7 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.49 | 187 |
| 14 | 9 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.60 | 255 |
| 14 | 12 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.68 | 328 |
| 14 | 19 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 0.79 | 487 |
| 14 | 25 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 0.93 | 663 |
| 14 | 30 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.00 | 780 |
| 14 | 37 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.10 | 940 |
| 12 | 2 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.39 | 100 |
| 12 | 3 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.42 | 130 |
| 12 | 4 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.45 | 163 |
| 12 | 5 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.50 | 194 |
| 12 | 7 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.58 | 274 |
| 12 | 9 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.67 | 359 |
| 12 | 12 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.75 | 445 |
| 12 | 15 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 0.87 | 603 |
| 12 | 19 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 0.92 | 709 |
| 12 | 25 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.03 | 907 |
| 12 | 30 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.13 | 1074 |
| 12 | 37 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.24 | 1288 |

All values are nominal and subject to correction

(Continued on page 33)

1-800-945-5542

www.PriorityWire.com



Tinned Copper XLP/CPE Multi Conductor Control Cable 600V (Industrial Tray Cable)

| Conductor Size AWG | No. of Conductors | No. of Strands | Insulation Thickness | | Jacket Thickness | | Overall Diameter inches | Weight lbs/ft |
|-----------------------|-------------------|----------------|----------------------|------|------------------|------|----------------------------|------------------|
| | | | inches | mm | inches | mm | | |
| 10 | 2 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.44 | 133 |
| 10 | 3 | 7 | 0.030 | 0.76 | 0.045 | 1.14 | 0.47 | 185 |
| 10 | 4 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.55 | 252 |
| 10 | 5 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.60 | 299 |
| 10 | 7 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.65 | 395 |
| 10 | 9 | 7 | 0.030 | 0.76 | 0.060 | 1.52 | 0.76 | 510 |
| 10 | 12 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 0.89 | 687 |
| 10 | 15 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 0.96 | 735 |
| 10 | 19 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.04 | 1032 |
| 10 | 25 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.19 | 1170 |
| 10 | 37 | 7 | 0.030 | 0.76 | 0.080 | 2.03 | 1.41 | 1680 |
| 12 | 2 | 12 | 0.030 | 0.76 | 0.045 | 1.14 | 0.41 | 105 |
| 12 | 3 | 12 | 0.030 | 0.76 | 0.045 | 1.14 | 0.43 | 140 |
| 12 | 4 | 12 | 0.030 | 0.76 | 0.045 | 1.14 | 0.47 | 170 |
| 10 | 2 | 10 | 0.030 | 0.76 | 0.045 | 1.14 | 0.47 | 183 |
| 10 | 3 | 10 | 0.030 | 0.76 | 0.060 | 1.52 | 0.54 | 246 |
| 10 | 4 | 10 | 0.030 | 0.76 | 0.060 | 1.52 | 0.60 | 302 |
| 8 | 2 | 10 | 0.045 | 1.14 | 0.060 | 1.52 | 0.65 | 362 |
| 8 | 3 | 10 | 0.045 | 1.14 | 0.060 | 1.52 | 0.66 | 373 |
| 8 | 4 | 10 | 0.045 | 1.14 | 0.060 | 1.52 | 0.74 | 415 |
| 6 | 2 | 8 | 0.045 | 1.14 | 0.060 | 1.52 | 0.69 | 393 |
| 6 | 3 | 8 | 0.045 | 1.14 | 0.060 | 1.52 | 0.76 | 531 |
| 6 | 4 | 8 | 0.045 | 1.14 | 0.060 | 1.52 | 0.84 | 650 |
| 4 | 2 | 8 | 0.045 | 1.14 | 0.060 | 1.52 | 0.77 | 537 |
| 4 | 3 | 8 | 0.045 | 1.14 | 0.080 | 2.03 | 0.93 | 778 |
| 4 | 4 | 8 | 0.045 | 1.14 | 0.080 | 2.03 | 1.00 | 909 |
| 2 | 3 | 6 | 0.045 | 1.14 | 0.080 | 2.03 | 1.03 | 1155 |
| 2 | 4 | 6 | 0.045 | 1.14 | 0.080 | 2.03 | 1.15 | 1429 |

All values are nominal and subject to correction



Transformer Riser Wire

APPLICATION: Used as uninsulated transformer risers for applications at high voltages. Although not treated as an insulation, the covering on transformer riser wire does reduce faults due to atmospheric conditions, shorts caused by excessive vibrations and faulting caused by objects crossing the leads.

CONSTRUCTION: Conductors are solid or stranded soft drawn bare copper. Stranded conductors are concentrically stranded, compressed. The covering is high molecular weight polyethylene, black.

SPECIFICATIONS: Transformer riser wire meets or exceeds the following specifications: ASTM B3 Soft or Annealed Copper Wire, ASTM B8 Concentric-Lay-Stranded Copper Conductor, D1248 Polyethylene Plastics Extrusion Materials for Wire and Cable, and ANSI/ICEA S-70-547 Weather-Resistant Polyethylene Covered Conductors.

OPTIONS: High Density Polyethylene. Other Covering Thickness

| Conductor Size AWG | No. of Strands | Bare Conductor Diameter | | Covering Thickness | | Covered Diameter | | Weight |
|-----------------------|----------------|-------------------------|-------|--------------------|------|------------------|------|---------|
| | | inches | mm | inches | mm | inches | mm | lbs/kft |
| 8 | Solid | 0.129 | 3.28 | 0.110 | 2.79 | 0.35 | 8.9 | 83 |
| 6 | Solid | 0.162 | 4.11 | 0.110 | 2.79 | 0.38 | 9.7 | 117 |
| 6 | 7 | 0.184 | 4.67 | 0.110 | 2.79 | 0.40 | 10.3 | 122 |
| 4 | Solid | 0.204 | 5.18 | 0.110 | 2.79 | 0.42 | 10.8 | 170 |
| 4 | 7 | 0.232 | 5.89 | 0.110 | 2.79 | 0.45 | 11.5 | 177 |
| 2 | Solid | 0.258 | 6.55 | 0.110 | 2.79 | 0.48 | 12.1 | 255 |
| 2 | 7 | 0.292 | 7.42 | 0.110 | 2.79 | 0.51 | 13.0 | 270 |
| 1/0 | 19 | 0.373 | 9.47 | 0.110 | 2.79 | 0.59 | 15.1 | 400 |
| 2/0 | 19 | 0.419 | 10.64 | 0.125 | 3.18 | 0.67 | 17.0 | 505 |
| 4/0 | 19 | 0.528 | 13.41 | 0.125 | 3.18 | 0.78 | 19.8 | 765 |

All values are nominal and subject to correction

5/15KV Jumper - Exciter Cable - Transformer Lead Wire

APPLICATION: This cable is for use as flexible power leads permitting temporary connections or bypassing energized power lines at voltages up through 15KV, phase to phase.

INSTALLATIONS: These cables must be positioned away from contact with grounds, transformer cases, cross-arms, etc., to avoid possible high stress and capacitance leakage due to the fact that jumper cables cannot be protected against prolonged contact with other conductors or grounds by shielding.

SPECIFICATIONS: Conductor: Flexible stranded tinned copper conductor with a semi-conducting tape separator. Insulation: Heat and moisture resistant 175mil thick ethylene propylene (EPR). Jacket: Heavy duty, red or black 80 mil thick CPE. Rating: 5KV/15KV -40°C to 90°C. ASTM B-33, B-172. ICEA S-75-381.

| Conductor Size AWG/kcmil | No. of Strands | Overall Diameter | | Weight |
|-----------------------------|----------------|------------------|------|---------|
| | | inches | mm | lbs/kft |
| 2 | 259 | 0.82 | 20.8 | 550 |
| 1/0 | 426 | 0.89 | 22.7 | 730 |
| 2/0 | 532 | 1.00 | 25.3 | 850 |
| 4/0 | 852 | 1.14 | 29.0 | 1,174 |
| 350 | 1,410 | 1.31 | 33.2 | 2,220 |
| 500 | 1,952 | 1.41 | 35.8 | 2,377 |
| 777 | 7,581 | 1.57 | 39.8 | 2,997 |
| 1550 | 15,561 | 1.97 | 49.9 | 5,649 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



1/C Copper XLP RHH/RHW-2/USE-2 600V

APPLICATION: Type RHH or RHW-2 or USE-2 copper conductors are used with conduit as specified with the National Electrical Code. When used as Type USE-2, conductor is suitable for use as underground service entrance cable for direct burial at conductor temperatures not to exceed 90°C. When used as RHH, conductor temperatures shall not exceed 90°C in dry locations. When used as RHW-2 or USE-2, conductor temperatures shall not exceed 90°C in wet or dry locations. Voltage rating for RHH or RHW-2 or USE-2 conductors is 600 volts. Sizes 1/0 AWG through 1000kcmil rated for use in cable tray.

CONSTRUCTION: Annealed or soft drawn copper. Insulation is an abrasion, moisture, heat, and sunlight resistant cross-linked polyethylene (XLP).

SPECIFICATIONS: Type RHH or RHW-2 or USE-2 meets or exceeds standards UL 44 (for RHH or RHW-2), UL 854 (for USE-2). ICEA S-95-658/NEMA WC 70 - Nonshielded 0 - 2 kV Cables. ASTM B3 Soft or Annealed Copper Wire, B8 Concentric Lay Stranded Copper Conductors, or B787 19 Wire Combination Unilay-Stranded Copper Conductors. Federal Specification A-A-59544, and requirements of the National Electrical Code. Sunlight Resistant. Colors Available. RoHS Compliant.

| Conductor Size AWG/kcmil | No. of Strands | Insulation Thickness | Nominal O.D. | Approx. Weight | Allowable Ampacities* (amps) | | |
|-----------------------------|----------------|----------------------|--------------|----------------|------------------------------|------|------|
| | | inches | inches | lbs/kft | 60°C | 75°C | 90°C |
| 14** | 7 | 0.045 | 0.16 | 21 | 15 | 20 | 25 |
| 12** | 7 | 0.045 | 0.18 | 30 | 20 | 25 | 30 |
| 10** | 7 | 0.045 | 0.21 | 43 | 30 | 35 | 40 |
| 8 | 7 | 0.060 | 0.26 | 69 | 40 | 50 | 55 |
| 6 | 7 | 0.060 | 0.30 | 103 | 55 | 65 | 75 |
| 4 | 7 | 0.060 | 0.35 | 156 | 70 | 85 | 95 |
| 2 | 7 | 0.060 | 0.40 | 238 | 95 | 115 | 130 |
| 1 | 19 | 0.080 | 0.48 | 307 | 110 | 130 | 145 |
| 1/0 | 19 | 0.080 | 0.52 | 384 | 125 | 150 | 170 |
| 2/0 | 19 | 0.080 | 0.56 | 476 | 145 | 175 | 195 |
| 3/0 | 19 | 0.080 | 0.61 | 590 | 165 | 200 | 225 |
| 4/0 | 19 | 0.080 | 0.67 | 735 | 195 | 230 | 260 |
| 250 | 37 | 0.095 | 0.76 | 868 | 215 | 255 | 290 |
| 300 | 37 | 0.095 | 0.80 | 1029 | 240 | 285 | 320 |
| 350 | 37 | 0.095 | 0.87 | 1192 | 260 | 310 | 350 |
| 400 | 37 | 0.095 | 0.90 | 1352 | 280 | 335 | 380 |
| 500 | 37 | 0.095 | 0.99 | 1673 | 320 | 380 | 430 |
| 600 | 61 | 0.110 | 1.09 | 2012 | 350 | 420 | 475 |
| 700 | 61 | 0.110 | 1.16 | 2332 | 385 | 460 | 520 |
| 750 | 61 | 0.110 | 1.21 | 2493 | 400 | 475 | 535 |
| 800 | 61 | 0.110 | 1.22 | 2652 | 410 | 490 | 555 |
| 900 | 61 | 0.110 | 1.28 | 2970 | 435 | 520 | 585 |
| 1000 | 61 | 0.110 | 1.37 | 3292 | 455 | 545 | 615 |

All values are nominal and subject to correction

* Allowable ampacities shown are for general use as specified by the National Electric Code, 2023 Edition, Table 310.16.

60°C - when terminated to equipment for circuits rated 100 amperes or less or marked for #14 through #1 conductors.

75°C - when terminated to equipment for circuits rated over 100 amperes or less or marked for conductors larger than #1.

90°C - RHH dry locations. RHW-2 and USE-2 wet or dry locations. For Ampacity derating purposes.

**Per the NEC 240.4(D) footnote, the overcurrent protection shall not exceed 15 amps for #14 AWG, 20 amps for #12 AWG, and 30 amps for #10 AWG.

1-800-945-5542

www.PriorityWire.com



1/C Aluminum XLP RHH/RHW-2/USE-2 600V

APPLICATION: The product can be installed as a General Purpose Building Wire, used in service entrance, feeders and branch circuits applications for residential, commercial, industrial, and transportation environments for permanent installations utilizing 600 volts or less. Thanks to its excellent performance in overload or short circuit situations, and its heavy wall thickness, the product is ideal for underground service entrance (USE) in wet locations. RHH/RHW-2/USE-2 conductors are suitable for directly buried installations, for environments where superior insulation toughness and chemical resistance are required, for outdoors, and for weather resistant use.

DESCRIPTION: Type RHH/RHW-2/USE-2, is a single insulated conductor of AA-8000 series aluminum alloy, compact stranded insulated with black thermoset crosslinked polyethylene (XLPE), designed to operate not over 600 volts, nominal, and at a maximum operating temperature of 90°C dry or wet.

INSTALLATION: RHH/RHW-2/USE-2 conductors can be installed in electrical metallic tubing, PVC conduits and other raceways, in free air messenger support or directly buried. It is recommended that the installation instruction indicated by the Local Electric Code, or any equivalent be followed so that the safeguarding of persons and the integrity of the product will not be affected by deficiencies in the installation.

SPECIFICATIONS: ASTM B800, B801, UL44, UL854, NEC, ICEA S-105-692, ICEA S-95-658/NEMA WC 70

| Conductor Size AWG/kcmil | No. of Strands | Insulation Thickness | Nominal O.D. | Approx. Weight | Allowable Ampacities* (amps) | | |
|-----------------------------|----------------|----------------------|--------------|----------------|------------------------------|------|------|
| | | inches | inches | lbs/kft | 60°C | 75°C | 90°C |
| 8 | 7 | 0.060 | 0.26 | 36 | 35 | 40 | 45 |
| 6 | 7 | 0.060 | 0.29 | 49 | 40 | 50 | 55 |
| 4 | 7 | 0.060 | 0.34 | 65 | 55 | 65 | 75 |
| 3 | 7 | 0.060 | 0.37 | 78 | 65 | 75 | 85 |
| 2 | 7 | 0.060 | 0.39 | 94 | 75 | 90 | 100 |
| 1 | 18 | 0.080 | 0.46 | 126 | 85 | 100 | 115 |
| 1/0 | 18 | 0.080 | 0.50 | 151 | 100 | 120 | 135 |
| 2/0 | 18 | 0.080 | 0.54 | 182 | 115 | 135 | 150 |
| 3/0 | 18 | 0.080 | 0.59 | 221 | 130 | 155 | 175 |
| 4/0 | 18 | 0.080 | 0.64 | 269 | 150 | 180 | 205 |
| 250 | 35 | 0.095 | 0.71 | 326 | 170 | 205 | 230 |
| 300 | 35 | 0.095 | 0.76 | 381 | 195 | 230 | 260 |
| 350 | 35 | 0.095 | 0.81 | 435 | 210 | 250 | 280 |
| 400 | 35 | 0.095 | 0.85 | 489 | 225 | 270 | 305 |
| 500 | 35 | 0.095 | 0.93 | 595 | 260 | 310 | 350 |
| 700 | 58 | 0.110 | 1.10 | 829 | 315 | 375 | 425 |
| 750 | 58 | 0.110 | 1.13 | 881 | 320 | 385 | 435 |
| 1000 | 58 | 0.110 | 1.28 | 1145 | 375 | 445 | 500 |

All values are nominal and subject to correction

* Allowable ampacities shown are for general use as specified by the National Electric Code, 2023 Edition, Table 310.16.

60°C - when terminated to equipment for circuits rated 100 amperes or less or marked for #14 through #1 conductors.

75°C - when terminated to equipment for circuits rated over 100 amperes or less or marked for conductors larger than #1.

90°C - RHH dry locations. RHW-2 and USE-2 wet or dry locations.

1-800-945-5542

www.PriorityWire.com



1/C Tinned Copper EPR RHH/RHW-2/USE-2 CPE 600V

APPLICATION: Primarily used for power distribution in a broad range of commercial, industrial and utility applications. Single conductor EPR/CPE can be installed in free air, raceways or direct buried for service entrance below ground in both wet and dry locations.

CONDUCTORS: Soft drawn tin coated copper, Class B stranded per ASTM B-8, B-33

SEPARATOR: Tape separator between the conductor and insulation

INSULATION: Ethylene-propylene rubber (EPR)

JACKET: Black heavy duty, thermoset CPE

STANDARDS: UL 44 Type RHH/RHW-2, UL 854 Type USE-2, ICEA S-95-658, NEMA WC70, ASTM B-8, B-33, VW-1, Sunlight Resistant, "FOR CT USE" for 1/0 AWG and larger.

| Size | No. of Strands | Insulation Thickness | Jacket Thickness | Overall Diameter | Weight | Ampacity* @ 90°C |
|-----------|----------------|----------------------|------------------|------------------|---------|---------------------|
| AWG/kcmil | | inches | inches | inches | lbs/kft | amps |
| 14 | 7 | 0.030 | 0.015 | 0.17 | 24 | 25 |
| 12 | 7 | 0.030 | 0.015 | 0.19 | 34 | 30 |
| 10 | 7 | 0.030 | 0.015 | 0.21 | 49 | 40 |
| 8 | 7 | 0.045 | 0.015 | 0.28 | 79 | 55 |
| 6 | 7 | 0.045 | 0.030 | 0.35 | 124 | 75 |
| 4 | 7 | 0.045 | 0.030 | 0.39 | 179 | 95 |
| 2 | 7 | 0.045 | 0.030 | 0.45 | 260 | 130 |
| 1/0 | 19 | 0.055 | 0.045 | 0.58 | 420 | 170 |
| 2/0 | 19 | 0.055 | 0.045 | 0.62 | 513 | 195 |
| 4/0 | 19 | 0.055 | 0.045 | 0.74 | 774 | 225 |
| 250 | 37 | 0.065 | 0.065 | 0.85 | 956 | 260 |
| 350 | 37 | 0.065 | 0.065 | 0.96 | 1290 | 350 |
| 500 | 37 | 0.065 | 0.065 | 1.09 | 1798 | 430 |
| 750 | 61 | 0.080 | 0.065 | 1.30 | 2686 | 535 |
| 1000 | 61 | 0.080 | 0.065 | 1.46 | 3463 | 615 |

All values are nominal and subject to correction

*Allowable ampacities shown are for general use as specified by the National Electric Code, 2023 Edition Table 310.16.

1-800-945-5542

www.PriorityWire.com



Bare and Tinned Copper Conductors

APPLICATION: For use on insulators for overhead distribution circuits or grounding conductors.

DESCRIPTION: Solid or concentric-lay stranded bare copper conductors available in soft, medium-hard, or hard temper. Tin coated copper conductors available in soft temper only.

SPECIFICATIONS: ASTM B-1 Hard Drawn ASTM B-2 Medium Hard Drawn ASTM B-3 Soft or Annealed ASTM B-8 Concentric lay stranded conductors Federal Spec A-A-59551.

OPTIONS: Tinned copper per ASTM B-33.

NOTE:

- When Hard Drawn is required add HD.
- When Medium Hard Drawn is required, add MHD.
- When Tinned is required, add T.

| Conductor Size | Cross Sectional Area | No. of Strands | Overall Diameter | Weight |
|-----------------------------------|----------------------|----------------|------------------|---------|
| AWG/kcmil | cmils | | inches | lbs/kft |
| SOFT DRAWN COPPER-SOLID | | | | |
| 14 | 4110 | Solid | 0.0640 | 13 |
| 12 | 6530 | Solid | 0.0810 | 20 |
| 10 | 10380 | Solid | 0.1020 | 32 |
| 8 | 16510 | Solid | 0.1285 | 50 |
| 6 | 26240 | Solid | 0.1620 | 79 |
| 4 | 41740 | Solid | 0.2043 | 126 |
| 2 | 66360 | Solid | 0.2576 | 201 |
| SOFT DRAWN COPPER-STRANDED | | | | |
| 8 | 16510 | 7 | 0.146 | 51 |
| 6 | 26240 | 7 | 0.184 | 81 |
| 4 | 41740 | 7 | 0.232 | 129 |
| 2 | 66360 | 7 | 0.292 | 205 |
| 1 | 83690 | 19 | 0.332 | 258 |
| 1/0 | 105600 | 7 or 19 | 0.373 | 326 |
| 2/0 | 133100 | 7 or 19 | 0.419 | 411 |
| 3/0 | 167800 | 7 or 19 | 0.470 | 518 |
| 4/0 | 211600 | 7 or 19 | 0.528 | 653 |
| 250 | 250000 | 19 or 37 | 0.575 | 772 |
| 350 | 350000 | 19 or 37 | 0.681 | 1081 |
| 500 | 500000 | 37 | 0.813 | 1544 |
| 750 | 750000 | 61 | 0.998 | 2316 |
| 1000 | 1000000 | 61 | 1.152 | 3088 |

| Conductor Size | Footage | Conductor Size | Footage |
|-------------------------------------|---------|----------------|---------|
| AWG/kcmil | | AWG | |
| 25 POUND DISTRIBUTION SPOOLS | | | |
| 14 Solid | 2015 | 8 - 7 | 490 |
| 12 Solid | 1265 | 6 - 7 | 308 |
| 10 Solid | 795 | 4 - 7 | 200 |
| 8 Solid | 500 | 2 - 7 | 125 |
| 6 Solid | 315 | | |
| 4 Solid | 200 | | |
| 2 Solid | 125 | | |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



Aluminum Clad Steel Wire

APPLICATION: Aluminum Clad Steel Guy or “Messenger” Wire and Static Wire are used in utility classifications for overhead use such as in power lines, telephone lines, railway signals, communication lines, towers, and masts. It is a high strength wire with aluminum thickness in minimum of 10% wire radius creating an electrical conductivity of 20.3%, highly corrosive resistant, and a thermal stability for high temperature operation and all with a lighter weight.

STANDARDS: ASTM B415, B416.

RUS ACCEPTED

| No. x Size | Diameter | Breaking Load | Weight |
|--------------------|----------|---------------|---------|
| AWG | inches | lbs | lbs/kft |
| Static Wire | | | |
| 3#5 | 0.392 | 12,230 | 225 |
| 3#6 | 0.349 | 10,280 | 178 |
| 3#7 | 0.311 | 8,621 | 141 |
| 3#8 | 0.277 | 7,206 | 112 |
| 3#9 | 0.247 | 5,715 | 89 |
| 3#10 | 0.220 | 4,532 | 70 |
| 7#5* | 0.546 | 27,030 | 525 |
| 7#6* | 0.486 | 22,730 | 416 |
| 7#7* | 0.433 | 19,060 | 330 |
| 7#8* | 0.385 | 15,930 | 262 |
| 7#9* | 0.343 | 12,630 | 208 |
| 7#10* | 0.306 | 10,020 | 165 |
| 7#11* | 0.272 | 7,954 | 131 |
| 7#12* | 0.242 | 6,301 | 104 |
| 19#5 | 0.910 | 73,350 | 1430 |
| 19#6 | 0.810 | 61,700 | 1134 |
| 19#7 | 0.721 | 51,730 | 900 |
| 19#8 | 0.642 | 43,240 | 714 |
| 19#9 | 0.572 | 34,290 | 566 |
| 19#10 | 0.509 | 27,190 | 449 |
| 37#5 | 1.270 | 142,800 | 2802 |
| 37#6 | 1.130 | 120,200 | 2222 |
| 37#7 | 1.010 | 100,700 | 1762 |
| 37#8 | 0.899 | 84,200 | 1398 |
| 37#9 | 0.801 | 66,770 | 1108 |
| 37#10 | 0.713 | 52,950 | 879 |

Static Wire: 5000' reel put ups

| Designation | No. x Size | Diameter | Breaking Load | Weight |
|--|------------|----------|---------------|---------|
| | AWG | inches | lbs | lbs/kft |
| Guy and Messenger Wire AWG Equivalent | | | | |
| 6M* | 7#12 | 0.242 | 6,300 | 104 |
| 8M* | 7#11 | 0.272 | 8,000 | 131 |
| 10M* | 7#10 | 0.306 | 10,000 | 165 |
| 12.5M* | 7#9 | 0.343 | 12,500 | 206 |
| 14M* | 7x0.121" | 0.363 | 14,100 | 232 |
| 16M* | 7#8 | 0.385 | 16,000 | 260 |
| 20M* | 7x0.148" | 0.444 | 20,000 | 348 |

All values are nominal and subject to correction

**RUS accepted construction*

Guy and Messenger Wire: 500' coils and 5000' reel put ups

1-800-945-5542

www.PriorityWire.com



Ground Rods & Plates

APPLICATION: To be driven into the earth to provide grounding for substations, towers, homes, buildings and all other structures that contain electrical products or for applications to provide grounding against lightning.

SPECIFICATIONS:

Copper: High Quality steel with a constant covering of electrolytic copper. UL 467 for ground rods of one-half inch to one inch in diameter, eight to ten feet in length. • 10 & 13 Mil Rods 8' and larger are UL approved , RUS accepted copper rods are as noted.

Galvanized Rod: High Quality Steel with a constant covering of zinc. ANSI/ASTM A153. Option: Also available with REA (RUS) electrical and telephone approvals.

Galvanized Plate: UL 467 approved. High Quality Steel with a consistent covering of zinc. Grounding plate as efficient as two 10ft. x 5/8" ground rods.

| Part Number | Rod Size x Length | Nominal O.D. | Master Bundle | Weight | | Copper Thickness | UL Listed |
|--|-------------------|--------------|---------------|------------|-------------|------------------|-----------|
| | | inches | pcs | lbs/bundle | lbs/100 Pcs | mils | |
| COPPER GROUND RODS SINGLE TYPE | | | | | | | |
| PWC125 | 1/2" x 5' | 0.433 | 100 | 312 | 312 | 5 | NO |
| PWC126 | 1/2" x 6' | 0.433 | 100 | 400 | 400 | 5 | NO |
| PWC128-5 | 1/2" x 8' | 0.433 | 100 | 500 | 500 | 5 | NO |
| PWC128 | 1/2" x 8' | 0.433 | 100 | 500 | 500 | 10 | YES |
| PWC128-10 | 1/2" x 8' | 0.496 | 100 | 500 | 500 | 10 | YES |
| PWC1210 | 1/2" x 10' | 0.496 | 100 | 625 | 625 | 10 | YES |
| PWC586 | 5/8" x 6' | 0.555 | 100 | 510 | 510 | 5 | NO |
| PWC588* | 5/8" x 8' | 0.555 | 100 | 700 | 700 | 10 | YES |
| PWC588-13* | 5/8" x 8' | 0.563 | 100 | 700 | 700 | 13 | YES |
| PWC5810-13 | 5/8" x 10' | 0.563 | 100 | 870 | 870 | 13 | YES |
| PWC5810* | 5/8" x 10' | 0.555 | 100 | 900 | 900 | 10 | YES |
| PWC348* | 3/4" x 8' | 0.673 | 50 | 500 | 1000 | 10 | YES |
| PWC348-13* | 3/4" x 8' | 0.680 | 50 | 572 | 1144 | 13 | YES |
| PWC3410* | 3/4" x 10' | 0.673 | 50 | 650 | 1300 | 10 | YES |
| PWC110 | 1" x 10' | 0.894 | 25 | 575 | 2300 | 10 | YES |
| COPPER GROUND RODS SECTIONAL TYPE | | | | | | | |
| PWCS1210 | 1/2" x 10' | 0.496 | 100 | 625 | 625 | 10 | YES |
| PWCS588* | 5/8" x 8' | 0.555 | 100 | 680 | 680 | 10 | YES |
| PWCS588-13* | 5/8" x 8' | 0.555 | 100 | 696 | 696 | 13 | YES |
| PWCS5810* | 5/8" x 10' | 0.555 | 100 | 900 | 900 | 10 | YES |
| PWCS348* | 3/4" x 8' | 0.673 | 50 | 500 | 1000 | 10 | YES |
| PWCS3410* | 3/4" x 10' | 0.673 | 50 | 650 | 1300 | 10 | YES |
| PWCS3410-13* | 3/4" x 10' | 0.673 | 50 | 745 | 1490 | 13 | YES |
| PWCS110 | 1" x 10' | 0.894 | 25 | 575 | 2300 | 10 | YES |

All values are nominal and subject to correction

*RUS accepted

**UL listed upon request

Call for additional sizes.

(Continued on page 41)

1-800-945-5542

www.PriorityWire.com



Ground Rods & Plates

CONTINUED

| Part Number | Rod Size x Length | Nominal O.D. | Master Bundle | Weight | | Copper Thickness | UL Listed |
|--|-------------------|--------------|---------------|------------|-------------|------------------|-----------|
| | | inches | pcs | lbs/bundle | lbs/100 Pcs | mils | |
| HOT DIPPED GALVANIZED GROUND RODS | | | | | | | |
| PWCG125 | ½" x 5' | 0.485 | 100 | 300 | 300 | - | NO |
| PWCG126 | ½" x 6' | 0.485 | 100 | 400 | 400 | - | NO |
| PWCG586 | ⅝" x 6' | 0.543-0.555 | 100 | 490 | 490 | - | NO |
| PWCG588 | ⅝" x 8' | 0.543-0.555 | 100 | 650 | 650 | - | NO** |
| PWCG588F | ⅝" x 8' | 0.625 | 100 | 800 | 800 | - | NO |
| PWCG5810 | ⅝" x 10' | 0.543-0.555 | 100 | 820 | 820 | - | NO** |
| PWCG3410 | ¾" x 10' | 0.75-0.765 | 50 | 1530 | 765 | - | NO** |

| Part Number | Plate Width x Length | Plate Thickness | Grounding Connector Post | Weight | | Copper Thickness | UL Listed |
|---|----------------------|-----------------|----------------------------|-----------|-------------|------------------|-----------|
| | | | Width x Length Above Plate | lbs/plate | lbs/100 Pcs | mils | |
| HOT DIPPED GALVANIZED GROUND PLATE | | | | | | | |
| PWCGP | 10" x 16" | 0.25" | 0.58" x 2" | 12 | 1200 | - | YES |

All values are nominal and subject to correction

*RUS accepted

**UL listed upon request

Call for additional sizes.

1-800-945-5542

www.PriorityWire.com



Ground Rod Accessories

Ground Rod Couplings: UL / CSA - Connects two copper sectional ground rods - Tapered ends to reduce driving friction - constructed of high strength, corrosion resistant bronze.

Direct Burial Ground Rod Clamps: UL / CSA - Connects grounding conductor to driven copper ground rod - Approved for direct burial in the earth and concrete - Contains a bronze hex headed bolt - Constructed of high strength, corrosive resistant bronze

Bronze Water Pipe Ground Clamps: UL / CSA - connects grounding conductor to driven galvanized ground rod - Constructed of high strength, highly conductive bronze - Steel screws plated for corrosion resistance or Bronze screw depending on part number

Cast Bronze Plated Water Pipe Ground Clamps: Connects grounding conductor to galvanized ground rod - Die cast zinc body with brass colored plating - Assembled with zinc plated steel screws for corrosion resistance

Ground Rod Driving Studs: UL listed - Threads onto ground rod coupling for driving to eliminate damage to ground rod threads • Constructed from high strength, corrosive resistant steel with bronze plating

| Part Number | Size | Wire Size (AWG) | | Standard Packaging Pcs | Weight | |
|---|--------------|-----------------|--------|------------------------|-------------|-------------|
| | | max | min | | lbs/Package | lbs/100 Pcs |
| Ground Rod Couplings | | | | | | |
| PC12 | 1/2" | - | - | 10 | 1.6 | 16 |
| PC58 | 5/8" | - | - | 10 | 2.5 | 25 |
| PC34 | 3/4" | - | - | 10 | 3.8 | 38 |
| PC01 | 1" | - | - | 10 | 6.5 | 65 |
| Direct Burial Rod Clamps | | | | | | |
| P4 | 1/2" | 2 | 10 | 100 | 9 | 9 |
| P5 | 5/8" | 2 | 10 | 50 | 5 | 10 |
| P6 | 3/4" | 2 | 10 | 50 | 5.5 | 11 |
| PU | 1/2" - 3/4" | 1/0 | 10 | 50 | 9.5 | 19 |
| Bronze Water Pipe Ground Clamps-Plated Steel Screw | | | | | | |
| PWP121 | 1/2" | 2 | 10 Sol | 25 | 4.8 | 19 |
| PWP1142 | 1 1/4" to 2" | 2 | 10 Sol | 10 | 4.3 | 43 |
| Bronze Water Pipe Ground Clamps-Bronze Screw-Direct Burial | | | | | | |
| PWP121-DB | 1/2" to 1" | 2 | 10 Sol | 10 | 4.3 | 43 |
| Cast Bronze Plated Water Pipe Ground Clamps | | | | | | |
| PWPP121 | 1/2" to 1" | 2 | 10 Sol | 100 | 17 | 17 |
| Ground Rod Driving Studs | | | | | | |
| PD12 | 1/2" | - | - | 10 | 1.2 | 12 |
| PD58 | 5/8" | - | - | 10 | 2.3 | 23 |
| PD34 | 3/4" | - | - | 10 | 3.5 | 35 |
| PD01 | 1" | - | - | 10 | 4.9 | 49 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



FR-NP™ Flame Resistant – Non-Propagating Spacer Cable (Tree Wire)

APPLICATION: Used in primary and secondary overhead distribution where there is limited space available for rights of way, and where fire hazards are concerns. Its close-proximity configuration minimizes the amount of space and hardware required for line installation effectively solving most right-of-way-problems. In case of a fire, the flame resistant wire will eliminate the spread of fires along transmission lines, which reduces the secondary fires caused by the propagation and dripping flaming material.

CONSTRUCTION: Stranded hard drawn AAC, AAAC, or ACSR conductors. A semi-conducting tape may be applied over conductor as needed. Semiconducting Cross-linked Polyethylene, black strand shield. Crosslinked polyethylene (XLP), natural inner covering. Flame, sunlight and track resistant crosslinked polyethylene (XLP), black or gray outer covering.

SPECIFICATIONS: UL 2556 Flame Test FT1/VW-1, FT2 • ICEA: S-121-733 Tree Wire and Messenger Supported Spacer Cable • ASTM B230 Aluminum 1350-H19 Wire for Electrical Purposes. B231 Concentric-Lay-Stranded Aluminum 1350 Conductors. B232 Concentric-Lay-Stranded Aluminum Conductors, Coated-Steel Reinforced (ACSR).B398 Aluminum-Alloy 6201-T81 and 6201-T83 Wire for Electrical Purposes. B399 Concentric Lay-Stranded Aluminum Alloy 6201-T81 Conductors. B-400 Compact Round Concentric-Lay-Stranded Aluminum 1350 Conductors. B498 Zinc-Coated (Galvanized) Steel Core Wire for Use in Overhead Electrical Conductors.

| Conductor Size AWG/kcmil | Min. Number of Strands* | Stranding Type | Conductor Diameter inches | Conductor Shield Thickness inches | Covering Thickness | | Finished Cable Diameter inches | Cable Weight lbs/kft | Rated Strength lbs |
|-----------------------------|-------------------------|----------------|------------------------------|--------------------------------------|--------------------|-----------------|-----------------------------------|-------------------------|-----------------------|
| | | | | | Inner inches | Outer inches | | | |
| AAC Conductors-15kV | | | | | | | | | |
| 2 | 7 | Compressed | 0.292 | 0.015 | 0.075 | 0.075 | 0.62 | 191 | 1,112 |
| 1/0 | 7 | Compact | 0.336 | 0.015 | 0.075 | 0.075 | 0.67 | 238 | 1,791 |
| 2/0 | 7 | Compact | 0.376 | 0.015 | 0.075 | 0.075 | 0.71 | 274 | 2,259 |
| 3/0 | 7 | Compact | 0.423 | 0.015 | 0.075 | 0.075 | 0.75 | 319 | 2,736 |
| 4/0 | 18 | Compact | 0.475 | 0.015 | 0.075 | 0.075 | 0.81 | 374 | 3,447 |
| 266.8 | 18 | Compact | 0.537 | 0.015 | 0.075 | 0.075 | 0.87 | 442 | 4,473 |
| 336.4 | 18 | Compact | 0.603 | 0.015 | 0.075 | 0.075 | 0.93 | 524 | 5,535 |
| 397.5 | 18 | Compact | 0.659 | 0.015 | 0.075 | 0.075 | 0.99 | 595 | 6,399 |
| 477 | 35 | Compact | 0.722 | 0.015 | 0.075 | 0.075 | 1.05 | 686 | 7,524 |
| 556.5 | 35 | Compact | 0.780 | 0.020 | 0.075 | 0.075 | 1.13 | 798 | 8,946 |
| 636 | 35 | Compact | 0.835 | 0.020 | 0.075 | 0.075 | 1.19 | 887 | 10,260 |
| 715.5 | 58 | Compact | 0.897 | 0.020 | 0.080 | 0.080 | 1.27 | 1,000 | 11,790 |
| 795 | 58 | Compact | 0.932 | 0.020 | 0.080 | 0.080 | 1.30 | 1,084 | 12,510 |
| AAC Conductors-25kV | | | | | | | | | |
| 2 | 7 | Compressed | 0.292 | 0.015 | 0.125 | 0.125 | 0.82 | 315 | 1,112 |
| 1/0 | 7 | Compact | 0.336 | 0.015 | 0.125 | 0.125 | 0.87 | 369 | 1,791 |
| 2/0 | 7 | Compact | 0.376 | 0.015 | 0.125 | 0.125 | 0.91 | 412 | 2,259 |
| 3/0 | 7 | Compact | 0.423 | 0.015 | 0.125 | 0.125 | 0.95 | 464 | 2,736 |
| 4/0 | 18 | Compact | 0.475 | 0.015 | 0.125 | 0.125 | 1.01 | 527 | 3,447 |
| 266.8 | 18 | Compact | 0.537 | 0.015 | 0.125 | 0.125 | 1.07 | 605 | 4,473 |
| 336.4 | 18 | Compact | 0.603 | 0.015 | 0.125 | 0.125 | 1.13 | 698 | 5,535 |
| 397.5 | 18 | Compact | 0.659 | 0.015 | 0.125 | 0.125 | 1.19 | 779 | 6,399 |
| 477 | 35 | Compact | 0.722 | 0.015 | 0.125 | 0.125 | 1.25 | 879 | 7,524 |
| 556.5 | 35 | Compact | 0.780 | 0.020 | 0.125 | 0.125 | 1.33 | 1,004 | 8,946 |
| 636 | 35 | Compact | 0.835 | 0.020 | 0.125 | 0.125 | 1.39 | 1,102 | 10,260 |
| 795 | 58 | Compact | 0.932 | 0.020 | 0.125 | 0.125 | 1.48 | 1,293 | 12,510 |

(Continued on page 44)

1-800-945-5542

www.PriorityWire.com



FR-NP™ Flame Resistant – CONTINUED Non-Propagating Spacer Cable (Tree Wire)

| Conductor Size AWG/kcmil | Min. Number of Strands* | Stranding Type | Conductor Diameter inches | Conductor Shield Thickness inches | Covering Thickness | | Finished Cable Diameter inches | Cable Weight lbs/kft | Rated Strength lbs |
|-----------------------------|-------------------------|----------------|------------------------------|--------------------------------------|--------------------|-----------------|-----------------------------------|-------------------------|-----------------------|
| | | | | | Inner inches | Outer inches | | | |
| AAC Conductors-35kV | | | | | | | | | |
| 1/0 | 7 | Compact | 0.336 | 0.015 | 0.175 | 0.125 | 0.97 | 437 | 1,791 |
| 2/0 | 7 | Compact | 0.376 | 0.015 | 0.175 | 0.125 | 1.01 | 482 | 2,259 |
| 3/0 | 7 | Compact | 0.423 | 0.015 | 0.175 | 0.125 | 1.05 | 538 | 2,736 |
| 4/0 | 18 | Compact | 0.475 | 0.015 | 0.175 | 0.125 | 1.11 | 604 | 3,447 |
| 266.8 | 18 | Compact | 0.537 | 0.015 | 0.175 | 0.125 | 1.17 | 686 | 4,473 |
| 336.4 | 18 | Compact | 0.603 | 0.015 | 0.175 | 0.125 | 1.23 | 783 | 5,535 |
| 397.5 | 18 | Compact | 0.659 | 0.015 | 0.175 | 0.125 | 1.29 | 867 | 6,399 |
| 477 | 35 | Compact | 0.722 | 0.015 | 0.175 | 0.125 | 1.35 | 972 | 7,524 |
| 556.5 | 35 | Compact | 0.780 | 0.020 | 0.175 | 0.125 | 1.43 | 1,102 | 8,946 |
| 636 | 35 | Compact | 0.835 | 0.020 | 0.175 | 0.125 | 1.49 | 1,204 | 10,260 |
| 795 | 58 | Compact | 0.932 | 0.020 | 0.175 | 0.125 | 1.58 | 1,401 | 12,510 |
| AAAC Conductors-15kV | | | | | | | | | |
| 123.3 | 7 | Compressed | 0.398 | 0.015 | 0.075 | 0.075 | 0.73 | 271 | 3,843 |
| 155.4 | 7 | Compressed | 0.447 | 0.015 | 0.075 | 0.075 | 0.78 | 314 | 4,851 |
| 195.7 | 7 | Compressed | 0.502 | 0.015 | 0.075 | 0.075 | 0.83 | 367 | 6,111 |
| 246.9 | 7 | Compressed | 0.563 | 0.015 | 0.075 | 0.075 | 0.89 | 430 | 7,704 |
| 312.8 | 19 | Compressed | 0.642 | 0.015 | 0.075 | 0.075 | 0.97 | 521 | 9,450 |
| 394.5 | 19 | Compressed | 0.721 | 0.015 | 0.075 | 0.075 | 1.05 | 619 | 11,970 |
| 465.4 | 19 | Compressed | 0.783 | 0.015 | 0.075 | 0.075 | 1.11 | 702 | 14,040 |
| 559.5 | 19 | Compressed | 0.858 | 0.020 | 0.075 | 0.075 | 1.21 | 834 | 16,920 |
| AAAC Conductors-35kV | | | | | | | | | |
| 123.3 | 7 | Compressed | 0.398 | 0.015 | 0.175 | 0.125 | 1.03 | 484 | 3,843 |
| 155.4 | 7 | Compressed | 0.447 | 0.015 | 0.175 | 0.125 | 1.08 | 538 | 4,851 |
| 195.7 | 7 | Compressed | 0.502 | 0.015 | 0.175 | 0.125 | 1.13 | 603 | 6,111 |
| 246.9 | 7 | Compressed | 0.563 | 0.015 | 0.175 | 0.125 | 1.19 | 681 | 7,704 |
| 312.8 | 19 | Compressed | 0.642 | 0.015 | 0.175 | 0.125 | 1.27 | 793 | 9,450 |
| 394.5 | 19 | Compressed | 0.721 | 0.015 | 0.175 | 0.125 | 1.35 | 908 | 11,970 |
| 465.4 | 19 | Compressed | 0.783 | 0.015 | 0.175 | 0.125 | 1.41 | 1,005 | 14,040 |
| 559.5 | 19 | Compressed | 0.858 | 0.020 | 0.175 | 0.125 | 1.51 | 1,159 | 16,920 |

All values are nominal and subject to correction

*AAC: The minimum number of wires refers to the structure of Class A or B in ASTM B231 and B400.

*AAAC: The minimum number of wires refers to the structure of Class AA or A in ASTM B 399.

(Continued on page 45)

1-800-945-5542

www.PriorityWire.com



FR-NP™ Flame Resistant – Non-Propagating Spacer Cable (Tree Wire)

CONTINUED

| Conductor Size | Number of Strands | Conductor Diameter | Conductor Shield Thickness | Covering Thickness | | Finished Cable Diameter | Cable Weight | Rated Strength |
|-----------------------------|-------------------|--------------------|----------------------------|--------------------|--------|-------------------------|--------------|----------------|
| | | | | Inner | Outer | | | |
| AWG/kcmil | AL/Steel | inches | inches | inches | inches | inches | lbs/kft | lbs |
| ACSR Conductors-15kV | | | | | | | | |
| 4 | 6/1 | 0.250 | 0.015 | 0.075 | 0.075 | 0.58 | 175 | 1,767 |
| 2 | 6/1 | 0.316 | 0.015 | 0.075 | 0.075 | 0.65 | 227 | 2,707 |
| 1/0 | 6/1 | 0.398 | 0.015 | 0.075 | 0.075 | 0.73 | 304 | 4,161 |
| 2/0 | 6/1 | 0.447 | 0.015 | 0.075 | 0.075 | 0.78 | 357 | 5,035 |
| 3/0 | 6/1 | 0.502 | 0.015 | 0.075 | 0.075 | 0.83 | 418 | 6,289 |
| 4/0 | 6/1 | 0.563 | 0.015 | 0.075 | 0.075 | 0.89 | 495 | 7,932 |
| 266.8 | 18/1 | 0.609 | 0.015 | 0.075 | 0.075 | 0.87 | 493 | 6,536 |
| 266.8 | 26/7 | 0.642 | 0.015 | 0.075 | 0.075 | 0.97 | 601 | 10,573 |
| 336.4 | 18/1 | 0.684 | 0.015 | 0.075 | 0.075 | 1.01 | 611 | 8,246 |
| 336.4 | 26/7 | 0.720 | 0.015 | 0.075 | 0.075 | 1.05 | 718 | 13,395 |
| 336.4 | 30/7 | 0.741 | 0.015 | 0.075 | 0.075 | 1.07 | 788 | 16,971 |
| 397.5 | 18/1 | 0.743 | 0.015 | 0.075 | 0.075 | 1.07 | 694 | 9,443 |
| 397.5 | 24/7 | 0.772 | 0.015 | 0.075 | 0.075 | 1.10 | 781 | 13,775 |
| 397.5 | 26/7 | 0.783 | 0.015 | 0.075 | 0.075 | 1.11 | 819 | 15,485 |
| 477 | 24/7 | 0.846 | 0.015 | 0.075 | 0.075 | 1.18 | 905 | 16,340 |
| 477 | 26/7 | 0.858 | 0.015 | 0.075 | 0.075 | 1.19 | 950 | 18,525 |
| 477 | 30/7 | 0.883 | 0.015 | 0.075 | 0.075 | 1.21 | 1,048 | 22,610 |
| 556.5 | 18/1 | 0.879 | 0.020 | 0.075 | 0.075 | 1.23 | 930 | 13,015 |
| 556.5 | 24/7 | 0.914 | 0.020 | 0.075 | 0.075 | 1.26 | 1,052 | 18,810 |
| 556.5 | 26/7 | 0.927 | 0.020 | 0.075 | 0.075 | 1.28 | 1,106 | 21,375 |
| 636 | 18/1 | 0.940 | 0.020 | 0.075 | 0.075 | 1.29 | 1,035 | 14,915 |
| 636 | 26/7 | 0.990 | 0.020 | 0.075 | 0.075 | 1.34 | 1,234 | 23,940 |
| ACSR Conductors-25kV | | | | | | | | |
| 2 | 6/1 | 0.316 | 0.015 | 0.125 | 0.125 | 0.85 | 355 | 2,707 |
| 1/0 | 6/1 | 0.398 | 0.015 | 0.125 | 0.125 | 0.93 | 445 | 4,161 |
| 2/0 | 6/1 | 0.447 | 0.015 | 0.125 | 0.125 | 0.98 | 506 | 5,035 |
| 3/0 | 6/1 | 0.502 | 0.015 | 0.125 | 0.125 | 1.03 | 576 | 6,289 |
| 4/0 | 6/1 | 0.563 | 0.015 | 0.125 | 0.125 | 1.09 | 663 | 7,932 |
| 266.8 | 18/1 | 0.609 | 0.015 | 0.125 | 0.125 | 1.07 | 659 | 6,536 |
| 336.4 | 18/1 | 0.684 | 0.015 | 0.125 | 0.125 | 1.21 | 800 | 8,246 |
| 397.5 | 18/1 | 0.743 | 0.015 | 0.125 | 0.125 | 1.27 | 893 | 9,443 |
| 477 | 18/1 | 0.814 | 0.015 | 0.125 | 0.125 | 1.34 | 1,012 | 22,610 |
| 556.5 | 18/1 | 0.879 | 0.020 | 0.125 | 0.125 | 1.43 | 1,154 | 13,015 |
| 636 | 18/1 | 0.940 | 0.020 | 0.125 | 0.125 | 1.49 | 1,269 | 14,915 |
| 795 | 36/1 | 1.040 | 0.020 | 0.125 | 0.125 | 1.59 | 1,415 | 12,510 |
| ACSR Conductors-35kV | | | | | | | | |
| 4/0 | 6/1 | 0.563 | 0.015 | 0.175 | 0.125 | 1.19 | 746 | 7,932 |
| 266.8 | 18/1 | 0.609 | 0.015 | 0.175 | 0.125 | 1.24 | 767 | 6,536 |
| 336.4 | 18/1 | 0.684 | 0.015 | 0.175 | 0.125 | 1.31 | 892 | 8,246 |
| 397.5 | 18/1 | 0.743 | 0.015 | 0.175 | 0.125 | 1.37 | 988 | 9,443 |
| 477 | 18/1 | 0.814 | 0.015 | 0.175 | 0.125 | 1.44 | 1,111 | 22,610 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



Galvanized Steel Guy Strand

APPLICATION: Used to add stability to a free-standing structure or tower.

SPECIFICATIONS: Manufactured and inspected per ASTM A475 and BS-183.

RUS ACCEPTED

OPTIONS: Overhead Ground Wire per ASTM A363 is available upon request.

| CONSTRUCTION | | | | MINIMUM BREAKING STRENGTH | | | | COATING | |
|---------------|----------------|------------------------|----------------|---------------------------|----------------------|---------------------|---------------------------|--------------|-----------------------------|
| Wire Diameter | No. of Strands | Coated Strand Diameter | Approx. Weight | Utilities Grade | Siemens-Martin Grade | High Strength Grade | Extra High Strength Grade | Zinc Coating | Min. Coating Weight Class A |
| inches | | inches | lbs/kft | lbs | lbs | lbs | lbs | | oz/sq.ft. |
| 1/4 | 7 | 0.080 | 121 | - | 3,150 | 4,750 | 6,650 | 100% | 0.60 |
| 5/16 | 7 | 0.104 | 205 | - | 5,350 | 8,000 | 11,200 | 100% | 0.80 |
| 3/8 | 7 | 0.120 | 273 | 11,500 | 6,950 | 10,800 | 15,400 | 100% | 0.85 |
| 7/16 | 7 | 0.145 | 399 | 18,000 | 9,350 | 14,500 | 20,800 | 100% | 0.90 |
| 1/2 | 7 | 0.165 | 517 | 25,000 | 12,100 | 18,800 | 26,900 | 100% | 0.90 |
| 9/16 | 7 | 0.188 | 671 | - | 15,700 | 24,500 | 35,000 | 100% | 1.00 |

All values are nominal and subject to correction

PACKAGING: 250' and 500' Coils with 18" ID • 2,500' and 5,000' Reels • Bulk cut to length

Tap Wire - TPE (TPR) Covered

APPLICATION: Used to connect an overhead phase conductor to equipment bushings. This aids in preventing outages caused by wildlife connecting the energized tap wire with another phase or ground plane. This may also be used in substation equipment connections and as a covered ground lead.

CONDUCTOR: Compressed stranded or solid bare copper

INSULATION: Black thermoplastic elastomer (thermoplastic rubber).

SPECIFICATIONS: ASTM B3, B8, B258

| Conductor Size | No. of Strands | Conductor Diameter | | Insulation Thickness | | Overall Diameter | | Approx. Weight | Ampacity* |
|----------------|----------------|--------------------|------|----------------------|------|------------------|------|----------------|-----------|
| | | inches | mm | inches | mm | inches | mm | | |
| 6 | 7 | 0.178 | 4.52 | 0.150 | 3.81 | 0.48 | 12.1 | 145 | 130 |
| 6 | solid | 0.162 | 4.11 | 0.150 | 3.81 | 0.46 | 11.7 | 143 | 130 |
| 4 | 7 | 0.225 | 5.72 | 0.150 | 3.81 | 0.53 | 13.5 | 214 | 175 |
| 4 | solid | 0.204 | 5.18 | 0.150 | 3.81 | 0.50 | 12.8 | 212 | 175 |
| 2 | 7 | 0.283 | 7.19 | 0.150 | 3.81 | 0.58 | 14.8 | 290 | 230 |

All values are nominal and subject to correction

*75 °C conductor, 25 °C ambient, 2ft/sec. wind in sun

1-800-945-5542

www.PriorityWire.com



600V Generator Cable

Tray Cable UL Type TC / TC-ER-JP

APPLICATION: Multi-conductor all in one cable for connecting a generator to a transfer switch. JP (Joist Pull) rated per the 2023 NEC 336.10(9). Black jacket and color coded inner conductors.

CONSTRUCTION: Conductors: Element 1 & 3: Annealed bare 19 strand copper OR Aluminum 8000 series Class B stranded, Element 2: Annealed bare copper Class K stranded. Polyvinylchloride (PVC) & Nylon insulation. Sunlight resistant and direct burial approved PVC jacket with ripcord. All 3 Elements or Conductors are cabled together with Non-Hygroscopic Polypropylene fillers as required for a circular cross-section with a clear mylar binder tape and an overall PVC jacket.

SPECIFICATIONS: UL Listed as TC-ER-JP per UL Standard 1277. Rated 75°C wet or dry to meet UL 83 for THHN/THWN. ICEA S-73-532. Meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements. Suitable for use in Class I Division 2 hazardous locations. Element 1 & 2 conductors pass UL VW-1 flame test, rated THWN/VW-1. ASTM B3, B174, B787, B801. RoHS & REACH Compliant.

| Part Number (Rating) | Section | Conductor Size | No. of Conductors | No. of Strands | Insulation Thickness | | Nylon Thickness | | Jacket Thickness | | Overall Diameter | Weight |
|---|-----------|----------------|-------------------|----------------|----------------------|------|-----------------|------|------------------|------|------------------|-----------|
| | | AWG | | | inches | mm | inches | mm | inches | mm | inches | lbs/M-kft |
| Copper Conductors | | | | | | | | | | | | |
| 8-03TCG/18-06-VN (50 amps, 7kW-11kW) | Element 1 | 8 | 3 | 19 | 0.030 | 0.76 | 0.006 | 0.15 | - | - | - | - |
| | Element 2 | 18 | 6 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 10 | 1 | 19 | 0.048 | 1.22 | 0.004 | 0.10 | | | | |
| | Overall | - | | - | - | - | - | - | 0.060 | 1.52 | 0.65 | 363 |
| 4-03TCG/18-06-VN (85 amps, 12kW-16kW) | Element 1 | 4 | 3 | 19 | 0.040 | 1.02 | 0.007 | 0.18 | - | - | - | - |
| | Element 2 | 18 | 6 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 8 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 0.89 | 750 |
| 3-03TCG/18-06-VN (100 amps, 17kW-24kW) | Element 1 | 3 | 3 | 19 | 0.040 | 1.02 | 0.007 | 0.18 | - | - | - | - |
| | Element 2 | 18 | 6 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 8 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 0.95 | 865 |
| 3-03TCG/18-08-VN (100 amps, 17kW-24kW) | Element 1 | 3 | 3 | 19 | 0.040 | 1.02 | 0.007 | 0.18 | - | - | - | - |
| | Element 2 | 18 | 8 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 8 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 0.95 | 885 |
| 3-03TCG/18-09-VN (100 amps, 17kW-24kW) | Element 1 | 3 | 3 | 19 | 0.040 | 1.02 | 0.007 | 0.18 | - | - | - | - |
| | Element 2 | 18 | 9 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 8 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 0.98 | 903 |

All values are nominal and subject to correction

(Continued on page 48)

1-800-945-5542

www.PriorityWire.com



600V Generator Cable

Tray Cable UL Type TC / TC-ER-JP

CONTINUED

| Part Number (Rating) | Section | Conductor Size | No. of Conductors | No. of Strands | Insulation Thickness | | Nylon Thickness | | Jacket Thickness | | Overall Diameter | Weight |
|---|-----------|-------------------|----------------------|-------------------|-------------------------|------|--------------------|------|---------------------|------|---------------------|-----------|
| | | AWG | | | inches | mm | inches | mm | inches | mm | inches | lbs/M-kft |
| Copper Conductors 26kW | | | | | | | | | | | | |
| 2-03TCG/18-06-VN (115 amps, 26kW) | Element 1 | 2 | 3 | 19 | 0.040 | 1.02 | 0.007 | 0.18 | - | - | - | - |
| | Element 2 | 18 | 6 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 6 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 1.01 | 1049 |
| 2-03TCG/18-08-VN (115 amps, 26kW) | Element 1 | 2 | 3 | 19 | 0.040 | 1.02 | 0.007 | 0.18 | - | - | - | - |
| | Element 2 | 18 | 8 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 6 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 1.01 | 1060 |
| 2-03TCG/18-09-VN (115 amps, 26kW) | Element 1 | 2 | 3 | 19 | 0.040 | 1.02 | 0.007 | 0.18 | - | - | - | - |
| | Element 2 | 18 | 9 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 6 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 1.01 | 1070 |
| Aluminum & Copper Conductors | | | | | | | | | | | | |
| 1-03TCGAL/18-06-VN (100 amps, 17kW- 24kW) | Element 1 | 1 | 3 | 19 | 0.050 | 1.27 | 0.008 | 0.20 | - | - | - | - |
| | Element 2 | 18 | 6 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 6 | 1 | 7 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 1.08 | 651 |
| 1-03TCGAL/18-08-VN (100 amps, 17kW- 24kW) | Element 1 | 1 | 3 | 19 | 0.050 | 1.27 | 0.008 | 0.20 | - | - | - | - |
| | Element 2 | 18 | 8 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 6 | 1 | 7 | 0.030 | 0.76 | 0.005 | 0.13 | - | - | - | - |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 1.09 | 668 |
| 1-03TCGAL/18-09-VN (100 amps, 17kW- 24kW) | Element 1 | 1 | 3 | 19 | 0.050 | 1.27 | 0.008 | 0.20 | - | - | - | - |
| | Element 2 | 18 | 9 | 16 | 0.015 | 0.38 | 0.005 | 0.13 | - | - | - | - |
| | Element 3 | 6 | 1 | 19 | 0.030 | 0.76 | 0.005 | 0.13 | | | | |
| | Overall | - | | - | - | - | - | - | 0.080 | 2.03 | 1.09 | 675 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



Tracer Wire 30V-600V Solid Copper

APPLICATION: Tracer Wire is suitable for direct burial or use with plastic pipe to aid in the detection and tracing of underground utility lines for gas, water, sewer, and telecommunication and other systems. Made with a high density high molecular weight polyethylene insulation that has excellent abrasion, crush, chemical, oil and moisture resistance. The temperature rating is -25 °C to 75 °C.

CONSTRUCTION: Solid copper conductor. High density high molecular weight polyethylene (HDHMWPE) insulation.

SPECIFICATIONS: ASTM B3, B258, D1248, UL 2989 (not listed). RoHS Compliant.

COLOR CODE: Blue - Potable Water • Green - Sewer, Drain Lines • Purple - Reclaimed Water • Red - Electric • Orange - Communication • Yellow - Gas • Black • White

| Conductor Size | Conductor Diameter | | Wire Diameter | | Weight | Approx. Break Strength |
|-----------------------------------|--------------------|--------|---------------|--------|--------|------------------------|
| | AWG | inches | mm | inches | | |
| 45 Mil Insulation 30V/600V | | | | | | |
| 16 | 0.051 | 1.30 | 0.11 | 2.8 | 11 | 69 |
| 14 | 0.064 | 1.63 | 0.12 | 3.1 | 16 | 110 |
| 12 | 0.081 | 2.06 | 0.14 | 3.6 | 24 | 174 |
| 10 | 0.102 | 2.59 | 0.16 | 4.1 | 36 | 277 |
| 45 Mil Insulation 30V/600V | | | | | | |
| 16 | 0.051 | 1.30 | 0.11 | 2.8 | 14 | 69 |
| 14 | 0.064 | 1.63 | 0.12 | 3.1 | 19 | 110 |
| 12 | 0.081 | 2.06 | 0.14 | 3.6 | 27 | 174 |
| 10 | 0.102 | 2.59 | 0.16 | 4.1 | 39 | 277 |

All values are nominal and subject to correction

Tracer Wire 30V-600V Standard Strength (SS-CCS)

APPLICATION: Tracer Wire is suitable for direct burial or use with plastic pipe to aid in the detection and tracing of underground utility lines for gas, water, sewer, telecommunication and other systems. Made with a high density high molecular weight polyethylene insulation that has excellent abrasion, crush, chemical, oil and moisture resistance. The temperature rating is -25 °C to 75 °C.

CONSTRUCTION: Copper-clad steel conductor, standard strength, 21% conductivity. High density high molecular weight polyethylene (HDHMWPE) insulation.

SPECIFICATIONS: ASTM B910, D1248. UL 2989 (not listed). RoHS Compliant.

COLOR CODE: Blue - Potable Water • Green - Sewer, Drain Lines • Purple - Reclaimed Water • Red - Electric • Orange - Communication • Yellow - Gas • Black • White

| Conductor Size | Conductor Diameter | | Wire Diameter | | Weight | Approx. Break Strength |
|-----------------------------------|--------------------|--------|---------------|--------|--------|------------------------|
| | AWG | inches | mm | inches | | |
| 30 Mil Insulation 30V | | | | | | |
| 18 | 0.040 | 1.02 | 0.10 | 2.5 | 7 | 75 |
| 16 | 0.051 | 1.29 | 0.11 | 2.8 | 10 | 115 |
| 14 | 0.064 | 1.63 | 0.12 | 3.1 | 15 | 194 |
| 12 | 0.081 | 2.05 | 0.14 | 3.6 | 22 | 302 |
| 10 | 0.102 | 2.59 | 0.16 | 4.1 | 34 | 513 |
| 8 | 0.129 | 3.26 | 0.19 | 4.8 | 51 | 700 |
| 45 Mil Insulation 30V/600V | | | | | | |
| 18 | 0.040 | 1.02 | 0.13 | 3.3 | 9 | 75 |
| 16 | 0.051 | 1.29 | 0.14 | 3.6 | 13 | 115 |
| 14 | 0.064 | 1.63 | 0.15 | 3.8 | 18 | 194 |
| 12 | 0.081 | 2.05 | 0.17 | 4.3 | 25 | 302 |
| 10 | 0.102 | 2.59 | 0.19 | 4.8 | 37 | 513 |
| 8 | 0.129 | 3.26 | 0.22 | 5.6 | 55 | 700 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



Tracer Wire 30V-600V High Strength (HS-CCS)

APPLICATION: Made for directional drilling/boring or similar applications that require high strength. The wire is made of high strength copper clad steel conductor with a high density high molecular weight polyethylene insulation that has excellent abrasion, crush, chemical, oil and moisture resistance. Suitable for direct burial or use with plastic pipe to aid in the detection and tracing of underground utility lines for gas, water, sewer, telecommunication and other systems. The temperature rating is -25 °C to 75 °C.

CONSTRUCTION: Copper-clad steel conductor with high carbon 1055 grade steel (HS-CCS), 21% conductivity. High density high molecular weight polyethylene (HDHMWPE) insulation.

SPECIFICATIONS: ASTM B910, D1248. UL 2989 (not listed). RoHS Compliant.

COLOR CODE: Blue - Potable Water • Green - Sewer, Drain Lines • Purple - Reclaimed Water • Red - Electric • Orange - Communication • Yellow - Gas • Black • White

| Conductor Size | Conductor Diameter | | Wire Diameter | | Weight | Approx. Break Strength |
|-----------------------------------|--------------------|--------|---------------|--------|--------|------------------------|
| | AWG | inches | mm | inches | | |
| 30 Mil Insulation 30V | | | | | | |
| 18 | 0.040 | 1.02 | 0.10 | 2.5 | 7 | 110 |
| 16 | 0.051 | 1.29 | 0.11 | 2.8 | 10 | 145 |
| 14 | 0.064 | 1.63 | 0.12 | 3.1 | 15 | 285 |
| 12 | 0.081 | 2.05 | 0.14 | 3.6 | 22 | 455 |
| 10 | 0.102 | 2.59 | 0.16 | 4.1 | 34 | 685 |
| 8 | 0.129 | 3.26 | 0.19 | 4.8 | 51 | 870 |
| 45 Mil Insulation 30V/600V | | | | | | |
| 18 | 0.040 | 1.02 | 0.13 | 3.3 | 9 | 110 |
| 16 | 0.051 | 1.29 | 0.14 | 3.6 | 13 | 145 |
| 14 | 0.064 | 1.63 | 0.15 | 3.8 | 18 | 285 |
| 12 | 0.081 | 2.05 | 0.17 | 4.3 | 25 | 455 |
| 10 | 0.102 | 2.59 | 0.19 | 4.8 | 37 | 685 |
| 8 | 0.129 | 3.26 | 0.22 | 5.6 | 55 | 870 |

All values are nominal and subject to correction

Tracer Wire 30V-600V Extra High Strength (EHS-CCS)

APPLICATION: Made for directional drilling/boring or similar applications that require high strength. The wire is made of high strength copper clad steel conductor with a high density high molecular weight polyethylene insulation that has excellent abrasion, crush, chemical, oil and moisture resistance. Suitable for direct burial or use with plastic pipe to aid in the detection and tracing of underground utility lines for gas, water, sewer, telecommunication and other systems. The temperature rating is -25 °C to 75 °C.

CONSTRUCTION: Solid copper-clad steel conductor with hard drawn high carbon 1055 grade steel (EHS-CCS), 21% conductivity. High density high molecular weight polyethylene (HDHMWPE) insulation.

SPECIFICATIONS: ASTM B1010, D1248, UL 2989 (not listed). RoHS Compliant.

COLOR CODE: Blue - Potable Water • Green - Sewer, Drain Lines • Purple - Reclaimed Water • Red - Electric • Orange - Communication • Yellow - Gas • Black • White

| Conductor Size | Conductor Diameter | | Wire Diameter | | Weight | Approx. Break Strength |
|-----------------------------------|--------------------|--------|---------------|--------|--------|------------------------|
| | AWG | inches | mm | inches | | |
| 45 Mil Insulation 30V/600V | | | | | | |
| 12 | 0.081 | 2.05 | 0.17 | 4.3 | 26 | 1155 |
| 10 | 0.102 | 2.59 | 0.20 | 5.1 | 39 | 2040 |
| 8 | 0.129 | 3.26 | 0.22 | 5.6 | 61 | 2790 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



XLPE/CPE Instrumentation Cable 600V Tinned Cu Shielded Pairs/Triads UL Type TC-ER

APPLICATION: Used for power, control, signal, communication and lighting circuits in commercial and industrial environments such as utility generating stations, sub stations, chemical plants, fertilizer plants and nuclear plants. It may be installed in wet or dry locations at 90°C or in areas exposed to chemicals and oils.

CONSTRUCTION: Fully annealed tinned copper Class B stranded conductors. Flame retardant Cross-linked Polyethylene (XLPE) insulation that is heat and moisture resistant. Foil free edge Aluminum/Mylar Tape with 100% coverage and a stranded tinned copper drain wire on each pair/triad, with an overall Aluminum/Mylar Tape with 100% coverage and a stranded tinned copper drain wire in contact with the overall shield. Flame and sunlight resistant black Chlorinated Polyethylene (CPE) jacket with ripcord.

SPECIFICATIONS: UL Listed as TC-ER per standard UL 1277 for tray cables with 3+ conductors • Suitable for Class 1 Division 2 industrial hazardous locations per NEC • UL approved for Direct Burial, Sunlight and Oil I & II Resistant applications • Rated at 90°C wet or dry • Cold bend rated at -25°C • Meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements • ICEA S-73-532 • RoHS & REACH compliant

| Conductor Size AWG | Pair Count | No. of Strands | Drain Wire Pair/Cable | Insulation Thickness | | Jacket Thickness | | Overall Diameter | | Weight |
|---|------------|----------------|-----------------------|----------------------|------|------------------|------|------------------|------|---------|
| | | | AWG | inches | mm | inches | mm | inches | mm | lbs/kft |
| SPOS XLPE/CPE 600V Shielded Tray Cable | | | | | | | | | | |
| 18 | 2 | 7 | 20/18 | 0.030 | 0.76 | 0.045 | 1.14 | 0.46 | 11.8 | 97 |
| 18 | 4 | 7 | 20/18 | 0.030 | 0.76 | 0.060 | 1.52 | 0.61 | 15.4 | 171 |
| 18 | 6 | 7 | 20/18 | 0.030 | 0.76 | 0.060 | 1.52 | 0.75 | 19.0 | 242 |
| 18 | 8 | 7 | 20/18 | 0.030 | 0.76 | 0.060 | 1.52 | 0.79 | 20.0 | 238 |
| 18 | 12 | 7 | 20/18 | 0.030 | 0.76 | 0.080 | 2.03 | 0.98 | 24.8 | 458 |
| 18 | 16 | 7 | 20/18 | 0.030 | 0.76 | 0.080 | 2.03 | 1.10 | 27.8 | 574 |
| 18 | 24 | 7 | 20/18 | 0.030 | 0.76 | 0.080 | 2.03 | 1.31 | 33.2 | 814 |
| 16 | 2 | 7 | 18/16 | 0.030 | 0.76 | 0.045 | 1.14 | 0.46 | 11.8 | 119 |
| 16 | 4 | 7 | 18/16 | 0.030 | 0.76 | 0.060 | 1.52 | 0.61 | 15.4 | 220 |
| 16 | 6 | 7 | 18/16 | 0.030 | 0.76 | 0.060 | 1.52 | 0.75 | 19.0 | 315 |
| 16 | 8 | 7 | 18/16 | 0.030 | 0.76 | 0.060 | 1.52 | 0.79 | 20.0 | 391 |
| 16 | 12 | 7 | 18/16 | 0.030 | 0.76 | 0.080 | 2.03 | 0.98 | 24.8 | 591 |
| 16 | 16 | 7 | 18/16 | 0.030 | 0.76 | 0.080 | 2.03 | 1.10 | 27.8 | 753 |
| 16 | 24 | 7 | 18/16 | 0.030 | 0.76 | 0.080 | 2.03 | 1.31 | 33.2 | 1073 |

All values are nominal and subject to correction

| Conductor Size AWG | Triad Count | No. of Strands | Drain Wire Triad/Cable | Insulation Thickness | | Jacket Thickness | | Overall Diameter | | Weight |
|---|-------------|----------------|------------------------|----------------------|------|------------------|------|------------------|------|---------|
| | | | AWG | inches | mm | inches | mm | inches | mm | lbs/kft |
| STOS XLPE/CPE 600V Shielded Tray Cable | | | | | | | | | | |
| 16 | 2 | 7 | 18/16 | 0.030 | 0.76 | 0.060 | 1.52 | 0.58 | 14.8 | 178 |
| 16 | 4 | 7 | 18/16 | 0.030 | 0.76 | 0.060 | 1.52 | 0.73 | 18.4 | 299 |
| 16 | 6 | 7 | 18/16 | 0.030 | 0.76 | 0.080 | 2.03 | 0.92 | 23.4 | 464 |
| 16 | 8 | 7 | 18/16 | 0.030 | 0.76 | 0.080 | 2.03 | 1.03 | 26.3 | 586 |
| 16 | 10 | 7 | 18/16 | 0.030 | 0.76 | 0.080 | 2.03 | 1.21 | 30.7 | 708 |
| 16 | 12 | 7 | 18/16 | 0.030 | 0.76 | 0.080 | 2.03 | 1.26 | 31.9 | 827 |

All values are nominal and subject to correction

1-800-945-5542

www.PriorityWire.com



XLPE/CPE Shielded Tray Cable 600V Tinned Cu UL Type TC or TC-ER

APPLICATION: Used for power, control, signal, communication and lighting circuits in commercial and industrial environments such as utility generating stations, sub stations, chemical plants, fertilizer plants and nuclear plants. It may be installed in wet or dry locations at 90°C or in areas exposed to chemicals and oils.

CONSTRUCTION: Fully annealed tinned copper Class B stranded conductors. Flame retardant Cross-linked Polyethylene (XLPE) insulation that is heat and moisture resistant. Aluminum/Mylar Tape with 100% coverage and a stranded tinned copper drain wire. Flame and sunlight resistant black Chlorinated Polyethylene (CPE) jacket with ripcord.

SPECIFICATIONS: UL Listed as TC-ER per UL Standard 1277 for tray cables with 3+ conductors • Suitable for Class 1 Division 2 industrial hazardous locations per NEC • UL approved for Direct Burial, Sunlight and Oil I & II Resistant applications • Rated at 90°C wet or dry • Cold bend rated at -25°C • Meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements • ICEA S-73-532 • RoHS compliant

| Conductor Size AWG | No. of Conductors | No. of Strands | Drain Wire | Insulation Thickness | | Jacket Thickness | | Overall Diameter | | Weight |
|-----------------------|-------------------|----------------|------------|----------------------|------|------------------|------|------------------|-----|---------|
| | | | AWG | inches | mm | inches | mm | inches | mm | lbs/kft |
| 18 | 2 | 7 | 22 | 0.030 | 0.76 | 0.045 | 1.14 | 0.30 | 7.7 | 50 |
| 16 | 2 | 7 | 22 | 0.030 | 0.76 | 0.045 | 1.14 | 0.32 | 8.2 | 59 |
| 16 | 3 | 7 | 22 | 0.030 | 0.76 | 0.045 | 1.14 | 0.36 | 9.1 | 78 |

All values are nominal and subject to correction


1-800-945-5542

www.PriorityWire.com


Quick Turn Fiber Now Available in Standard Length Reels from Stock

ExpressLT™ Dry - Single Mode Dry Loose Tube Cable

Armored (12F-288F) and Non-Armored (12F-288F)




- MDPE Outer Jacket
- Water Blocking Tape
- MDPE Inner Jacket (Double Jacket Designs Only)
- Central Strength Member
- Outer Strength Members (where applicable)
- Dry Buffer Tube Containing up to 12 Fibers
- Ripcord
- ezPREP® Corrugated Steel Armor (optional)



Dry FusionLink™ - Single Mode Ribbon Central Tube (Dry) Cable


Armored (72F-864F)

- MDPE Outer Jacket
- Water Blocking Tape
- Ribbon Stack
- Water Blocking Tape (In tube)
- Dry Water-Blocked Buffer Tube
- Ripcord



Non-Armored (72F-432F)


- Strength Rod
- Ripcord
- Dry Water-Blocked Buffer Tube
- Ribbon Stack
- Water Blocking Tape (In tube)
- Core Water Blocking Tape
- MDPE Outer Jacket



ResiLink™ ADF

Single Mode All-dielectric Flat Drop Cable


- Strength Member
- Water-Blocking Material
- HDPE Outer Jacket
- Gel-Filled Buffer Tube (up to 24 Fibers)



ResiLink™ TF

Single Mode Toneable Flat Drop Cable

- 24 AWG Tracer Wire
- Strength Member
- Water-Blocking Material
- HDPE Outer Jacket
- Gel-Filled Buffer Tube (up to 24 Fibers)



Don't see what you are needing? Our offering is ever-expanding so contact us at Fiber@prioritywire.com with any questions or send us the spec for what you are using and we will get you answers. Scan the QR code above for more info and where you can find full spec sheets.



UTILITY PRODUCTS

ALUMINUM PRODUCTS

- Aluminum ACSR-AAC-AAAC
ACAR, ACSS, ACSS/TW
ACSS/AW, ACSR/AW
Non-specular ACSR
- Aluminum Service Drop Cable
- Tree Wire
- Spacer Cable
- Aluminum 600 Volt UD Cable
 - Ruggedized
 - 1350 & 8000 Series
- Aluminum XLP-USE (1350)
- Aluminum USE-2 (8000)
- Aluminum Tie Wire
- Aluminum MV 105 15 & 35KV
- Aluminum URD Cable 15, 25 & 35KV
- OPGW

COPPER PRODUCTS

- Riser Wire/Down Ground/Pole Ground
- Tap Wire
- Jumper Cable 5/15 KV
- EPR/CPE USE Network Underground
- Copper Overhead
- Tracer CCS (Pipeline Tracer Wire)
- 20/10 Control Cable
- Instrumentation Cable
- Tinned & Bare Copper
- Tray Cable THHN, XLPE & EPR
- PV Cable (Copper & Aluminum)
- DLO 2KV
- Connectors (Splice, Term & Lugs)
- XHHW, XLP, USE-2 Copper
- THHN Copper
- Fiber Optic Cable
- Copper MV105 5, 15, 35KV

NON-WIRE PRODUCTS

- Copper and Galvanized Ground Rods & Accessories
- Aluminum Clad Steel Wire
(6m, 8m, 10m, 12.5m, 16m, 20m)
- Guy Wire

VALUE ADDED SERVICES

- Striping
- Paralleling
- Pulling Eyes
- No Minimum
- Custom Cuts
- Same Day Shipping
- Stacking/Layering

Visit our website to sign up for our
Portal to check inventory

In U.S. 1-800-945-5542
WWW.PRIORITYWIRE.COM

In Canada 1-877-611-5122
WWW.PRIORITYWIRE.CA



When **TIME** and **EFFICIENCY**
are just as important as **PRICE** and **QUALITY** . . .

We make your business our **PRIORITY**

Millions of Square Feet of Warehouse



Multi-Millions of Dollars in Inventory

Your Inside Contact is: _____
_____ @prioritywire.com

US: 1-800-945-5542

CANADA: 1-877-611-5122

WWW.PRIORITYWIRE.COM