



Broadcast & Security Cable (18-12 AWG) Shielded CMR 60°C

Part Number	Size AWG	No. of Conductors	Min Average Thickness		Nominal Overall Diameter	Approx. Weight
			Insulation inches	Jacket inches		
18-02STR-BSC-SH	18	2	0.010	0.020	0.175	22
18-03STR-BSC-SH	18	3	0.010	0.020	0.185	29
18-04STR-BSC-SH	18	4	0.010	0.020	0.202	37
18-05STR-BSC-SH	18	5	0.010	0.020	0.221	45
18-06STR-BSC-SH	18	6	0.010	0.020	0.24	55
18-07STR-BSC-SH	18	7	0.010	0.020	0.245	60
18-08STR-BSC-SH	18	8	0.010	0.020	0.262	65
18-09STR-BSC-SH	18	9	0.010	0.020	0.283	72
16-02STR-BSC-SH	16	2	0.010	0.020	0.196	34
16-03STR-BSC-SH	16	3	0.010	0.020	0.207	45
16-04STR-BSC-SH	16	4	0.010	0.020	0.227	58
14-02STR-BSC-SH	14	2	0.010	0.020	0.248	53
14-03STR-BSC-SH	14	3	0.010	0.020	0.253	70
12-02STR-BSC-SH	12	2	0.010	0.020	0.28	68

All values are nominal and subject to correction

- Application:** Broadcast & Security Cable is suitable for use on public address systems, intercoms, audio, internal telephones, remote controls, sound circuits and burglar/security systems.
- Conductors:** Stranded soft drawn bare copper conductor. Optional solid conductor constructions are available.
- Insulation:** Color coded polyvinyl chloride (PVC) insulation.
- Shield:** Aluminum polyester shield with a tinned copper drain wire.
- Jacket:** Gray polyvinyl chloride (PVC) jacket.
- Standards:** UL type CMR & CL3R
UL 13
NEC Article 725

1-800-945-5542

© Priority Wire & Cable, Little Rock, AR PWC-2017