



Lamp Cord Type SPT • 300V • 60°C

| Part Number | Size (AWG) | No. of Conductors | Conductor Stranding (No./AWG) | Insulation Thickness (inches) | Overall Diameter (inches) | Ampacity (amps) | Weight (lbs/kft) |
|----------------|------------|-------------------|-------------------------------|-------------------------------|---------------------------|-----------------|------------------|
| SPT - 1 | | | | | | | |
| SPT1-18/2 | 18 | 2 | 41/34 | 0.030 | 0.11 x 0.22 | 10 | 20 |
| SPT1-18/3 | 18 | 3 | 41/34 | 0.030 | 0.11 x 0.33 | 10 | 30 |
| SPT - 2 | | | | | | | |
| SPT2-18/2 | 18 | 2 | 41/34 | 0.045 | 0.14 x 0.27 | 10 | 27 |
| SPT2-16/2 | 16 | 2 | 65/34 | 0.045 | 0.15 x 0.30 | 13 | 36 |
| SPT2-16/3 | 16 | 3 | 65/34 | 0.045 | 0.15 x 0.45 | 10 | 54 |
| SPT - 3 | | | | | | | |
| SPT3-16/2 | 16 | 2 | 65/34 | 0.060 | 0.18 x 0.36 | 13 | 47 |
| SPT3-14/2 | 14 | 2 | 41/30 | 0.060 | 0.20 x 0.40 | 18 | 61 |
| SPT3-14/3 | 14 | 3 | 41/30 | 0.060 | 0.20 x 0.60 | 15 | 92 |
| SPT3-12/2 | 12 | 2 | 65/30 | 0.060 | 0.22 x 0.44 | 25 | 82 |
| SPT3-12/3 | 12 | 3 | 65/30 | 0.060 | 0.22 x 0.66 | 20 | 123 |

All values are nominal and subject to correction

Application: Lamp Cord UL Type SPT is suitable for use in small appliances, lamps, radio equipment and Malibu type lighting. It is suitable for applications up to 300 volts and temperatures up to 60°C.

Conductors: Stranded soft drawn bare copper conductor.

Insulation: Premium-grade integral polyvinyl chloride (PVC) insulation over two or three conductors laid parallel. Available insulation colors: Black, Brown, White, Silver, Clear, & Gold.

Standards: UL 62/CSA 22.2 No. 49 Flexible Cords and Cables
NEC Article 400 Flexible Cords and Cables
UL / c(UL) Listed

1-800-945-5542

© Priority Wire & Cable, Little Rock, AR PWC-May 2020