



## NMLT Non-Metallic Liquid-Tight Conduit

Part Number	Internal Diameter		External Diameter		Lengths	Weight
	Min	Max	Min	Max		
	inches	inches	inches	inches	FT	lbs/100'
NML3/8-100'COIL	0.484	0.504	0.690	0.710	100	13
NML1/2-100'COIL	0.622	0.640	0.820	0.840	100	14
NML1/2-1000'RL	0.622	0.640	0.820	0.840	1000	14
NML3/4-100'COIL	0.820	0.840	1.030	1.050	100	16
NML3/4-700'REEL	0.820	0.840	1.030	1.050	100	16
NML1-100'COIL	1.041	1.066	1.290	1.315	100	26
NML1-500'RL	1.041	1.066	1.290	1.315	500	26
NML1-1/4-50'CL	1.380	1.410	1.635	1.660	50	34
NML1-1/2-50 CL	1.575	1.600	1.865	1.900	50	45
NML2-50'COIL	2.020	2.045	2.340	2.375	50	62

All values are nominal and subject to correction.

**Application:** NMLT is designed for liquid tight applications which are subject to vibration, movement, oil, and corrosives. Suitable for indoor and outdoor use such as indoor lighting, water treatment systems, and HVAC equipment.

**Construction:** One-piece construction of rigid, non-metallic reinforcement embedded in flexible PVC wall for exceptional crush and corrosion resistance. Durable, sunlight resistant and flame retardant thermoplastic PVC that resists heat, oil and chemical breakdown. Convenient markings in feet for easy measurement.

**Standards:** UL 1660, listed for direct burial applications  
 CSA approved  
 NEC Article 356  
 Sunlight and Oil resistant  
 Temperature range: -27°C to 80°C

**1-800-945-5542**