

Tray Cable UL Type TC / TC-ER – 600V

14-10 AWG THHN/THWN-2 Insulation – with Ground – PVC Jacket



APPLICATION:

Primarily used for power, control, signal, communication and lighting circuits in commercial and industrial environments. Suitable for installation in cable trays, supported by messenger wire in open air, raceways, channels, conduits and ducts. Approved for direct burial and outdoors in cable trays where sunlight resistant is required. Also may be installed in wet or dry locations or in areas exposed to chemicals and oils.

CONDUCTORS:

- Fully annealed bare copper Class B compressed strand per ASTM B-3 and ASTM B-8

INSULATION:

- Flame retardant PVC/NYLON that is heat and moisture resistant per UL 62. Insulation meets requirements of Type THHN/THWN-2 as specified by UL 83.

GROUND:

- Soft bare annealed copper per ASTM B-3, Class B stranding per ASTM B-8

COLOR CODE:

- Black insulation with ICEA Method 1, Table E-2

ICEA S-58-679 Method 1, Table E-2

Cond #	Cond Printing
1	Black
2	Red
3	Blue

ASSEMBLY:

- Conductors are cabled together with or without fillers as required to form a round, compact cable core with a binder tape.

JACKET:

- Flame and sunlight resistant black PVC rated 90°C wet or dry per UL 1277. Ripcord provided for jackets with thickness of 60 mils or less.

STANDARDS:

- UL Listed as TC-ER (Exposed Run) per UL Standard 1277 and used in accordance with NEC for 3 or more conductors.
- Approved for Class 1 or 2, Division 2 industrial hazardous locations per NEC
- Rated 90°C wet or dry to meet UL 83 for THHN/THWN-2
- Meets cold bend test at -25°C
- ICEA S-95-658, ICEA S-73-532
- UL 62, UL 66, UL 83, UL1277
- UL1685 and IEEE 383 70,000 BTU Vertical Flame Test
- UL Listed to IEEE1202 and CSA FT4 70,000 BTU Flame Test

Part Number	Conductor Size	No. of Conductors	No. of Strands	Ground Wire Size	Insulation Thickness		Nylon Thickness		Jacket Thickness		Overall Diameter	Net Weight
	AWG			AWG	inches	mm	inches	mm	inches	mm		
14-03TCG-VN	14	3	7	14	0.015	0.38	0.005	0.13	0.045	1.14	0.336	100
12-03TCG-VN	12	3	7	12	0.015	0.38	0.005	0.13	0.045	1.14	0.384	145
10-03TCG-VN	10	3	7	10	0.020	0.51	0.005	0.13	0.045	1.14	0.463	212

All values are nominal and subject to correction



1-800-945-5542
www.PriorityWire.com



©2021 Priority Wire & Cable
12-2021